

## PCT-TRS-6LMG

TRS Universal Compression Connector, Torque Retaining, Continuous Ground, Series 6 60% through Quad-Shield



<b>GENERAL SPECIFICATIONS</b>	
Bandwidth	5 MHz to 3 GHz
Impedance	75 Ohms (Nominal)
Return Loss	Minimum -30 dB to 1 GHz
Shielding Effectiveness	> -100 dB to 300 MHz, > -90 dB to 1 GHz
Insertion Loss	≤ 0.2 dB @ 1 GHz
Operating Voltage	90 V (at 60 Hz continuous AC)
Loosened Condition	Continuous ground feature maintains the ground path even in a loosened state
Operating Temperature	-40 to +140 °F (-40 to +60 °C)
Cable Range	RG6 Cable 60% through Quad-Shield
Acceptable Maximum Core Diameter (Dielectric + Tape)	0.193 in (4.91 mm)
Acceptable Minimum Jacket Diameter	0.273 in ± 0.008 in (6.93 mm ± 0.20 mm)
Acceptable Maximum Jacket Diameter	0.297 in ± 0.008 in (7.54 mm ± 0.20 mm)
Cable Retention	>60 lb. (27.21 kg.), Ambient Temperature
Cable Insertion	<15 lb. maximum insertion force, Ambient Temperature
<b>PHYSICAL CHARACTERISTICS</b>	
Length Before Compression	1.09 in (27.8 mm)
Mating Mechanism	7/16 Hex 3/8-32 UNEF Threading
Construction Material	Nickel Plated Brass
<b>TOOLING</b>	
Compression Tools *	PCT-AIO-CT, PCT-RH-CT-AS, PCT-TRS-CT, PCT-TRS-CT-AS
<b>PART NUMBER</b>	
PCT-TRS-6LMG	Compression Connector, Torque Retaining, Continuous Ground, Series 6 60% through Quad-Shield

\*This list is not all inclusive and only reflects the tooling options available by PCT International, Inc.

## PCT-TRS-6LMG

### TRS Universal Compression Connector, Torque Retaining, Continuous Ground, Series 6 60% through Quad-Shield

PARAMETER	SPECIFICATIONS REFERENCED	REQUIREMENT / PCT INTERNATIONAL SPECIFIED	RESULT
Cable Retention	ANSI/SCTE 99 2004	> 50 lbs pull force	PASS
Chemical Resistance	BLCR GR-1503-CORE 4.7	No cracking or swelling	PASS
Corrosion Resistance	BLCR GR 1503-CORE 3.2.1	1,000 hours salt spray	PASS
Tightening Torque	ANSI/SCTE 98 2004	Tightened to 60 in /lbs without damage	PASS
Insertion Loss	ANSI/SCTE 73 2007	< 0.05 dB to 350 MHz, < 0.1 dB to 700 MHz, < 0.2 dB to 1 GHz	PASS
Installation Force	ANSI/SCTE 73 2007	< 20 lbs maximum insertion	PASS
Loosening Torque	BLCR GR-1503-CORE 4.2	≥ 30 in / lbs after temperature cycling	PASS
Moisture Migration	ANSI/SCTE 60 2004	No dye penetration after 5 days of temperature cycling	PASS
Ozone Degradation	BLCR GR-1503-CORE 4.1	70 hours exposure	PASS
Return Loss	ANSI/SCTE 05 2008	> -30 dB to 1 GHz	PASS
Salt Fog	ANSI/SCTE 143 2007	> -30 dB return loss to 1 GHz	PASS
Shielding Effectiveness	ANSI/SCTE 48-1 2007 ANSI/SCTE 48-2 2008	> -100 dB to 300 MHz, > -90 dB to 1 GHz	PASS
Temperature Cycling with Humidity	BLCR GR-1503 4.1	> 50 lbs pull force after temperature cycling	PASS
UV Degradation	BLCR GR-1503-CORE 4.8	UV resistant after 7 days	PASS
Vibration	BLCR GR-1503-CORE 4.6	> 32 in / lbs loosening torque after vibration	PASS
DC Contact Resistance Outer Conductor	ANSI/SCTE 103 2004	< 5 milliohms	PASS

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Connectors](#) / [Coaxial Connectors](#) category:*

*Click to view products by [PCT manufacturer](#):*

Other Similar products are found below :

[R125315120](#) [8915-1511-000](#) [89674-0827](#) [5916-1103-603](#) [0106-001-000](#) [6-0001-3](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39012/25-0021](#) [M39012/79-3008](#) [M39030/3-01N](#) [M39030/3-03N](#) [M3933/25-29N](#) [M3933/25-36N](#) [6500-7071-046](#) [6501-1071-002](#) [M83723/72W24576](#) [M83723/72W2457N](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7003-1572-002](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7105-1521-002](#) [7145-1521-002](#) [7209-1511-011](#) [7210-1511-012](#) [7210-1511-015](#) [7210-1511-019](#) [7210-1511-040](#) [7225-1512-050](#) [7242-1511-000](#) [73137-5015](#) [73216-2241](#) [73251-0111](#) [73251-0672](#) [73276-1501](#) [73366-0013](#) [73404-2300](#) [73413-6080](#) [734151610](#)