

This document was generated on 03/27/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Status: Overview:	2 <mark>2-17-2202</mark> Active K <u>® Interconnect System - Molex</u> K® 254 PC Board Connector, Bottom Entry, 0.50µm Gold (Au), 20 Circuits	
Documents: <u>3D Model</u> Drawing (PDF)	Product Specification PS-10-07 (PDF) RoHS Certificate of Compliance (PDF)	and the second sec
Agency Certificatio	LR19980	Se image - Reference only
UL General Product Family Series Application Overview Product Name UPC	E29179 PCB Receptacles <u>4455</u> Board-to-Board, Signal <u>KK® Interconnect System - Molex</u> KK® 254 800753736917	EU RoHS ELV and RoHS Compliant REACH SVHC Not Reviewed Low-Halogen Status Low-Halogen
Physical Circuits (Loaded)	20	Need more information on product environmental compliance? Email productcompliance@molex.com
Circuits (maximum) Color - Resin Flammability	20 Natural (White) 94V-0	For a multiple part number RoHS Certificat Compliance, <u>click here</u>
Glow-Wire Compliant Guide to Mating Part Keying to Mating Part Lock to Mating Part	No No None No	Please visit the <u>Contact Us</u> section for any non-product compliance questions.
Material - Plating Mating Material - Plating Termin Material - Resin Net Weight	Gold	Search Parts in this Series 4455Series
Number of Rows Orientation PC Tail Length PCB Locator PCB Retention PCB Thickness - Recom Packaging Type	1 Bottom Entry 3.35mm No None	Mates With <u>42153</u> KK® Wire-to-Board Header, <u>4094</u> KK® Wire-to-Board Header, <u>42376</u> KK® Header, <u>42375</u> KK® Header, <u>42377</u> , <u>422</u> KK® Wire-to-Board Header, <u>4030</u> KK® Wire-to-Board Header, <u>4380</u> KK® Heade
Pitch - Mating Interface Pitch - Termination Interf Plating min - Mating Plating min - Termination Polarized to PCB Surface Mount Compatik Temperature Range - Op Termination Interface: St	2.54mm face 2.54mm 0.508μm 0.051μm No ble (SMC) No perating See Product Specification	

2.5A

250V

No

5

Electrical

Current - Maximum per Contact Grounding to PCB Voltage - Maximum

Solder Process Data

Duration at Max. Process Temperature (seconds)

Lead-free Process Capability	Wave Capable (TH only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	235
Material Info Old Part Number	A-4455-BH20D(565)

Reference - Drawing Numbers Product Specification

Sales Drawing

PS-10-07 SDA-4455

This document was generated on 03/27/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 891-007-9SS-BST1T 000-34000 0008550134 0009482033 0009507031 57102-F02-18ULF 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 CSU011177004 636-1427 638009-1 641938-9 641991-4 644168-1 644827-2 647662-1 65039-019ELF 65692-001LF 65781-018 65781-047