


## Product Data Sheet Type: PR32/50,8/SE


Group: HEATSINKS Board Level

For single mounting

Width : 35 mm  
 Height : 12.7 mm  
 Length : 50.8 mm  
 Minimum thermal resistance : 9 K/W  
 For device : TO 220|TO 218|TOP 3|TO  
 Device mounted by : Screw  
 Heatsink mounted by : Solder  
 Surface : Black Anodised  
 Material : AlMgSi0,5



- Special extruded heatsink for semiconductor case TO220, TO202, TO218(TOP3)
- Aluminium, anodised black, solderable
- Standard heights: 25.4, 38.1 and 50.8 mm
- 2 x 3.2 mm holes for semiconductor assembly
- Heatsink solderable by tin plated solder pins



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Heat Sinks](#) category:*

*Click to view products by [Alutronic](#) manufacturer:*

Other Similar products are found below :

[581102B00000G](#) [630-35ABT3](#) [656-15ABPE](#) [657-20ABPNE](#) [73452PPBA](#) [7721-13NG](#) [7G0011A](#) [FI306/SE](#) [PF720G](#) [A22-4026](#) [120-1873-007](#) [HAH10L](#) [1542256-2](#) [1542026-1](#) [1542616-1](#) [HS-2506-F1](#) [HS-87M0-F2](#) [218-40CTE3](#) [25-7520](#) [188854F00000G](#) [F-QB-F1](#) [APA501-60-003](#) [253-122ABE-22](#) [PSC22CB](#) [CLP-201](#) [CLP212SG](#) [CLP-7701G](#) [HAA072](#) [HAA083](#) [HAF10L](#) [HAQ10T](#) [D10100-28](#) [TO5-002D](#) [513101B02500G](#) [BDN183CBA01](#) [531202B0000](#) [HS-56M0-C1](#) [3-21053-4](#) [TX0506-1B](#) [TX1806B](#) [336614B-00000](#) [V2004X](#) [LAE66A3CB](#) [WA-DT2-101E](#) [511-3U](#) [017177](#) [530510B00000G](#) [6110BG](#) [73381PPBA](#) [73403PPBA](#)