

# Non-Contact Phase Sequence Tester

**Checks phase sequence and phase status**

*Tests up to 1000VAC with LED and audible indication*

## Features:

- 75 to 1000VAC input voltage with 45 to 65Hz frequency range
- LEDs indicate phase orientation (clockwise or counter-clockwise) and whether each phase is live
- Beeper sounds intermittently when correct phase is detected and continuously if phase is reversed
- Durable housing with back cover magnet for attachment to an AC distribution panel for easy measurement
- Adjustable Hi/Lo LED brightness switch for making measurements in dimly lit areas or sunlight
- Fully insulated alligator clips with wide jaws
- Low battery warning
- CAT IV-600V safety rating
- Dimensions: 4.7 x 2.7 x 1.5" (118 x 69 x 38mm); Weight: 13oz (370g)
- Complete with three built-in 30" test leads with large color-coded alligator clips, four AA batteries, and pouch case



## Ordering Information:

PRT200 .....Non-Contact Phase Sequence Tester



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Component Testers](#) category:*

*Click to view products by [Extech](#) manufacturer:*

Other Similar products are found below :

[FLUKE 9062](#) [N3302A](#) [N3304A](#) [570A](#) [ET30B](#) [ET40B](#) [1301270009](#) [ET26B](#) [ET23B](#) [ET38](#) [ET25](#) [ET60](#) [ET28B](#) [ET20B](#) [1301270007](#) [35135](#)  
[C.A 6608](#) [C.A 6609](#) [FLUKE-9040EUR](#) [881](#) [3239635](#) [575](#) [575A](#) [8600](#) [ET15](#) [ET10](#) [LCR200](#) [LCR203](#) [LCR205](#) [PRT200](#) [RT50](#) [35100](#)  
[1301270003](#) [1301270005](#) [1212598](#) [PRM-5](#) [T3EL15060P](#) [T3EL50015P](#)