




## Heyco® Nylon Hose Clamps


EFFECTIVE CLAMP RANGE				PART NO.			DESCRIPTION	PART DIMENSIONS				
Minimum Diameter		Maximum Diameter		6/6 NYLON		GF*		A		B		
in.	mm.	in.	mm.	Black	White	Black		in.	mm.	in.	mm.	
<b>Regular Style</b>												
.25	6,4	.31	7,9	—	—	<b>2302</b>	HC 250	.13	3,2	.04	1,0	
.34	8,7	.41	10,3	<b>2306</b>	<b>2307</b>	<b>2308</b>	HC 344	.21	5,3	.07	1,8	
.41	10,3	.47	11,9	<b>2310</b>	<b>2311</b>	<b>2312</b>	HC 406					
.47	11,9	.53	13,5	<b>2314</b>	<b>2315</b>	<b>2316</b>	HC 468					
.53	13,5	.59	15,1	<b>2318</b>	<b>2319</b>	<b>2320</b>	HC 531					
.59	15,1	.66	16,7	<b>2322</b>	<b>2323</b>	<b>2324</b>	HC 593					
.67	17,1	.81	20,6	<b>2326</b>	<b>2327</b>	<b>2328</b>	HC 672					
.75	19,1	.88	22,2	<b>2330</b>	<b>2331</b>	<b>2332</b>	HC 750					
.88	22,2	1.00	25,4	<b>2334</b>	<b>2335</b>	<b>2336</b>	HC 875					
.95	21,2	1.09	26,2	<b>2338</b>	<b>2339</b>	<b>2340</b>	HC 953					
1.03	26,2	1.19	30,2	<b>2342</b>	<b>2343</b>	<b>2344</b>	HC 1031					
1.25	31,8	1.44	36,5	<b>2346</b>	<b>2347</b>	<b>2348</b>	HC 1250					
1.41	35,7	1.63	41,3	<b>2350</b>	<b>2351</b>	<b>2352</b>	HC 1406	.36	9,1			
1.59	15,1	1.81	46,0	<b>2354</b>	<b>2355</b>	<b>2356</b>	HC 1593					
1.69	42,9	1.91	48,4	<b>2358</b>	<b>2359</b>	<b>2360</b>	HC 1687					
1.88	47,6	2.13	54,0	<b>2362</b>	<b>2363</b>	<b>2364</b>	HC 1875	.40	10,2			
2.13	54,0	2.38	60,3	<b>2366</b>	<b>2367</b>	<b>2368</b>	HC 2.125					
<b>Strap Mate Style</b>												
1.94	49,2	2.28	57,9	-	-	<b>2374</b>	HC 1930	.44	11,2	.08	2,0	
2.25	57,1	2.88	73,0	-	-	<b>2377</b>	HC 2.25					
2.75	69,8	3.63	92,1	-	-	<b>2380</b>	HC 2.75					
3.50	88,9	4.25	108,0	-	-	<b>2383</b>	HC 3.5					
4.00	101,6	5.00	127,0	-	-	<b>2386</b>	HC 4.0					

Standard colors 6/6 nylon black and white. Glass filled nylon standard color is black.

\* HC 250 features a single tang design in glass-filled nylon only.



Regular Style



Strap Mate Style

## Heyco® Pneumatic Air Tool for Nylon Hose Clamps

For Lockit and Regular Style Hose Clamp only

AIR TOOL PART NO. INCLUDING JAWS	JAW PART NO.*	
	Upper	Lower
<b>0170</b>	<b>0T83</b>	<b>0T84</b>

\*Jaw Part No. if purchased separately.



- Allows for a **semi-automated process** which increases speed over manual tools.
- Activated by hand lever reducing stress on the hand and the risk of carpal tunnel syndrome associated with repetitive assembly.
- Maximum Pressure Rating: 125 psi
- Adjustable jaws allow tool to accommodate a wide range of Heyco Hose Clamps.
- Operates only when lever is depressed.
- Tool operates on standard shop air.

Quick Specs

Materials	Nylon 6/6 or glass-filled Nylon
Flammability Rating	94V-2 for 6/6 Nylon, 94HB for glass-filled Nylon
Temperature Range	32°F (0°C) to 221°F(105°C)