



Heyco® Vent Plugs

Mounting Hole Diameter Range: .500" (12,7 mm) to 4.000" (101,6 mm)

- Permit the passage of air for ventilation and heat dissipation.
- Quick and easy installation with only fingertip pressure.
- Convex, matte finish head tapers to a thin edge.
- VP-500 through VP-875 have .094" (2,4 mm) diameter vent holes. All other sizes have .125" (3,2 mm) diameter vents.
- Lock firmly into panel up to .250" (6,4 mm) thick.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Multiple sizes for use in .500" (12,7 mm) to 4.000" (101,6 mm) diameter holes.
- Approximate Head Thickness: .062" (1,6 mm). Thickness may vary.
- Heyco Louvered Plugs available, see page 12.

MOUNTING HOLE DIAMETER		PART NO.		DESCRIPTION	No. of Vent Holes	PART DIMENSIONS			
in.	mm.	Black	White			A Head Diameter		B Overall Height	
						in.	mm.	in.	mm.


Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)

.500	12,7	2637	2638	VP 500	4	.560	14,2	.406	10,3
.562	14,3	2647	-	VP 562	4	.656	16,7		
.625	15,9	2657	2658	VP 625	5	.734	18,7		
.750	19,1	2677	2678	VP 750	8	.906	23,0		
.812	20,6	2688	2689	VP 812	8	.890	22,6	.453	11,5
.875	22,2	2697	2698	VP 875	9	1.015	25,8		
1.000	25,4	2707	2708	VP 1000	9	1.203	30,6		
1.093 - 1.125	27,8 - 28,6	2726	2727	VP 1093	9	1.218	30,9		
1.187	30,1	2736	2737	VP 1187	10	1.312	33,3		
1.250	31,7	2743	2744	VP 1250	10	1.375	34,9		
		2797	-	SVP 1250-4	4				
1.375	34,9	2756	2757	VP 1375	11	1.500	38,1		
1.500	38,1	2766	2767	VP 1500	13	1.671	42,4		
1.750	44,5	2776	2777	VP 1750	13	1.906	48,4		
2.000	50,8	2786	2787	VP 2000	19	2.140	54,4	.468	11,9

Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)

2.500	63,5	2793	2794	VP 2.5	19	2.718	69,0	.750	19,1
3.000	76,2	2458	2459	VP 3.0	26	3.150	80,0	.740	18,8
3.500	88,9	2467	2468	VP 3.5	38	3.656	92,9	.750	19,1
4.000	101,6	2476	2477	VP 4.0	48	4.156	105,6		

Standard color black. Consult Heyco for other colors.



Quick Specs

Material
Certifications

Nylon 6/6

Recognized under the Component Program of Underwriters' Laboratories, File E51579

Certified by Canadian Standards Association, File 8919

Flammability Rating
Temperature Rating

94V-2

-40°F (-40°C) to 221°F (105°C)