

ACLD Screw Termination Boards

Features

General

- Low-cost universal screw termination boards
- Blank pads accommodate applications such as break detection, low-pass filter, current shunt and voltage attenuator on ACLD-9881-01, ACLD-9178-01, ACLD-9188-01, ACLD-9138-01, and ACLD-8125-01
- Table-top mounting using nylon standoffs

ACLD-9881-01⁽¹⁾

General-Purpose Termination Board with One 37-pin D-sub Connector for PCI-9113A and ACL-8113A

- For use with PCI-9113A and ACL-8113
- Onboard 37-pin D-sub female connector
- Reliable screw clamp termination blocks
- Mating Cables:
 - ACL-10137-1MM: 37-Pin D-sub male/male Cable, 1 M
- Dimensions: 222 mm x 105 mm

ACLD-9188-01⁽¹⁾

General-Purpose Termination Board with Two 20-pin Ribbon Connectors and One 37-pin D-sub Connector

- Onboard 20-pin ribbon male connector x 2
- Onboard 37-pin D-sub female connector
- Reliable screw clamp termination blocks
- Mating Cable:
 - ACL-10120-1: 20-Pin Flat Cable, 1 M
- Dimensions: 222 mm x 114 mm

ACLD-9138-01⁽¹⁾

General-Purpose Termination Board with one 37-pin D-sub Connector

- Onboard 37-pin D-sub female connector
- Blank RC circuits for analog input boards
- Reliable screw clamp termination blocks
- Mating Cable:
 - ACL-10237-1: 37-Pin D-sub male/male flat Cable, 1 M
- Dimensions: 103 mm x 114 mm

ACLD-9137-01/ACLD-9137F-01

General-Purpose Termination Board with one 37-pin D-sub Connector

- ACLD-9137: onboard 37-pin D-sub male connector
- ACLD-9137F: onboard 37-pin D-sub female connector
- Reliable screw clamp termination blocks
- Mating Cables:
 - ACL-10137-1MM: 37-Pin D-sub male/male Cable, 1 M
 - ACL-10137-1MF: 37-Pin D-sub male/female Cable, 1 M (ACLD-9137-01)
- Dimensions: 124 mm x 72 mm

ACLD-8125-01⁽¹⁾

Termination Board with one 37-pin D-sub Connector and One Cold Junction Temperature Sensor

- One onboard temperature sensor for cold-junction compensation
- Jumper configurable sensor outputs in either DI or SE mode
- Onboard calibration for the temperature sensor
- Onboard 37-pin D-sub female connector
- Reliable screw clamp termination blocks
- Mating Cables:
 - ACL-10137-1MM: 37-Pin D-sub male/male Cable, 1 M
- Dimensions: 168 mm x 114 mm

TB-6201-01/6221-01/6231-01⁽¹⁾

General-Purpose/Multiplexer/Matrix switch termination board with one 62-pin D-sub connector


- Termination board for PXI-7901/7921/7931
- Onboard connector type: 62-pin D-sub female
- Mating Cable:
 - ACL-10262: 62-Pin D-sub male/female cable
- Reliable screw clamp termination blocks
- Dimensions: 105.81 mm x 2.30 mm

Note: (1) Cables are not included.

ACLD-9881-01



ACLD-9188-01




ACLD-9138-01




ACLD-9137-01/ACLD-9137F-01



ACLD-8125-01



TB-6201-01



Ordering Information

- | | |
|---|--|
| <ul style="list-style-type: none"> ■ ACLD-9881-01
General-Purpose Termination Board with one 37-pin D-sub Connector ■ ACLD-9188-01
General-Purpose Termination Board with Two 20-pin Ribbon Connectors and One 37-pin D-sub Connector ■ ACLD-9138-01
General-Purpose Termination Board with one 37-pin D-sub Connector ■ ACLD-9137-01
General-Purpose Termination Board with one 37-pin D-sub Male Connector ■ ACLD-9137F-01
General-Purpose Termination Board with one 37-pin D-sub Female Connector | <ul style="list-style-type: none"> ■ ACLD-8125-01
Termination Board with one 37-pin D-sub Connector and One Cold Junction Temperature Sensor ■ TB-6201-01
General-Purpose Switch Termination Board with one 62-Pin D-Sub Female Connector ■ TB-6221-01
Multiplexer Switch Termination Board with one 62-Pin D-Sub Female Connector ■ TB-6231-01
Matrix Switch Termination Board with one 62-Pin D-Sub Female Connector |
|---|--|

- 1 Software Solutions
- 2 PXI/CompactPCI Platforms
- 3 Modular Instrument
- 4 PXI/CompactPCI Modules
- 5 Bus Interface
- 6 GPIB Interface
- 7 PCI/PCI Express[®] DAQ Cards
- 8 PCI/PCI Express[®] DIO Cards
- 9 PC/104-Plus Modules
- 10 ISA DAS/DIO Cards
- 11 System Product
- 12 Wiring Termination Boards
- 13 Motion, HSL, Vision, COM & GEME
- 14 Remote I/O Modules
- 15 Industrial Computers