


**SPECIFICATIONS**

**Material:** HEXSEALS: Silicone rubber conforms to A-A-59588 Class III, GR 50 (unless otherwise specified)  
**Mounting Nut:** HEXSEALS: Brass, nickel-plated  
**Temperature Range:** HEXSEALS: -94°F to +400°F  
**Pressure Range:** Exceeds 15 psi internal and 1500 psi external.  
**Operational Life:** 30,000 actuations (minimum).  
**Shelf Life:** Excess of 25 years.  
**Resistant to:** Salt spray, sunlight, ozone, weather, fungus, and most acids and lubricating oils  
**Agency Recognition:** E-SEELS and HEXSEALS are UL-listed to UL Std. 50 types 1-13, and meet CSA standards.  
**Installation:** If a reducing adaptor is required - see page 14 of HEXSEAL catalog HEX200 for part numbers and drawing.



O	REDRAWN and MAT'L CHANGED	S.GOK	05-14-09
N	CAD COMPUTER GENERATED		9-23-02
M	MAT'L. NUT WAS ALUMINUM	NICK	8-27-69
L	ALUM. SPEC. WAS QQ-A22-15A	NICK	8-9-69
K	REDRAWN, ADDED SPECS, CORRECT BOOT AND ADAPTER P/N CALLOUT	NICK	1-13-67
REV.	DESCRIPTION		DATE
MAXIMUM AND MINIMUM MEASUREMENTS ARE STATED DIRECTLY ON EACH DIMENSION. MAT'L: SILICONE RUBBER A-A-59588 CLIII GR50 FINISH: TRANSPARENT CLEAR	BOOT, INDICATOR AND LIGHTED PUSHBUTTON (4080) APM-HEXSEAL CORPORATION	ENG. M.M.	12-15-59
		DWN. ANDREWS	12-15-59
		CHKD. B.G.	12-15-59
	SCALE 2:1	DWG. NO. (4080) HEXSEAL®	

THIS DRAWING COVERS PROPRIETARY ITEM AND IS THE PROPERTY OF THE APM-HEXSEAL CORPORATION.  
 THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE WRITTEN APPROVAL OF AN OFFICER OF THE APM-HEXSEAL CORPORATION.