



SEALRIB SILICONE RUBBER PER ZZ-R-765, CLII GRADE 70 RED *

NOTES: DIMENSIONS ARE IN INCHES - TOLERANCES ARE AS SHOWN

NOM SIZE	F	H	T	C	RECOMMEND MAX CLEARANCE HOLE DIA FOR SCREW OF BOLT
0	$5/32^{+.000}_{-.010}$	3/64	.005	5/64	.070
1	5/32	3/64	.006	3/32	.081
2	3/16	1/16	.007	1/8	.096
3	3/16	1/16	.008	9/64	.110
4	1/4	3/32	.010	5/32	.123
5	5/16	7/64	.010	11/64	.140
6	5/16	7/64	.012	3/16	.149
8	11/32	1/8	.012	7/32	.177
10	$3/8^{+.000}_{-.010}$	1/8	1/64	17/64	.201
12	$7/16^{+.000}_{-.015}$	5/32	1/64	19/64	.227
1/4	7/16	7/32	1/64	11/32	.266
5/16	1/2	17/64	1/64	13/32	.332
3/8	9/16	21/34	1/64	31/64	.397
7/16	11/16	3/8	1/64	9/16	.468
1/2	3/4	7/16	1/32	21/32	.531
9/16	7/8	31/64	1/32	23/32	.594
5/8	15/16	35/64	1/32	13/16	.656
3/4	1 1/8	41/64	1/32	31/32	.781
7/8	1 5/16	3/4	1/32	1 1/8	.906
1	$1\ 1/2^{+.000}_{-.031}$	55/64	3/64	1 19/64	1.031

* FOR OTHER MATERIALS & METRIC SIZES - CONSULT FACTORY

G	CAD COMPUTER GENERATED	12-23-02
F	REDRAWN, REVISED; DWG WAS "A" SIZE	R.O.R 1-28-77
REV.	DESCRIPTION	DATE
	SEELNUT ®	9-16-53
	APM-HEXSEAL CORPORATION	3100/1

MAXIMUM AND MINIMUM MEASUREMENTS ARE STATED DIRECTLY ON EACH DIMENSION.

MAT'L: TO BE SPECIFIED

FINISH:

ENG. DWN. J. PALUMBO

CHKD.

SCALE

DWG. NO. 3100/1

THIS DRAWING COVERS PROPRIETARY ITEM AND IS THE PROPERTY OF THE APM-HEXSEAL CORPORATION. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE WRITTEN APPROVAL OF AN OFFICER OF THE APM-HEXSEAL CORPORATION.