Crystal Units
Surface Mount Type CX3225SB

KYOCERA

3.2×2.5mm for Consumer Products/ Mobile Communications/ Automotive



RoHS Compliant

Features

- Crystal unit for Consumer Products
- Miniature and low profile (3.2×2.5×0.55mm)
- Ceramic package
- Reflow compatible
- AEC-Q200 qualified
  (Please contact us for Automotive use)

Applications

- Digital Electronics
- Consumer Products
- Car Electronics
- Mobile Communications, Bluetooth®, Wireless LAN

* Bluetooth® Trademarks are owned by Bluetooth SIG Inc.

How to Order

CX3225SB 12000 □□ □ □ □ □ □□

① ② ③ ④ ⑤ ⑥ ⑦

① Series
② Frequency
③ Load Capacitance
④ Frequency Tolerance

D0	8 pF	G	±15×10⁻⁶

⑤ Operating Temp. Range ⑥ Frequency Temp. Stability

EJ	−10 to +70°C	±15×10⁻⁶
LJ	−30 to +85°C	±15×10⁻⁶
SS	−40 to +125°C	±50×10⁻⁶

⑦ Individual Specification

Packaging (Tape & Reel 1000/ 3000 pcs./ reel)

Specifications

Item	Symbol	Specification			Units	Remarks
Frequency Range	f_nom	12000 to 54000			kHz	
Overtone Order	OT	Fundamental			—	
Load Capacitance	CL	8			pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f_tol	±15			×10⁻⁶	25°C±3°C
Motional Series Resistance	R1	Table 1			ohm	
Drive Level	DL	Table 2			µW	
Operating Temp. Range	T_use	−10 to +70	−30 to +85	−40 to +125	°C	
Storage Temp. Range	T_stg	−40 to +85		−40 to +125	°C	
Frequency Temp. Characteristics	f_tem	±15		±50	×10⁻⁶	Freq. deviation from the value at 25°C

Please contact us for other specifications.

Table1 Motional Series Resistance

Frequency Range	Motional Series Resistance
12000≤f_nom<13000kHz	150Ω max.
13000≤f_nom<20000kHz	80Ω max.
20000≤f_nom≤54000kHz	50Ω max.

Table2 Level of Drive

Frequency Range	Level of Drive
12000≤f_nom≤54000kHz	10µW (100µW max.)

Dimensions

(Unit: mm)



Recommended Land Pattern

(Unit: mm)