



REVISIONS			
REV	ECN, ERN NO.	DATE	APPRD.
B	PRODUCT DRAWING (EAR 13733)	JUL05/10	K.L.

MOUNTING CODE 2, 4 OR 6  
 .120 [3.05], #4-40 OR M3 THREAD  
 THROUGH HOLES (4 PLACES).  
 SEE ORDERING CODE.

MOUNTING CODE E  
 #4-40 UNC THREADED  
 HEX JACK SOCKET  
 (4 SUPPLIED LOOSE  
 PER CONNECTOR)

ORDERING CODE: F C E 1 7 - X A S A S - X X X 0

SERIES

VERTICAL MOUNTING DIMENSION  
 BETWEEN CONNECTORS  
 1=.625 [15.88]  
 2=.750 [19.05]

UPPER CONNECTOR SIZE/STYLE  
 AS=15 SOCKET

LOWER CONNECTOR SIZE/STYLE  
 AS=15 SOCKET

MOUNTING  
 2=.120 [3.05] DIA HOLES ON FLANGES  
 4=#4-40 UNC THREAD ON FLANGES  
 6=M3x0.5 THREAD ON FLANGES  
 E=CODE 4 MOUNTING WITH #4-40 UNC  
 HEX JACK SOCKET SUPPLIED.

MODIFIER  
 0=STANDARD

LOWER CONNECTOR FILTER  
 CAPACITANCE  
 FOR CAPACITANCE CODES, SEE  
 UPPER CONNECTOR LIST BELOW.

UPPER CONNECTOR FILTER  
 CAPACITANCE

D=50 pF	5=1000 pF
B=100 pF	7=1200 pF
O=180 pF	6=1300 pF
T=220 pF	J=1500 pF
F=330 pF	E=2200 pF
L=380 pF	9=5600 pF
1=470 pF	8=47000 pF
2=680 pF	N=NO FILTERS
4=820 pF	

REFER TO AMPHENOL  
 CATALOGUE FOR FILTER  
 PERFORMANCE CHARACTERISTICS



- NOTES:
- MATERIALS: ALL MATERIALS ARE RoHS COMPLIANT
    - SHELLS: STEEL, TIN PLATED
    - CONTACTS: PHOSPHOR BRONZE PLATED WITH 15µ" [0.38 MICRONS] GOLD OVER 50µ" [1.27 MICRONS] MINIMUM NICKEL IN THE MATING AREA AND 100µ" [2.54 MICRONS] MINIMUM MATTE TIN ON THE TAILS.
    - INSULATOR: ENGINEERING THERMOPLASTIC, UL FLAMMABILITY RATING 94V-0, COLOUR: BLACK
    - BRACKETS: ZINC DIECAST, NICKEL PLATED
    - BOARDLOCKS: COPPER ALLOY, MATTE TIN PLATED

VERTICAL MOUNTING DIMENSION (SEE ORDERING CODE)		
DIM'N	CODE 1	CODE 2
A	.625 [15.88]	.750 [19.05]
B	1.122 [28.50]	1.247 [31.67]

DRAWN I.SPRAGGS	DATE FEB06/07
DESIGNED	
CHECKED K.LAMBIE	FEB06/07
I. E. APPRD.	
Q. A. APPRD.	
DWG. APPRD.	
ENG. REL. NO.	
REF. EAR 13042	
DIMENSIONS ARE IN INCHES [mm]	CODE ID. NO. 03554

Amphenol Canada Corp.	
FCE17 FILTERED STACKED D-SUB CONNECTOR, 15 SIZE SOCKET OVER 15 SIZE SOCKET, BRACKET WITH BOARDLOCK, RoHS COMPLIANT	
DWG C	DRAWING NO. P-FCE17-XASAS-XXX0
REV. B	
SCALE 3/1	WT. -----
SURF. -----	SHEET 1 OF 1

LOCATE HOLES  
 Ⓢ Ⓢ.005 [0.13]  
 POSITION  
 DIMENSIONS ARE  
 BASIC

RECOMMENDED P.C.B. LAYOUT  
 (COMPONENT SIDE OF BOARD)

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.