

# Serial Modem Data Splitters

**9PMDS, 232MDS** 



### **PRODUCT FEATURES**


- Computers & terminals use one modem without switching
- Connect two PCs to one peripheral
- Use with modems, scanners, scales, other serial devices
- · Quick plug-and-play installation no configuration required
- May be left permanently installed

With B&B Electronics' serial port splitters you gain reliability by capturing data from one peripheral on redundant PCs. These serial RS-232 splitters can improve a system's economy by sharing multiple PCs on a single peripheral,

Model **9PMDS** connects two computers or terminals to one modem without switching. The modem data splitter can combine two 9-pin DTE ports to one 9-pin DCE port.

Model **232MDS** can be connected so two computers or terminals can use one modem without switching. This modem data splitter can combine two 25-pin DTE ports and connect them to a 25-pin DCE port.

## MECHANICAL DIAGRAM - 9PMDS



## **ORDERING INFORMATION**

MODEL NUMBER	PC PORTS	PERIPHERAL PORTS
9PMDS	(2) DB9 Female	(1) DB9 Male
232MDS	(2) DB25 Female	(1) DB25 Male

#### **ACCESSORIES**

**9PAMF6** - DB9 Male To DB9 Female, 6 ft. (1.8 m) **232CAM** - DB9 Female to DB25 Male, 6 ft. (1.8 m) **232CAMS** - DB9 Female to DB25 Male, 6 in (15.2 cm)

232AMF5 - DB25 Male to DB25 Female, 6 ft. (1.8 m)

## **SPECIFICATIONS**

C. 2011 10/41 10 110			
SERIAL TECHNOLOGY			
RS-232			
9PMDS - Connectors	Straight Through Ports: (2) DB9 Female Monitoring Port: (1) DB9 Male		
232MDS - Connectors	Straight Through Ports: (2) DB25 Female Monitoring Port: (1) DB25 Male		
Installation	In-line		
MECHANICAL			
Weight	9PMDS: 81.7 grams (0.18 lbs) 232MDS: 176.9 grams (0.39 lbs)		
ENVIRONMENTAL			
Operating Temperature	0 to +70 °C (+32 to +185 °F)		
Storage Temperature	-40 to +85 °C (-40 to +185 °F)		
Operating Humidity	0 to 95% Non-Condensing		
MTBF	9PMDS: 2595488 232MDS: 1133093		
MTBF Calc. Method	Parts Count Reliability Prediction		
APPROVALS / CERTIFICATIONS - 9PMDS, 232MDS			
FCC Part 15, CISPR, EN 55022: 2010 + AC:2011 Class A Emissions			
CE			
EN 61000-6-1: 2007 Generic Standards for Residential, Commercial and Light- Industrial Environments			

Download complete Declaration of Conformity at www.bb.elec.com