


S505SCH

5 x 20 mm Time-delay, high I²t, axial lead, ceramic tube fuses



Product description

- Time-delay, high breaking capacity
- High I²t
- Nickel-plated brass end cap construction
- 5 x 20mm physical size
- Halogen free, lead free, RoHS compliant

Applications

Primary circuit protection:

- Power supplies
- LED lighting
- LED/LCD televisions
- Appliances and white goods
- Printers

Agency information

- cURus Recognition file number: E19180, Guide JDYX2/JDYX8
- CQC: 14012118443, 14012118444
- KC-Mark: File SU05030-14002
- TUV: R50294952

Ordering

- Specify packaging prefix and part number as shown

Packaging prefix
BK/

Part number
S505SCH-1-R

Packaging prefixes

- BK/20 parts in a carrier, 5 carriers in a box
- TR2/1500 parts per reel, tape width 52mm
- TR3/1500 parts per reel, tape width 54mm

Electrical characteristics

I _n	1.5I _n min minute	2.1I _n max minute	2.75I _n min ms	max s	4I _n min ms	max s	10I _n min ms	max ms
3.15A	60	30	750	80	95	5	10	150
5A-6.3A	60	30	750	80	150	5	10	150

Product specifications

Part number ⁵	Voltage rating AC	Interrupting rating at rated voltage (50 Hz) AC ¹ (amps)	Typical DC cold resistance (Ω) ²	Typical pre-arcing I ² t (A ² s) ³	Typical voltage drop (mV) ⁴	cURus	KC	CQC	TUV
S505SCH-3.15-R	250	1500	0.017	120	67	x	x	x	x
S505SCH-5-R	250	1500	0.014	160	90	x	x	x	x
S505SCH-6.3-R	250	1500	0.010	330	85	x	x	x	x


- 1 Interrupting ratings 1A to 10A were measured at 70% to 80% PF on AC.
- 2 Typical DC cold resistance measured at <10% of rated current .
- 3. Typical I²t value is measured at 10 times the rated current under DC.

- 4. Typical voltage drop is measured at 20°C ambient temperature at rated current .
- 5. Part number definition: S505SCH-xxx-R
S505 = Product code
SCH = Single cap- high I²t
xxx = Ampere rating
-R = RoHS compliant


Dimensions—mm

A


BK: 38.1±0.38
TR2: 15.0 typ
TR3: 16.0 typ




Time vs. current curve




I²t vs. current curve



I²t vs. time curve



Temperature derating curve



Environmental data

Operating temperature: -55°C to 125°C (with derating)


Thermal shock: MIL-STD- 202G, Method 107G, test condition B (5 cycles - 65°C to 125°C)

Vibration: MIL-STD- 202G, method 201A

Humidity: MIL-STD- 202G, method 103B, test condition A

Salt spray: MIL-STD- 202G, method 101E, test condition B

Wave solder profile



Reference EN 61760-1:2006

Profile Feature	Standard SnPb Solder	Lead (Pb) Free Solder
Preheat	• Temperature min. (T_{smin})	100°C
	• Temperature typ. (T_{styp})	120°C
	• Temperature max. (T_{smax})	130°C
	• Time (T_{smin} to T_{smax}) (t_s)	70 seconds
Δ preheat to max Temperature	150°C max.	150°C max.
Peak temperature (T_p)*	235°C – 260°C	250°C – 260°C
Time at peak temperature (t_p)	10 seconds max 5 seconds max each wave	10 seconds max 5 seconds max each wave
Ramp-down rate	~ 2 K/s min ~3.5 K/s typ ~5 K/s max	~ 2 K/s min ~3.5 K/s typ ~5 K/s max
Time 25°C to 25°C	4 minutes	4 minutes

Manual solder

350°C, 4-5 seconds. (by soldering iron), generally manual, hand soldering is not recommended.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
www.eaton.com/elx

© 2015 Eaton
All Rights Reserved
Printed in USA
Publication No. 10401 BU-SB15188
May 2015



Eaton is a registered trademark.
All other trademarks are property of their respective owners.