

# LRG-Series

## ILLUMINATED DOUBLE POLE ROCKER & PADDLE SWITCHES

The double pole lighted version of the R-Series incorporates the same sleek lines as the original Corvette, in a double pole envelope. This illuminated version features silver-plated butt-action contacts with ratings to 20A/125, 15A 250VAC and withstand peak inrush currents up to 100 amps. Clear or translucent style rocker actuators and a choice of solder lug, .250 Tab and wire lead terminations enable this switch to adapt to high current applications.



### Product Highlights:

- ◆ Ratings to 20A
- ◆ Neon or Incandescent Illumination
- ◆ Silver Plated Butt-contact mechanism
- ◆ Clear or translucent style rockers

### Typical Applications:

- ◆ Power Supply
- ◆ Appliance
- ◆ Exercise Equipment
- ◆ Music Equipment



### Dielectric Strength

UL/CSA:  
1000V - live to dead metal parts &  
opposite polarity

### Electrical Life

50,000 cycles

### Mechanical Life

100,000 cycles

### Operating Temperature

-40°F to 185°F (-40°C to 85°C)



<b>1 BASE PART NUMBER: SERIES / CIRCUITRY / RATING 1 / TERMINATION</b>			
15A 250 VAC, 20A 125 VAC, 3/4 HP 125-250 VAC			
	Solder Lugs	.250 Tabs	Wire Leads
<b>Standard Base</b>			
OFF-NONE-ON	LRGSK610	LRGSK611	LRGSK615
<b>European Base</b> (22 x 30 mm cutout)			
OFF-NONE-ON (Single Pole)	LRGSEK610	LRGSEK611	LRGSEK615
<b>15A 6-24 V</b> 3			
<b>Standard Base</b>			
OFF-NONE-ON	LRGSK510	LRGSK511	LRGSK515
<b>European Base</b> (22 x 30 mm cutout)			
OFF-NONE-ON (Single Pole)	LRGSEK510	LRGSEK511	LRGSEK515

<b>2 ACTUATOR STYLE</b>			
<b>R</b>	Rocker (translucent)	<b>C</b>	Rocker (clear)

<b>3 ACTUATOR COLOR</b>			
<b>A</b>	Amber	<b>L</b> 3	Lime Green
<b>B</b> 3,5	Blue	<b>P</b>	Yellow
<b>C</b> 4	White/Clear	<b>R</b>	Red (clear)
<b>G</b> 5	Green	<b>S</b>	Red
		<b>W</b>	Pale Red

<b>4 BEZEL COLOR 1</b>			
<b>B</b>	Black	<b>W</b>	White



  

<b>5 ROCKER LEGEND</b>			
		<b>hot stamp</b>	
NO LEGEND		<b>0</b>	
OFF-ON vertical		<b>A</b>	
OFF-ON horizontal		<b>B</b>	
O-I horizontal		<b>D</b>	
O-I vertical		<b>E</b>	
Dual OFF-ON, O-I vertical		<b>H</b>	
Dual OFF-ON, O-I horizontal		<b>J</b>	

<b>6 LAMP VOLTAGE 2</b>			
<b>006V</b>	6V incandescent	<b>024V</b>	24V incandescent
<b>012V</b>	12V incandescent	<b>125N</b>	125V neon
<b>018V</b>	18V incandescent	<b>250N</b>	250V neon

Notes:  
 1 Additional ratings, colors and clear style actuators are available. Consult factory.  
 2 Incandescent lamps must specify 15A 24V rating only.  
 3 Available with incandescent lamps only.  
 4 Clear color provided where specified with clear style rocker.  
 5 Available with clear style rocker only.



\*Manufacturer reserves the right to change product specification without prior notice.

## Authorized Sales Representatives and Distributors

Click on a region of the map below to find your local representatives and distributors or visit [www.carlingtech.com/findarep](http://www.carlingtech.com/findarep).



## About Carling

Founded in 1920, Carling Technologies is a leading manufacturer of electrical and electronic switches and assemblies, circuit breakers, electronic controls, power distribution units, and multiplexed power distribution systems. With four ISO registered manufacturing facilities and technical sales offices worldwide, Carling Technologies Sales, Service and Engineering teams do much more than manufacture electrical components, they engineer powerful solutions! To learn more about Carling please visit [www.carlingtech.com/company-profile](http://www.carlingtech.com/company-profile).

To view all of Carling's environmental, quality, health & safety certifications please visit [www.carlingtech.com/environmental-certifications](http://www.carlingtech.com/environmental-certifications)

## **Worldwide Headquarters**

Carling Technologies, Inc.  
60 Johnson Avenue, Plainville, CT 06062  
**Phone:** 860.793.9281 **Fax:** 860.793.9231  
**Email:** sales@carlingtech.com

**Northern Region Sales Office:** nrsm@carlingtech.com  
**Southeast Region Sales Office:** sersm@carlingtech.com  
**Midwest Region Sales Office:** mrrsm@carlingtech.com  
**West Region Sales Office:** wrsm@carlingtech.com  
**Latin America Sales Office:** larsm@carlingtech.com

## **Asia-Pacific Headquarters**

Carling Technologies, Asia-Pacific Ltd.,  
Suite 1607, 16/F Tower 2, The Gateway,  
Harbour City, 25 Canton Road,  
Tsimshatsui, Kowloon, Hong Kong  
**Phone:** Int + 852-2737-2277 **Fax:** Int + 852-2736-9332  
**Email:** sales@carlingtech.com.hk

**Shenzhen, China:** shenzhen@carlingtech.com  
**Shanghai, China:** shanghai@carlingtech.com  
**Pune, India:** india@carlingtech.com  
**Kaohsiung, Taiwan:** taiwan@carlingtech.com  
**Yokohama, Japan:** japan@carlingtech.com

## **Europe | Middle East | Africa Headquarters**

Carling Technologies LTD  
4 Airport Business Park, Exeter Airport,  
Clyst Honiton, Exeter, Devon, EX5 2UL, UK  
**Phone:** Int + 44 1392.364422 **Fax:** Int + 44 1392.364477  
**Email:** ltd.sales@carlingtech.com

**Germany:** gmbh@carlingtech.com  
**France:** sas@carlingtech.com



**Carling Technologies®**

Innovative Designs. Powerful Solutions.