

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

2N5306
2N5308

NPN SILICON
DARLINGTON TRANSISTOR

JEDEC TO-92 CASE (ECB)

DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N5306, 2N5308 types are NPN Silicon Epitaxial Planar Darlington Transistors designed for high gain amplifier applications.

MAXIMUM RATINGS (T_A = 25°C)

	SYMBOL	2N5306	2N5308	UNITS
Collector-Base Voltage	V _{CB0}	25	40	V
Collector-Emitter Voltage	V _{CEO}	25	40	V
Emitter-Base Voltage	V _{EBO}		12	V
Continuous Collector Current	I _C		300	mA
Peak Collector Current	I _{CM}		500	mA
Continuous Base Current	I _B		50	mA
Power Dissipation	P _D		625	mW
Power Dissipation (T _C = 25°C)	P _D		1.5	W
Operating and Storage				
Junction Temperature	T _J , T _{stg}	-65 to +150		°C
Thermal Resistance	θ _{JA}	200		°C/W
Thermal Resistance	θ _{JC}	83.3		°C/W

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	2N5306		2N5308		UNITS
		MIN	MAX	MIN	MAX	
I _{CBO}	V _{CB} = Rated V _{CB0}		100		100	nA
I _{CBO}	V _{CB} = Rated V _{CB0} , T _A = 100°C		20		20	µA
I _{EBO}	V _{EB} = 12V		100		100	nA
BV _{CB0}	I _C = 100nA	25		40		V
BV _{CEO}	I _C = 10mA	25		40		V
BV _{EBO}	I _E = 100nA	12		12		V
V _{CE(SAT)}	I _C = 200mA, I _B = 0.2mA		1.4		1.4	V
V _{BE(SAT)}	I _C = 200mA, I _B = 0.2mA		1.6		1.6	V
V _{BE(ON)}	V _{CE} = 5.0V, I _C = 200mA		1.5		1.5	V
h _{FE}	V _{CE} = 5.0V, I _C = 2.0mA	7K	70K	7K	70K	
h _{FE}	V _{CE} = 5.0V, I _C = 100mA	20K		20K		

(Continued on Reverse Side)

ELECTRICAL CHARACTERISTICS (Continued)

<u>SYMBOL</u>	<u>TEST CONDITIONS</u>	<u>MIN</u>	<u>TYP</u>	<u>MAX</u>	<u>UNITS</u>
h_{fe}	$V_{CE} = 5.0V, I_C = 2.0mA, f = 1.0kHz$	7K			
$ h_{fe} $	$V_{CE} = 5.0V, I_C = 2.0mA, f = 10MHz$	15.6			dB
f_T	$V_{CE} = 5.0V, I_C = 2.0mA, f = 10MHz$	60			MHz
h_{ie}	$V_{CE} = 5.0V, I_C = 2.0mA, f = 1.0kHz$		650		k Ω
C_{cb}	$V_{CB} = 10V, f = 1.0MHz$			10	pF
C_{eb}	$V_{EB} = 0.5V, f = 1.0MHz$		12		pF

Central[™]
Semiconductor Corp.

145 Adams Avenue
Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824
www.centrasemi.com

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms