

CMR3-02 CMR3-08
 CMR3-04 CMR3-10
 CMR3-06 CMR3-11

**SURFACE MOUNT SILICON
 GENERAL PURPOSE RECTIFIERS
 3.0 AMP, 200 THRU 1100 VOLT**



www.centrasemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMR3-02 series 3.0 Amp surface mount silicon rectifiers are highly reliable components designed for use in all types of commercial, industrial, entertainment, computer, and automotive applications. To order devices on 16mm Tape and Reel (3000/13" Reel), add TR13 suffix to part number.



SMC CASE

MARKING CODE: SEE MARKING CODE TABLE ON FOLLOWING PAGE

FEATURES:

- High reliability
- Glass passivated chip
- Special selections available
- "C" bend construction provides strain relief when mounted on PC board

MAXIMUM RATINGS: ($T_A=25^\circ\text{C}$ unless otherwise noted)

| | | CMR3 -02 | CMR3 -04 | CMR3 -06 | CMR3 -08 | CMR3 -10 | CMR3 -11 | UNITS |
|--|----------------|-------------|-------------|-------------|-------------|-------------|-------------|--------------------|
| Peak Repetitive Reverse Voltage | V_{RRM} | 200 | 400 | 600 | 800 | 1000 | 1100 | V |
| DC Blocking Voltage | V_R | 200 | 400 | 600 | 800 | 1000 | 1100 | V |
| RMS Reverse Voltage | $V_{R(RMS)}$ | 140 | 280 | 420 | 560 | 700 | 770 | V |
| Average Forward Current ($T_A=75^\circ\text{C}$) | I_O | | | | 3.0 | | | A |
| Peak Forward Surge Current, $t_p=8.3\text{ms}$ | I_{FSM} | | | | 200 | | | A |
| Operating and Storage Junction Temperature | T_J, T_{stg} | | | | -65 to +175 | | | $^\circ\text{C}$ |
| Thermal Resistance | θ_{JL} | | | | 10 | | | $^\circ\text{C/W}$ |

ELECTRICAL CHARACTERISTICS: ($T_A=25^\circ\text{C}$ unless otherwise noted)


| SYMBOL | TEST CONDITIONS | MIN | MAX | UNITS |
|--------|--|-----|-----|---------------|
| I_R | $V_R=\text{Rated } V_{RRM}$ | | 5.0 | μA |
| I_R | $V_R=\text{Rated } V_{RRM}, T_A=125^\circ\text{C}$ | | 250 | μA |
| V_F | $I_F=3.0\text{A}$ | | 1.2 | V |

CMR3-02 CMR3-08
 CMR3-04 CMR3-10
 CMR3-06 CMR3-11



**SURFACE MOUNT SILICON
 GENERAL PURPOSE RECTIFIERS
 3.0 AMP, 200 THRU 1100 VOLT**

SMC CASE - MECHANICAL OUTLINE



| DEVICE | MARKING CODE |
|---------|--------------|
| CMR3-02 | C302 |
| CMR3-04 | C304 |
| CMR3-06 | C306 |
| CMR3-08 | C308 |
| CMR3-10 | C310 |
| CMR3-11 | C311 |

| SYMBOL | INCHES | | MILLIMETERS | |
|--------|--------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | 0.030 | 0.060 | 0.76 | 1.52 |
| B | 0.002 | 0.008 | 0.05 | 0.20 |
| C | 0.305 | 0.320 | 7.75 | 8.13 |
| D | 0.006 | 0.012 | 0.15 | 0.31 |
| E | 0.079 | 0.103 | 2.00 | 2.62 |
| F | 0.260 | 0.280 | 6.60 | 7.11 |
| G | 0.108 | 0.128 | 2.75 | 3.25 |
| H | 0.220 | 0.245 | 5.59 | 6.22 |

SMC (REV: R2)

R5 (11-September 2013)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centalsemi.com

Worldwide Field Representatives:
www.centalsemi.com/wwreps

Worldwide Distributors:
www.centalsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centalsemi.com/terms