


Central Semiconductor Corp.  
**Central Semiconductor Corp.**  
**Central Semiconductor Corp.**  
 145 Adams Avenue  
 Hauppauge, New York 11788



1N4454

SILICON SWITCHING DIODE

JEDEC DO-35 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 1N4454 type is a high speed Silicon Switching Diode designed for computer and general purpose applications.

MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ )

	<u>SYMBOL</u>		<u>UNITS</u>
Peak Repetitive Reverse Voltage	$V_{RRM}$	75	V
Average Forward Current	$I_O$	150	mA
Forward Steady-State Current	$I_F$	200	mA
Peak Forward Surge Current (1.0 $\mu\text{s}$ pulse)	$I_{FSM}$	4000	mA
Power Dissipation	$P_D$	500	mW
Operating and Storage Junction Temperature	$T_J, T_{stg}$	-65 to +200	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

<u>SYMBOL</u>	<u>TEST CONDITIONS</u>	<u>MIN</u>	<u>MAX</u>	<u>UNITS</u>
$BV_R$	$I_R = 5.0\mu\text{A}$	75		V
$I_R$	$V_R = 50\text{V}$		100	nA
$I_R$	$V_R = 50\text{V}, T_A = 150^\circ\text{C}$		100	$\mu\text{A}$
$V_F$	$I_F = 10\text{mA}$		1.0	V
$C_T$	$V_r = 0, f = 1.0\text{MHz}$		2.0	pF
$t_{rr}$	$V_R = 6.0\text{V}, I_F = 10\text{mA}, I_{rr} = 1.0\text{mA}, R_L = 100\Omega$		2.0	ns
$t_{rr}$	$I_F = I_R = 10\text{mA}, I_{rr} = 1.0\text{mA}$		4.0	ns

**Central**<sup>TM</sup>  
**Semiconductor Corp.**

145 Adams Avenue  
 Hauppauge, NY 11788 USA  
 Tel: (631) 435-1110 • Fax: (631) 435-1824  
 www.centrasemi.com

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centalsemi.com](http://www.centalsemi.com)

**Worldwide Field Representatives:**  
[www.centalsemi.com/wwreps](http://www.centalsemi.com/wwreps)

**Worldwide Distributors:**  
[www.centalsemi.com/wwdistributors](http://www.centalsemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centalsemi.com/terms](http://www.centalsemi.com/terms)