




# Power Inductors – DR0608 Series



- Small footprint power inductors designed for maximum efficiency and low cost.
- Ideal for noise filtering in power amplifiers, power supplies and speaker crossover networks.
- Inductance values from 3.3 to 1000  $\mu\text{H}$ , most at 10% tolerance
- Current ratings up to 6.4 Amps with only 0.012 Ohms DCR
- Industry-standard pin spacings; protective PVC sleeve

**Core material** Ferrite

**Terminations** RoHS compliant tin-silver over copper

**Weight:** 1.0 – 1.3 g

**Ambient temperature**  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$  with  $I_{\text{rms}}$  current,  $+85^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$  with derated current

**Storage temperature** Component:  $-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ .

Tray packaging:  $-40^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at  $<30^{\circ}\text{C}$  / 85% relative humidity)

**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

**Packaging** 300 parts per tray; 1200 parts in optional fan-fold tape

**PCB washing** Tested with pure water or alcohol only. For other solvents, see Doc787\_PCB\_Washing.pdf

| Part number | Inductance <sup>1</sup><br>( $\mu\text{H}$ ) | DCR max<br>(Ohms) | SRF typ <sup>2</sup><br>(MHz) | Isat (A) <sup>3</sup> |          |          | Irms (A) <sup>4</sup> |           |
|-------------|--|-------------------|-------------------------------|-----------------------|----------|----------|-----------------------|-----------|
|             |  |                   |                               | 10% drop              | 20% drop | 30% drop | 20°C rise             | 40°C rise |
| DR0608-332L | 3.3 $\pm 20\%$                               | 0.012             | 40                            | 5.3                   | 6.1      | 6.4      | 5.0                   | 7.5       |
| DR0608-472L | 4.7 $\pm 20\%$                               | 0.018             | 36                            | 4.6                   | 5.4      | 5.8      | 4.6                   | 6.9       |
| DR0608-562L | 5.6 $\pm 20\%$                               | 0.022             | 32                            | 4.6                   | 5.2      | 5.5      | 4.2                   | 6.3       |
| DR0608-682L | 6.8 $\pm 20\%$                               | 0.025             | 30                            | 3.9                   | 4.5      | 4.8      | 3.8                   | 5.7       |
| DR0608-822L | 8.2 $\pm 20\%$                               | 0.028             | 25                            | 3.6                   | 4.1      | 4.4      | 3.4                   | 5.1       |
| DR0608-103L | 10 $\pm 10\%$                                | 0.035             | 23                            | 3.2                   | 3.6      | 4.0      | 3.0                   | 4.5       |
| DR0608-123L | 12 $\pm 10\%$                                | 0.045             | 20                            | 2.8                   | 3.2      | 3.5      | 2.8                   | 4.2       |
| DR0608-153L | 15 $\pm 10\%$                                | 0.052             | 19                            | 2.7                   | 3.0      | 3.2      | 2.7                   | 4.0       |
| DR0608-183L | 18 $\pm 10\%$                                | 0.065             | 17                            | 2.4                   | 2.7      | 2.9      | 2.5                   | 3.7       |
| DR0608-223L | 22 $\pm 10\%$                                | 0.078             | 16                            | 2.1                   | 2.5      | 2.7      | 2.3                   | 3.4       |
| DR0608-273L | 27 $\pm 10\%$                                | 0.086             | 12                            | 1.9                   | 2.2      | 2.4      | 2.2                   | 3.2       |
| DR0608-333L | 33 $\pm 10\%$                                | 0.12              | 11                            | 1.7                   | 2.0      | 2.2      | 2.0                   | 2.9       |
| DR0608-393L | 39 $\pm 10\%$                                | 0.13              | 10                            | 1.6                   | 1.9      | 2.0      | 1.8                   | 2.6       |
| DR0608-473L | 47 $\pm 10\%$                                | 0.16              | 9.5                           | 1.4                   | 1.7      | 1.8      | 1.7                   | 2.4       |
| DR0608-563L | 56 $\pm 10\%$                                | 0.19              | 9.0                           | 1.3                   | 1.5      | 1.7      | 1.5                   | 2.1       |
| DR0608-683L | 68 $\pm 10\%$                                | 0.25              | 9.0                           | 1.3                   | 1.4      | 1.5      | 1.3                   | 1.8       |
| DR0608-823L | 82 $\pm 10\%$                                | 0.28              | 7.0                           | 1.2                   | 1.3      | 1.4      | 1.2                   | 1.6       |
| DR0608-104L | 100 $\pm 10\%$                               | 0.38              | 6.5                           | 1.0                   | 1.2      | 1.3      | 1.0                   | 1.3       |
| DR0608-124L | 120 $\pm 10\%$                               | 0.42              | 6.0                           | 0.96                  | 1.0      | 1.1      | 0.94                  | 1.23      |
| DR0608-154L | 150 $\pm 10\%$                               | 0.50              | 5.5                           | 0.83                  | 0.93     | 1.0      | 0.88                  | 1.15      |
| DR0608-184L | 180 $\pm 10\%$                               | 0.65              | 5.0                           | 0.76                  | 0.85     | 0.93     | 0.82                  | 1.08      |
| DR0608-224L | 220 $\pm 10\%$                               | 0.73              | 4.8                           | 0.73                  | 0.83     | 0.89     | 0.76                  | 1.00      |
| DR0608-274L | 270 $\pm 10\%$                               | 0.96              | 4.0                           | 0.69                  | 0.77     | 0.82     | 0.70                  | 0.93      |
| DR0608-334L | 330 $\pm 10\%$                               | 1.11              | 3.7                           | 0.60                  | 0.68     | 0.72     | 0.64                  | 0.85      |
| DR0608-394L | 390 $\pm 10\%$                               | 1.25              | 3.0                           | 0.59                  | 0.66     | 0.70     | 0.58                  | 0.78      |
| DR0608-474L | 470 $\pm 10\%$                               | 1.60              | 2.8                           | 0.50                  | 0.56     | 0.61     | 0.52                  | 0.70      |
| DR0608-564L | 560 $\pm 10\%$                               | 1.85              | 2.5                           | 0.47                  | 0.53     | 0.56     | 0.46                  | 0.63      |
| DR0608-684L | 680 $\pm 10\%$                               | 2.40              | 2.5                           | 0.43                  | 0.48     | 0.51     | 0.40                  | 0.55      |
| DR0608-824L | 820 $\pm 10\%$                               | 2.70              | 2.1                           | 0.40                  | 0.45     | 0.48     | 0.34                  | 0.48      |
| DR0608-105L | 1000 $\pm 10\%$                              | 3.00              | 2.1                           | 0.35                  | 0.40     | 0.43     | 0.30                  | 0.40      |

1. To order parts packaged in optional fanfold tape (1200 parts per box), add the letter "F" at the end of the part number, e.g. DR0608-824LF

2. Inductance tested at 100 kHz, 0.1 Vrms, 0 Adc on an Agilent/HP 4284A LCR-meter or equivalent.

3. SRF measured using an Agilent/HP 4191A or equivalent.

4. DC current at which the inductance drops the specified amount from its value without current

5. Current that causes the specified temperature rise from 25°C ambient.

6. Electrical specifications at 25°C.



www.coilcraft.com

**US** +1-847-639-6400 sales@coilcraft.com

**UK** +44-1236-730595 sales@coilcraft-europe.com

**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw

**China** +86-21-6218 8074 sales@coilcraft.com.cn

**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 275-1 Revised 05/14/13


© Coilcraft Inc. 2013

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.





# Power Inductors - DR0608 Series

## Typical L vs Frequency



## Typical L vs Current



Dimensions are in  $\frac{\text{inches}}{\text{mm}}$



www.coilcraft.com

**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 275-2 Revised 05/14/13

© Coilcraft Inc. 2013

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.