

# Ordering Information Radial-Leaded Dipped Mica Capacitors

## Ordering Information

Order by complete part number as below. For other options, write your requirements on your purchase order or request for quotation.

**Note: RoHS compliant not available for CD6, CD7 or MIL-C5 parts.**

## Radial-Leaded Silvered Mica Capacitors (Except D7, D10\*)

<b>CD15</b> Series	<b>C</b> Characteristic Code	<b>D</b> Voltage (Vdc)	<b>100</b> Capacitance (pF)	<b>J</b> Capacitance Tolerance	<b>O</b> Temperature Range	<b>3</b> Vibration Grade	<b>F</b> Blank = Not Specified F = RoHS Compliant																						
		Y = 50 Vdc A = 100 Vdc C = 300 Vdc D = 500 Vdc	F = 1000 Vdc H = 1500 Vdc J = 2000 Vdc K = 2500 Vdc	010 = 1 pF (1.5) = 1.5 pF 361 = 360 pF 122 = 1200 pF	O = -55 °C to +125 °C P = -55 °C to +150 °C	<b>Vibration Grade</b>																							
<b>Characteristics</b>																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Code</th> <th style="text-align: center;">Temp. Coeff. ppm/ °C</th> <th style="text-align: center;">Capacitance Drift</th> <th style="text-align: center;">Standard Cap. Range</th> </tr> </thead> <tbody> <tr> <td>C</td> <td style="text-align: center;">-200 to +200</td> <td style="text-align: center;">±(0.5% +0.1pF)</td> <td style="text-align: center;">1–18 pF</td> </tr> <tr> <td>E</td> <td style="text-align: center;">-20 to +100</td> <td style="text-align: center;">±(0.1% +0.1 pF)</td> <td style="text-align: center;">20–82 pF</td> </tr> <tr> <td>F</td> <td style="text-align: center;">0 to +70</td> <td style="text-align: center;">±(0.05% +0.1 pF)</td> <td style="text-align: center;">91 pF and up</td> </tr> </tbody> </table>	Code	Temp. Coeff. ppm/ °C	Capacitance Drift	Standard Cap. Range	C	-200 to +200	±(0.5% +0.1pF)	1–18 pF	E	-20 to +100	±(0.1% +0.1 pF)	20–82 pF	F	0 to +70	±(0.05% +0.1 pF)	91 pF and up				<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">MIL-STD-202</th> <th style="text-align: center;">Vibration Condition (Hz)</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">Method 201</td> <td style="text-align: center;">10 to 55</td> </tr> <tr> <td style="text-align: center;">3</td> <td style="text-align: center;">Method 204 Condition D</td> <td style="text-align: center;">10 to 2,000</td> </tr> </tbody> </table>	No.	MIL-STD-202	Vibration Condition (Hz)	1	Method 201	10 to 55	3	Method 204 Condition D	10 to 2,000
Code	Temp. Coeff. ppm/ °C	Capacitance Drift	Standard Cap. Range																										
C	-200 to +200	±(0.5% +0.1pF)	1–18 pF																										
E	-20 to +100	±(0.1% +0.1 pF)	20–82 pF																										
F	0 to +70	±(0.05% +0.1 pF)	91 pF and up																										
No.	MIL-STD-202	Vibration Condition (Hz)																											
1	Method 201	10 to 55																											
3	Method 204 Condition D	10 to 2,000																											
				Standard vibration grade is 3, the more severe requirement																									

## Options Available

- ◆ Non-flammable units per IEC 695-2-2 are available for standard dipped capacitors. Specify IEC 695-2-2 on your order.
- ◆ Tape and reeling, specify per next page.
- ◆ “P” temperature range available for CD10, CD15, CD19, CD30, CD42, CDA15
- ◆ For MIL-C-5 capacitors, see below.

## MIL-C-5 Capacitors

Capacitors are available marked and manufactured to the requirements of standard MIL-C-5. To order the MIL-C-5 part number, change the Catalog Number by

CDE Type Number	MIL-C-5 Style Number	
CD10	CM04	CM09
CD15	CM05	CM10
CD19	CM06	CM11
CD30	CM07	CM12

### Capacitance Tolerance

Tol. Code	Tolerance	Capacitance Range
C	±1 pF	1– 9 pF
D	±1/2 pF	1–99 pF
E	±1/2 %	100 pF and up
F	±1 %	50 pF and up
G	±2 %	25 pF and up
H	±3 %	18 pF and up
J	±5 %	10 pF and up

Standard tolerance is ±1/2 pF for less than 10 pF and ±5% for 10 pF and up

replacing the CDE type with the MIL-C-5 Style Number using the table below. Example: Change CD15ED470J03 to CM05ED470J03.

The following ratings have no MIL-C-5 equivalents:

Type CD10: 2, 3, 4, 50, 250 and 400 pF

Type CD15: 2, 3, 4, 50, 250, 430 and higher pF

Type CD19: 390 and lower pF, 2,500 pF, and 5000 and higher pF

Type CD30: 5,000 and lower pF, 33,000 and higher pF

\* Order Type D7 and D10 using the Catalog Numbers shown in the ratings tables.