


Features

- 500mW Power Dissipation
- High Stability
- Surface Mount Equivalents Available
- Hermetic Package
- Vz - Tolerance $\pm 5\%$
- Lead Free Finish, RoHS Compliant (Note 2)

Mechanical Data

- Case: DO-35
- Case Material: Glass
- Moisture Sensitivity: Level 1 per J-STD-020
- Leads: Solderable per MIL-STD-202, Method 208
- Terminals: Finish - Sn96.5Ag3.5. Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band
- Marking: Type Number
- Weight: 0.13 grams (approximate)



| DO-35 | | |
|----------------------|-------|------|
| Dim | Min | Max |
| A | 25.40 | — |
| B | — | 4.00 |
| C | — | 0.60 |
| D | — | 2.00 |
| All Dimensions in mm | | |

Maximum Ratings and Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

| Characteristic | Symbol | Value | Unit |
|--|-----------------|-------------|---------------------------|
| Power Dissipation (Note 1) | P_D | 500 | mW |
| Thermal Resistance, Junction to Ambient Air (Note 1) | $R_{\theta JA}$ | 300 | $^\circ\text{C}/\text{W}$ |
| Forward Voltage @ $I_F = 200\text{mA}$ | V_F | 1.1 | V |
| Operating and Storage Temperature Range | T_J, T_{STG} | -65 to +200 | $^\circ\text{C}$ |

- Notes:
1. Valid provided that leads are kept at $T_L \leq 75^\circ\text{C}$ with lead length = 9.5mm (3/8") from case; derate above 75°C .
 2. EU Directive 2002/95/EC (RoHS). All applicable RoHS exemptions applied, see EU Directive 2002/95/EC Annex Notes.



**NOT RECOMMENDED FOR
NEW DESIGN, USE
MMSZ52xxB**

Electrical Characteristics

@T_A = 25°C unless otherwise specified

Table 1

| Type Number | Zener Voltage Range (Note 3) | | | Test Current | Maximum Zener Impedance | | Maximum Reverse Current | | Maximum Temperature Coefficient @ I _{ZT} |
|-------------|----------------------------------|---------|---------|-----------------|-----------------------------------|--|-------------------------|-----------------|---|
| | V _Z @ I _{ZT} | | | I _{ZT} | Z _{ZT} @ I _{ZT} | Z _{ZK} @ I _{ZK} = 0.25mA | I _R | @V _R | |
| | Nom (V) | Min (V) | Max (V) | mA | Ω | Ω | μA | V | |
| 1N5221B | 2.4 | 2.28 | 2.52 | 20 | 30 | 1200 | 100 | 1.0 | -0.085 |
| 1N5222B | 2.5 | 2.38 | 2.63 | 20 | 30 | 1250 | 100 | 1.0 | -0.085 |
| 1N5223B | 2.7 | 2.57 | 2.84 | 20 | 30 | 1300 | 75 | 1.0 | -0.080 |
| 1N5224B | 2.8 | 2.66 | 2.94 | 20 | 30 | 1400 | 75 | 1.0 | -0.080 |
| 1N5225B | 3.0 | 2.85 | 3.15 | 20 | 29 | 1600 | 50 | 1.0 | -0.075 |
| 1N5226B | 3.3 | 3.14 | 3.47 | 20 | 28 | 1600 | 25 | 1.0 | -0.070 |
| 1N5227B | 3.6 | 3.42 | 3.78 | 20 | 24 | 1700 | 15 | 1.0 | -0.065 |
| 1N5228B | 3.9 | 3.71 | 4.10 | 20 | 23 | 1900 | 10 | 1.0 | -0.060 |
| 1N5229B | 4.3 | 4.09 | 4.52 | 20 | 22 | 2000 | 5.0 | 1.0 | +0.055 |
| 1N5230B | 4.7 | 4.47 | 4.94 | 20 | 19 | 1900 | 5.0 | 2.0 | +0.030 |
| 1N5231B | 5.1 | 4.85 | 5.36 | 20 | 17 | 1600 | 5.0 | 2.0 | +0.030 |
| 1N5232B | 5.6 | 5.32 | 5.88 | 20 | 11 | 1600 | 5.0 | 3.0 | +0.038 |
| 1N5233B | 6.0 | 5.70 | 6.30 | 20 | 7.0 | 1600 | 5.0 | 3.5 | +0.038 |
| 1N5234B | 6.2 | 5.89 | 6.51 | 20 | 7.0 | 1000 | 5.0 | 4.0 | +0.045 |
| 1N5235B | 6.8 | 6.46 | 7.14 | 20 | 5.0 | 750 | 3.0 | 5.0 | +0.050 |
| 1N5236B | 7.5 | 7.13 | 7.88 | 20 | 6.0 | 500 | 3.0 | 6.0 | +0.058 |
| 1N5237B | 8.2 | 7.79 | 8.61 | 20 | 8.0 | 500 | 3.0 | 6.5 | +0.062 |
| 1N5238B | 8.7 | 8.27 | 9.14 | 20 | 8.0 | 600 | 3.0 | 6.5 | +0.065 |
| 1N5239B | 9.1 | 8.65 | 9.56 | 20 | 10 | 600 | 3.0 | 7.0 | +0.068 |
| 1N5240B | 10 | 9.50 | 10.50 | 20 | 17 | 600 | 3.0 | 8.0 | +0.075 |
| 1N5241B | 11 | 10.45 | 11.55 | 20 | 22 | 600 | 2.0 | 8.4 | +0.076 |
| 1N5242B | 12 | 11.40 | 12.60 | 20 | 30 | 600 | 1.0 | 9.1 | +0.077 |
| 1N5243B | 13 | 12.35 | 13.65 | 9.5 | 13 | 600 | 0.5 | 9.9 | +0.079 |
| 1N5244B | 14 | 13.30 | 14.70 | 9.0 | 15 | 600 | 0.1 | 10 | +0.082 |
| 1N5245B | 15 | 14.25 | 15.75 | 8.5 | 16 | 600 | 0.1 | 11 | +0.082 |
| 1N5246B | 16 | 15.20 | 16.80 | 7.8 | 17 | 600 | 0.1 | 12 | +0.083 |
| 1N5247B | 17 | 16.15 | 17.85 | 7.4 | 19 | 600 | 0.1 | 13 | +0.084 |
| 1N5248B | 18 | 17.10 | 18.90 | 7.0 | 21 | 600 | 0.1 | 14 | +0.085 |
| 1N5249B | 19 | 18.05 | 19.95 | 6.6 | 23 | 600 | 0.1 | 14 | +0.086 |
| 1N5250B | 20 | 19.00 | 21.00 | 6.2 | 25 | 600 | 0.1 | 15 | +0.086 |
| 1N5251B | 22 | 20.90 | 23.10 | 5.6 | 29 | 600 | 0.1 | 17 | +0.087 |
| 1N5252B | 24 | 22.80 | 25.20 | 5.2 | 33 | 600 | 0.1 | 18 | +0.087 |
| 1N5253B | 25 | 23.75 | 26.25 | 5.0 | 35 | 600 | 0.1 | 19 | +0.089 |
| 1N5254B | 27 | 25.65 | 28.35 | 4.6 | 41 | 600 | 0.1 | 21 | +0.090 |
| 1N5255B | 28 | 26.60 | 29.40 | 4.5 | 44 | 600 | 0.1 | 21 | +0.091 |
| 1N5256B | 30 | 28.50 | 31.50 | 4.2 | 49 | 600 | 0.1 | 23 | +0.091 |
| 1N5257B | 33 | 31.35 | 34.65 | 3.8 | 58 | 700 | 0.1 | 25 | +0.092 |
| 1N5258B | 36 | 34.20 | 37.80 | 3.4 | 70 | 700 | 0.1 | 27 | +0.093 |
| 1N5259B | 39 | 37.05 | 40.95 | 3.2 | 80 | 800 | 0.1 | 30 | +0.094 |
| 1N5260B | 43 | 40.85 | 45.15 | 3.0 | 93 | 900 | 0.1 | 33 | +0.095 |
| 1N5261B | 47 | 44.65 | 49.35 | 2.7 | 105 | 1000 | 0.1 | 36 | +0.095 |
| 1N5262B | 51 | 48.45 | 53.55 | 2.5 | 125 | 1100 | 0.1 | 39 | +0.096 |
| 1N5263B | 56 | 53.20 | 58.80 | 2.2 | 150 | 1300 | 0.1 | 43 | +0.096 |
| 1N5264B | 60 | 57.00 | 63.00 | 2.1 | 170 | 1400 | 0.1 | 46 | +0.097 |
| 1N5265B | 62 | 58.90 | 65.10 | 2.0 | 185 | 1400 | 0.1 | 47 | +0.097 |
| 1N5266B | 68 | 64.60 | 71.40 | 1.8 | 230 | 1600 | 0.1 | 52 | +0.097 |
| 1N5267B | 75 | 71.25 | 78.75 | 1.7 | 270 | 1700 | 0.1 | 56 | +0.098 |

Notes: 3. Based on dc measurement at thermal equilibrium; lead length = 9.5mm (3/8"); thermal resistance of heat sink = 30°C/W.



**NOT RECOMMENDED FOR
NEW DESIGN, USE
MMSZ52xxB**

Ordering Information (Notes 4 & 5)

| Device | Packaging | Shipping |
|-----------------|-----------|-----------------|
| (Type Number)-A | DO-35 | 5K/Ammo Pack |
| (Type Number)-T | DO-35 | 10K/Tape & Reel |

Notes: 4. Add "-A" or "-T" to the appropriate type number in Table 1. Example: 6.2V Zener = 1N5234B-A for ammo pack.
5. For packaging details, visit our website at <http://www.diodes.com/datasheets/ap02008.pdf>.

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

- A. Life support devices or systems are devices or systems which:
 - 1. are intended to implant into the body, or
 - 2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.
- B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2011, Diodes Incorporated

www.diodes.com