

Film Capacitors

Metallized Polypropylene Film Capacitors (MKP)

Series/Type: B32671L ... B32672L

Date: March 2017

© EPCOS AG 2017. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

EPCOS AG is a TDK Group Company.

Typical applications

- Electronic ballasts (resonant circuits)
- SMPS
- High-frequency AC loads
- Pulse circuits

Climatic

- Max. operating temperature: 125 °C
- Climatic category (IEC 60068-1): 55/110/56

Construction

- Dielectric: metallized polypropylene (PP)
- Wound capacitor technology
- Plastic case (UL 94 V-0)
- Epoxy resin sealing

Features

- Very high AC voltages for all frequency ranges
- Very small dimensions
- High peak voltage for short time periods
- High peak current
- High pulse withstand capability
- RoHS-compatible
- Halogen-free capacitors available on request

Terminals

- Parallel wire leads, lead-free tinned
- Special lead lengths available on request

Marking


- Manufacturer's logo
- lot number, series number
- Rated capacitance (coded)
- Capacitance tolerance (code letter)
- Rated voltage
- Date of manufacture (coded)

Delivery mode

- Bulk (untaped)
- Taped (Ammo pack or reel)


For notes on taping, refer to chapter "Taping and packing".

Dimensional drawing




Dimensions in mm

| Lead spacing | Lead diameter | Type |
|--------------|----------------|---------|
| $e \pm 0.4$ | $d_1 \pm 0.05$ | |
| 10 | 0.6 | B32671L |
| 15 | 0.8 | B32672L |



Overview of available types

| Lead spacing | 10 mm | | | | | | 15 mm | | | | | | | | |
|-------------------------|---------|-----|------|------|------|------|---------|-----|-----|------|------|------|------|------|--|
| Type | B32671L | | | | | | B32672L | | | | | | | | |
| Page | 4 | | | | | | 6 | | | | | | | | |
| V _{RMS} (V AC) | 200 | 250 | 250 | 500 | 600 | 700 | 160 | 200 | 250 | 250 | 500 | 600 | 700 | 900 | |
| V _R (V DC) | 400 | 630 | 1000 | 1000 | 1600 | 2000 | 250 | 450 | 630 | 1000 | 1300 | 1600 | 2000 | 2000 | |
| C _R (nF) | | | | | | | | | | | | | | | |
| 1.0 | | | | | | | | | | | | | | | |
| 1.2 | | | | | | | | | | | | | | | |
| 1.5 | | | | | | | | | | | | | | | |
| 2.2 | | | | | | | | | | | | | | | |
| 2.7 | | | | | | | | | | | | | | | |
| 3.3 | | | | | | | | | | | | | | | |
| 3.9 | | | | | | | | | | | | | | | |
| 4.7 | | | | | | | | | | | | | | | |
| 5.6 | | | | | | | | | | | | | | | |
| 6.2 | | | | | | | | | | | | | | | |
| 6.8 | | | | | | | | | | | | | | | |
| 8.2 | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | |
| 15 | | | | | | | | | | | | | | | |
| 22 | | | | | | | | | | | | | | | |
| 33 | | | | | | | | | | | | | | | |
| 47 | | | | | | | | | | | | | | | |
| 56 | | | | | | | | | | | | | | | |
| 68 | | | | | | | | | | | | | | | |
| 100 | | | | | | | | | | | | | | | |
| 150 | | | | | | | | | | | | | | | |
| 220 | | | | | | | | | | | | | | | |
| 330 | | | | | | | | | | | | | | | |
| 390 | | | | | | | | | | | | | | | |
| 470 | | | | | | | | | | | | | | | |
| 680 | | | | | | | | | | | | | | | |
| 1000 | | | | | | | | | | | | | | | |


B32671L
High V AC, high temperature (wound)
Ordering codes and packing units (lead spacing 10 mm)

| V_{RMS} $f \leq 1$ kHz | V_R | C_R | Max. dimensions $w \times h \times l$ | Ordering code (composition see below) | Straight terminals, Ammo pack pcs./MOQ | Straight terminals, Reel pcs./MOQ | Straight terminals, Untaped pcs./MOQ |
|-----------------------------|-------|-------|--|---|--|--|---|
| V AC | V DC | nF | mm | | | | |
| 200 | 400 | 22 | 4.0 × 9.0 × 13.0 | B32671L4223+*** | 4000 | 6800 | 4000 |
| | | 33 | 4.0 × 9.0 × 13.0 | B32671L4333+*** | 4000 | 6800 | 4000 |
| | | 47 | 5.0 × 11.0 × 13.0 | B32671L4473+*** | 3320 | 5200 | 4000 |
| | | 68 | 5.0 × 11.0 × 13.0 | B32671L4683+*** | 3320 | 5200 | 4000 |
| | | 100 | 6.0 × 12.0 × 13.0 | B32671L4104+*** | 2720 | 4400 | 4000 |
| 250 | 630 | 15 | 4.0 × 9.0 × 13.0 | B32671L6153+*** | 4000 | 6800 | 4000 |
| | | 22 | 5.0 × 11.0 × 13.0 | B32671L6223+*** | 3320 | 5200 | 4000 |
| | | 33 | 5.0 × 11.0 × 13.0 | B32671L6333+*** | 3320 | 5200 | 4000 |
| | | 47 | 6.0 × 12.0 × 13.0 | B32671L6473+*** | 2720 | 4400 | 4000 |
| | | 56 | 6.0 × 12.0 × 13.0 | B32671L6563+*** | 2720 | 4400 | 4000 |
| 250 | 1000 | 4.7 | 4.0 × 9.0 × 13.0 | B32671L9472+*** | 4000 | 6800 | 4000 |
| | | 6.8 | 4.0 × 9.0 × 13.0 | B32671L9682+*** | 4000 | 6800 | 4000 |
| | | 10 | 5.0 × 11.0 × 13.0 | B32671L9103+*** | 3320 | 5200 | 4000 |
| | | 15 | 5.0 × 11.0 × 13.0 | B32671L9153+*** | 3320 | 5200 | 4000 |
| | | 22 | 6.0 × 12.0 × 13.0 | B32671L9223+*** | 2720 | 4400 | 4000 |
| 500 | 1000 | 3.3 | 4.0 × 9.0 × 13.0 | B32671L0332+*** | 4000 | 6800 | 4000 |
| | | 3.9 | 4.0 × 9.0 × 13.0 | B32671L0392+*** | 4000 | 6800 | 4000 |
| | | 4.7 | 4.0 × 9.0 × 13.0 | B32671L0472+*** | 4000 | 6800 | 4000 |
| | | 5.6 | 5.0 × 11.0 × 13.0 | B32671L0562+*** | 3320 | 5200 | 4000 |
| | | 6.2 | 5.0 × 11.0 × 13.0 | B32671L0622+*** | 3320 | 5200 | 4000 |
| | | 6.8 | 5.0 × 11.0 × 13.0 | B32671L0682+*** | 3320 | 5200 | 4000 |
| | | 8.2 | 6.0 × 12.0 × 13.0 | B32671L0822+*** | 2720 | 4400 | 4000 |
| | | 10 | 6.0 × 12.0 × 13.0 | B32671L0103+*** | 2720 | 4400 | 4000 |
| | | 12 | 6.0 × 12.0 × 13.0 | B32671L0123+*** | 2720 | 4400 | 4000 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series, intermediate capacitance values and closer tolerances on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%

*** = Packaging code:

289 = Straight terminals, Ammo pack

189 = Straight terminals, Reel

240 = Crimped down to lead spacing 7.5 mm,
Ammo pack

140 = Crimped down to lead spacing 7.5 mm,
Reel

003 = Straight terminals, untaped (lead length
3.2 ± 0.3 mm)

000 = Straight terminals, untaped (lead length
6–1 mm)


Ordering codes and packing units (lead spacing 10 mm)

| V_{RMS} $f \leq 1$ kHz | V_R | C_R | Max. dimensions $w \times h \times l$ | Ordering code (composition see below) | Straight terminals, Ammo pack pcs./MOQ | Straight terminals, Reel pcs./MOQ | Straight terminals, Untaped pcs./MOQ |
|-----------------------------|-------------------|-----------------|--|---|--|--|---|
| V AC | V DC | nF | mm | | | | |
| 600 | 1600 | 1.2 | 4.0 × 9.0 × 13.0 | B32671L1122+*** | 4000 | 6800 | 4000 |
| | | 1.5 | 4.0 × 9.0 × 13.0 | B32671L1152+*** | 4000 | 6800 | 4000 |
| | | 2.2 | 5.0 × 11.0 × 13.0 | B32671L1222+*** | 3320 | 5200 | 4000 |
| | | 2.7 | 5.0 × 11.0 × 13.0 | B32671L1272+*** | 3320 | 5200 | 4000 |
| | | 3.3 | 6.0 × 12.0 × 13.0 | B32671L1332+*** | 2720 | 4400 | 4000 |
| | | 3.9 | 6.0 × 12.0 × 13.0 | B32671L1392+*** | 2720 | 4400 | 4000 |
| | | 4.7 | 6.0 × 12.0 × 13.0 | B32671L1472+*** | 2720 | 4400 | 4000 |
| 700 | 2000 | 1.0 | 4.0 × 9.0 × 13.0 | B32671L8102+*** | 4000 | 6800 | 4000 |
| | | 1.2 | 4.0 × 9.0 × 13.0 | B32671L8122+*** | 4000 | 6800 | 4000 |
| | | 1.5 | 4.0 × 9.0 × 13.0 | B32671L8152+*** | 4000 | 6800 | 4000 |
| | | 2.2 | 5.0 × 11.0 × 13.0 | B32671L8222+*** | 3320 | 5200 | 4000 |
| | | 2.7 | 5.0 × 11.0 × 13.0 | B32671L8272+*** | 3320 | 5200 | 4000 |
| | | 3.3 | 5.0 × 11.0 × 13.0 | B32671L8332+*** | 3320 | 5200 | 4000 |
| | | 3.9 | 6.0 × 12.0 × 13.0 | B32671L8392+*** | 2720 | 4400 | 4000 |
| 4.7 | 6.0 × 12.0 × 13.0 | B32671L8472+*** | 2720 | 4400 | 4000 | | |

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series, intermediate capacitance values and closer tolerances on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%

*** = Packaging code:

289 = Straight terminals, Ammo pack

189 = Straight terminals, Reel

240 = Crimped down to lead spacing 7.5 mm,
Ammo pack

140 = Crimped down to lead spacing 7.5 mm,
Reel

003 = Straight terminals, untaped (lead length
3.2 ± 0.3 mm)

000 = Straight terminals, untaped (lead length
6–1 mm)


B32672L
High V AC, high temperature (wound)
Ordering codes and packing units (lead spacing 15 mm)

| V_{RMS} $f \leq 1$ kHz | V_R | C_R | Max. dimensions $w \times h \times l$ | Ordering code (composition see below) | Straight terminals, Ammo pack pcs./MOQ | Straight terminals, Reel pcs./ MOQ | Straight terminals, Untaped pcs./ MOQ |
|-----------------------------|-------|-------|--|---|--|--|---|
| V AC | V DC | nF | mm | | | | |
| 160 | 250 | 150 | 5.0 × 10.5 × 18.0 | B32672L2154+*** | 4680 | 5200 | 4000 |
| | | 220 | 6.0 × 11.0 × 18.0 | B32672L2224+*** | 3840 | 4400 | 4000 |
| | | 330 | 7.0 × 12.5 × 18.0 | B32672L2334+*** | 3320 | 3600 | 4000 |
| | | 470 | 8.5 × 14.5 × 18.0 | B32672L2474+*** | 2720 | 2800 | 2000 |
| | | 680 | 9.0 × 17.5 × 18.0 | B32672L2684+*** | 2560 | 2800 | 2000 |
| | | 1000 | 11.0 × 18.5 × 18.0 | B32672L2105+*** | — | 2200 | 1200 |
| 200 | 450 | 68 | 5.0 × 10.5 × 18.0 | B32672L4683+*** | 4680 | 5200 | 4000 |
| | | 100 | 5.0 × 10.5 × 18.0 | B32672L4104+*** | 4680 | 5200 | 4000 |
| | | 150 | 6.0 × 11.0 × 18.0 | B32672L4154+*** | 3840 | 4400 | 4000 |
| | | 220 | 7.0 × 12.5 × 18.0 | B32672L4224+*** | 3320 | 3600 | 4000 |
| | | 330 | 8.0 × 14.0 × 18.0 | B32672L4334+*** | 2920 | 3000 | 2000 |
| | | 470 | 9.0 × 17.5 × 18.0 | B32672L4474+*** | 2560 | 2800 | 2000 |
| 250 | 630 | 680 | 11.0 × 18.5 × 18.0 | B32672L4684+*** | — | 2200 | 1200 |
| | | 33 | 5.0 × 10.5 × 18.0 | B32672L6333+*** | 4680 | 5200 | 4000 |
| | | 47 | 5.0 × 10.5 × 18.0 | B32672L6473+*** | 4680 | 5200 | 4000 |
| | | 68 | 6.0 × 11.0 × 18.0 | B32672L6683+*** | 3840 | 4400 | 4000 |
| | | 100 | 7.0 × 12.5 × 18.0 | B32672L6104+*** | 3320 | 3600 | 4000 |
| | | 150 | 8.5 × 14.5 × 18.0 | B32672L6154+*** | 2720 | 2800 | 2000 |
| | | 220 | 9.0 × 17.5 × 18.0 | B32672L6224+*** | 2560 | 2800 | 2000 |
| | | 390 | 11.0 × 18.5 × 18.0 | B32672L6394+*** | — | 2200 | 1200 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series, intermediate capacitance values and closer tolerances on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%

*** = Packaging code:

289 = Straight terminals, Ammo pack


189 = Straight terminals, Reel

255 = Crimped down to lead spacing 7.5 mm,
Ammo pack

155 = Crimped down to lead spacing 7.5 mm,
Reel

003 = Straight terminals, untaped (lead length
3.2 ± 0.3 mm)

000 = Straight terminals, untaped (lead length
6–1 mm)


Ordering codes and packing units (lead spacing 15 mm)

| V_{RMS} $f \leq 1$ kHz | V_R | C_R | Max. dimensions $w \times h \times l$ | Ordering code (composition see below) | Straight terminals, Ammo pack pcs./MOQ | Straight terminals, Reel pcs./ MOQ | Straight terminals, Untaped pcs./ MOQ |
|-----------------------------|--------------------|-----------------|--|---|--|--|---|
| V AC | V DC | nF | mm | | | | |
| 250 | 1000 | 10 | 5.0 × 10.5 × 18.0 | B32672L0103+*** | 4680 | 5200 | 4000 |
| | | 15 | 5.0 × 10.5 × 18.0 | B32672L0153+*** | 4680 | 5200 | 4000 |
| | | 22 | 5.0 × 10.5 × 18.0 | B32672L0223+*** | 4680 | 5200 | 4000 |
| | | 33 | 6.0 × 11.0 × 18.0 | B32672L0333+*** | 3840 | 4400 | 4000 |
| | | 47 | 7.0 × 12.5 × 18.0 | B32672L0473+*** | 3320 | 3600 | 4000 |
| | | 68 | 8.5 × 14.5 × 18.0 | B32672L0683+*** | 2720 | 2800 | 2000 |
| | | 100 | 9.0 × 17.5 × 18.0 | B32672L0104+*** | 2560 | 2800 | 2000 |
| 500 | 1300 | 150 | 11.0 × 18.5 × 18.0 | B32672L0154+*** | — | 2200 | 1200 |
| | | 6.8 | 5.0 × 10.5 × 18.0 | B32672L7682+*** | 4680 | 5200 | 4000 |
| | | 10 | 5.0 × 10.5 × 18.0 | B32672L7103+*** | 4680 | 5200 | 4000 |
| | | 22 | 7.0 × 12.5 × 18.0 | B32672L7223+*** | 3320 | 3600 | 4000 |
| | | 33 | 8.5 × 14.5 × 18.0 | B32672L7333+*** | 2720 | 2800 | 2000 |
| | | 47 | 9.0 × 17.5 × 18.0 | B32672L7473+*** | 2560 | 2800 | 2000 |
| 600 | 1600 | 68 | 11.0 × 18.5 × 18.0 | B32672L7683+*** | — | 2200 | 1200 |
| | | 6.2 | 5.0 × 10.5 × 18.0 | B32672L1622+*** | 4680 | 5200 | 4000 |
| | | 6.8 | 5.0 × 10.5 × 18.0 | B32672L1682+*** | 4680 | 5200 | 4000 |
| | | 8.2 | 6.0 × 11.0 × 18.0 | B32672L1822+*** | 3840 | 4400 | 4000 |
| | | 10 | 6.0 × 11.0 × 18.0 | B32672L1103+*** | 3840 | 4400 | 4000 |
| | | 12 | 6.0 × 12.0 × 18.0 | B32672L1123+*** | 3840 | 4400 | 4000 |
| | | 15 | 7.0 × 12.5 × 18.0 | B32672L1153+*** | 3320 | 3600 | 4000 |
| | | 22 | 8.5 × 14.5 × 18.0 | B32672L1223+*** | 2720 | 2800 | 2000 |
| | | 33 | 9.0 × 17.5 × 18.0 | B32672L1333+*** | 2560 | 2800 | 2000 |
| 47 | 11.0 × 18.5 × 18.0 | B32672L1473+*** | — | 2200 | 1200 | | |

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series, intermediate capacitance values and closer tolerances on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%

*** = Packaging code:

289 = Straight terminals, Ammo pack


189 = Straight terminals, Reel

255 = Crimped down to lead spacing 7.5 mm,
Ammo pack

155 = Crimped down to lead spacing 7.5 mm,
Reel

003 = Straight terminals, untaped (lead length
3.2 ± 0.3 mm)

000 = Straight terminals, untaped (lead length
6–1 mm)


B32672L
High V AC, high temperature (wound)
Ordering codes and packing units (lead spacing 15 mm)

| V_{RMS} $f \leq 1$ kHz | V_R | C_R | Max. dimensions $w \times h \times l$ | Ordering code (composition see below) | Straight terminals, Ammo pack | Straight terminals, Reel | Straight terminals, Untaped |
|-----------------------------|--------------------|-----------------|--|---|--|--------------------------------|-----------------------------------|
| V AC | V DC | nF | mm | | pcs./MOQ | pcs./MOQ | pcs./MOQ |
| 700 | 2000 | 1.0 | 5.0 × 10.5 × 18.0 | B32672L8102+*** | 4680 | 5200 | 4000 |
| | | 1.2 | 5.0 × 10.5 × 18.0 | B32672L8122+*** | 4680 | 5200 | 4000 |
| | | 1.5 | 5.0 × 10.5 × 18.0 | B32672L8152+*** | 4680 | 5200 | 4000 |
| | | 2.2 | 5.0 × 10.5 × 18.0 | B32672L8222+*** | 4680 | 5200 | 4000 |
| | | 2.7 | 5.0 × 10.5 × 18.0 | B32672L8272+*** | 4680 | 5200 | 4000 |
| | | 3.3 | 5.0 × 10.5 × 18.0 | B32672L8332+*** | 4680 | 5200 | 4000 |
| | | 3.9 | 5.0 × 10.5 × 18.0 | B32672L8392+*** | 4680 | 5200 | 4000 |
| | | 4.7 | 5.0 × 10.5 × 18.0 | B32672L8472+*** | 4680 | 5200 | 4000 |
| | | 5.6 | 6.0 × 11.0 × 18.0 | B32672L8562+*** | 3840 | 4400 | 4000 |
| | | 6.2 | 6.0 × 11.0 × 18.0 | B32672L8622+*** | 3840 | 4400 | 4000 |
| | | 6.8 | 6.0 × 11.0 × 18.0 | B32672L8682+*** | 3840 | 4400 | 4000 |
| | | 8.2 | 6.0 × 12.0 × 18.0 | B32672L8822+*** | 3840 | 4400 | 4000 |
| | | 10 | 7.0 × 12.5 × 18.0 | B32672L8103+*** | 3320 | 3600 | 4000 |
| | | 12 | 8.5 × 14.5 × 18.0 | B32672L8123+*** | 2720 | 2800 | 2000 |
| | | 15 | 8.5 × 14.5 × 18.0 | B32672L8153+*** | 2720 | 2800 | 2000 |
| | | 22 | 9.0 × 17.5 × 18.0 | B32672L8223+*** | 2560 | 2800 | 2000 |
| 33 | 11.0 × 18.5 × 18.0 | B32672L8333+*** | — | 2200 | 1200 | | |

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series, intermediate capacitance values and closer tolerances on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%

*** = Packaging code:

289 = Straight terminals, Ammo pack


189 = Straight terminals, Reel

255 = Crimped down to lead spacing 7.5 mm,
Ammo pack

155 = Crimped down to lead spacing 7.5 mm,
Reel

003 = Straight terminals, untaped (lead length
3.2 ± 0.3 mm)

000 = Straight terminals, untaped (lead length
6–1 mm)


Ordering codes and packing units (lead spacing 15 mm)

| V_{RMS} $f \leq 1$ kHz | V_R | C_R | Max. dimensions $w \times h \times l$ | Ordering code (composition see below) | Straight terminals, Ammo pack pcs./MOQ | Straight terminals, Reel pcs./ MOQ | Straight terminals, Untaped pcs./ MOQ |
|-----------------------------|-------|-------|--|---|--|--|---|
| V AC | V DC | nF | mm | | | | |
| 900 | 2000 | 1.0 | 5.0 × 10.5 × 18.0 | B32672L9102+*** | 4680 | 5200 | 4000 |
| | | 1.2 | 6.0 × 11.0 × 18.0 | B32672L9122+*** | 3840 | 4400 | 4000 |
| | | 1.5 | 6.0 × 11.0 × 18.0 | B32672L9152+*** | 3840 | 4400 | 4000 |
| | | 2.2 | 7.0 × 12.5 × 18.0 | B32672L9222+*** | 3320 | 3600 | 4000 |
| | | 2.7 | 8.0 × 14.0 × 18.0 | B32672L9272+*** | 2920 | 3000 | 2000 |
| | | 3.3 | 8.5 × 14.5 × 18.0 | B32672L9332+*** | 2720 | 2800 | 2000 |
| | | 3.9 | 9.0 × 17.5 × 18.0 | B32672L9392+*** | 2560 | 2800 | 2000 |
| | | 4.7 | 9.0 × 17.5 × 18.0 | B32672L9472+*** | 2560 | 2800 | 2000 |
| | | 5.6 | 11.0 × 18.5 × 18.0 | B32672L9562+*** | — | 2200 | 1200 |
| | | 6.2 | 11.0 × 18.5 × 18.0 | B32672L9622+*** | — | 2200 | 1200 |
| | | 6.8 | 11.0 × 18.5 × 18.0 | B32672L9682K*** | — | 2200 | 1200 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series, intermediate capacitance values and closer tolerances on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%

*** = Packaging code:

289 = Straight terminals, Ammo pack

189 = Straight terminals, Reel

255 = Crimped down to lead spacing 7.5 mm,
Ammo pack

155 = Crimped down to lead spacing 7.5 mm,
Reel

003 = Straight terminals, untaped (lead length
3.2 ± 0.3 mm)

000 = Straight terminals, untaped (lead length
6–1 mm)



B32671L ... B32672L

High V AC, high temperature (wound)

Technical data

Reference standard: IEC 60384-16. All data given at T = 20 °C, otherwise is specified.

| | | | | | |
|--|--|--|----------------------------------|--|------------|
| Operating temperature range | Max. operating temperature $T_{op,max}$ | +125 °C | | | |
| | Upper category temperature T_{max} | +110 °C | | | |
| | Lower category temperature T_{min} | -55 °C | | | |
| | Rated temperature T_R | +85 °C | | | |
| Dissipation factor $\tan \delta$ (in 10^{-3}) at 20 °C (upper limit values) | at | ≤ 27 nF | 27 nF < $C_R \leq 0.1$ μ F | 0.1 μ F < $C_R \leq 1$ μ F | >1 μ F |
| | 1 kHz | 0.8 | 0.8 | 0.8 | 0.8 |
| | 10 kHz | 1.0 | 1.0 | 1.0 | — |
| | 100 kHz | 2.0 | 3.0 | — | — |
| Insulation resistance R_{ins} or time constant $\tau = C_R \cdot R_{ins}$ at 20 °C, rel. humidity $\leq 65\%$ (minimum as-delivered values) | 100 G Ω ($C_R \leq 0.33$ μ F) | | | | |
| | 30000 s ($C_R > 0.33$ μ F) | | | | |
| DC test voltage | $1.6 \cdot V_R$, 2 s | | | | |
| Category voltage V_C (continuous operation with V_{DC} or V_{AC} at $f \leq 1$ kHz) | T_{op} (°C) | DC voltage derating | | AC voltage derating | |
| | $T_{op} \leq 85$ $85 < T_{op} \leq 110$ | $V_C = V_R$ $V_C = V_R \cdot (165 - T_{op})/80$ | | $V_{C,RMS} = V_{RMS}$ $V_{C,RMS} = V_{RMS} \cdot (165 - T_{op})/80$ | |
| Operating voltage V_{op} for short operating periods (V_{DC} or V_{AC} at $f \leq 1$ kHz) | T_{op} (°C) | DC voltage (max. hours) | | AC voltage (max. hours) | |
| | $T_{op} \leq 100$ $100 < T_{op} \leq 125$ | $V_{op} = 1.25 \cdot V_C$ (2000 h) $V_{op} = 1.25 \cdot V_C$ (1000 h) | | $V_{op} = 1.0 \cdot V_{C,RMS}$ (2000 h) $V_{op} = 1.0 \cdot V_{C,RMS}$ (1000 h) | |
| Reliability: Failure rate λ Service life t_{SL} | 1 fit ($\leq 1 \cdot 10^{-9}/h$) at $0.5 \cdot V_R$, 40 °C 200 000 h at $1.0 \cdot V_R$, 85 °C For conversion to other operating conditions and temperatures, refer to chapter "Quality, 2 Reliability". | | | | |
| Failure criteria: Total failure Failure due to variation of parameters | Short circuit or open circuit | | | | |
| | Capacitance change $ \Delta C/C $ | | > 10% | | |
| | Dissipation factor $\tan \delta$ | | > 4 · upper limit values | | |
| | Insulation resistance R_{ins} | | < 1500 M Ω | | |



Pulse handling capability

"dV/dt" represents the maximum permissible voltage change per unit of time for non-sinusoidal voltages, expressed in V/μs.

"k₀" represents the maximum permissible pulse characteristic of the waveform applied to the capacitor, expressed in V²/μs.

Note:

The values of dV/dt and k₀ provided below must not be exceeded in order to avoid damaging the capacitor. These parameters are given for isolated pulses in such a way that the heat generated by one pulse will be completely dissipated before applying the next pulse. For a train of pulses, please refer to the curves of permissible AC voltage-current versus frequency.

dV/dt values

| | | | | | | |
|-------------------------|---------------|-----|------|------|------|-------|
| Lead spacing | 10 mm | | | | | |
| Type | B32671L | | | | | |
| V _{RMS} (V AC) | 200 | 250 | | 500 | 600 | 700 |
| V _R (V DC) | 400 | 630 | 1000 | 1000 | 1600 | 2000 |
| C _R (nF) | dV/dt in V/μs | | | | | |
| 1.0 | – | – | – | – | – | 11000 |
| 1.2 | – | – | – | – | 6000 | 10000 |
| 1.5 | – | – | – | – | 5600 | 9500 |
| 2.2 | – | – | – | – | 5200 | 9000 |
| 2.7 | – | – | – | – | 5000 | 8600 |
| 3.3 | – | – | – | 4700 | 4700 | 8500 |
| 3.9 | – | – | – | 4300 | 4500 | 8200 |
| 4.7 | – | – | 810 | 3800 | 4000 | 8000 |
| 5.6 | – | – | – | 3400 | – | – |
| 6.2 | – | – | – | 3200 | – | – |
| 6.8 | – | – | 810 | 3100 | – | – |
| 8.2 | – | – | – | 2700 | – | – |
| 10 | – | – | 810 | 2500 | – | – |
| 12 | – | – | – | 2300 | – | – |
| 15 | – | 540 | 810 | – | – | – |
| 22 | 400 | 540 | 810 | – | – | – |
| 33 | 400 | 540 | – | – | – | – |
| 47 | 400 | 540 | – | – | – | – |
| 56 | – | 540 | – | – | – | – |
| 68 | 400 | – | – | – | – | – |
| 100 | 400 | – | – | – | – | – |


B32671L ... B32672L
High V AC, high temperature (wound)
dV/dt values


| | | | | | | | | |
|-------------------------|---------------|-----|-----|------|------|------|-------|-------|
| Lead spacing | 15 mm | | | | | | | |
| Type | B32672L | | | | | | | |
| V _{RMS} (V AC) | 160 | 200 | 250 | | 500 | 600 | 700 | 900 |
| V _R (V DC) | 250 | 450 | 630 | 1000 | 1300 | 1600 | 2000 | 2000 |
| C _R (nF) | dV/dt in V/μs | | | | | | | |
| 1.0 | – | – | – | – | – | – | 10000 | 15000 |
| 1.2 | – | – | – | – | – | – | 9400 | 14100 |
| 1.5 | – | – | – | – | – | – | 9000 | 13500 |
| 2.2 | – | – | – | – | – | – | 7500 | 11000 |
| 2.7 | – | – | – | – | – | – | 7100 | 10600 |
| 3.3 | – | – | – | – | – | – | 6800 | 10000 |
| 3.9 | – | – | – | – | – | – | 6000 | 9000 |
| 4.7 | – | – | – | – | – | – | 5500 | 8200 |
| 5.6 | – | – | – | – | – | – | 5000 | 7500 |
| 6.2 | – | – | – | – | – | 3600 | 4700 | 7000 |
| 6.8 | – | – | – | – | 1000 | 3500 | 4500 | 6700 |
| 8.2 | – | – | – | – | – | 3100 | 4200 | – |
| 10 | – | – | – | 445 | 1000 | 2800 | 3900 | – |
| 12 | – | – | – | – | – | 2600 | 3600 | – |
| 15 | – | – | – | 445 | – | 2300 | 3300 | – |
| 22 | – | – | – | 445 | 1000 | 2000 | 2900 | – |
| 33 | – | – | 300 | 445 | 1000 | 1700 | 2300 | – |
| 47 | – | – | 300 | 445 | 1000 | 1400 | – | – |
| 56 | – | – | – | – | – | – | – | – |
| 68 | – | 200 | 300 | 445 | 1000 | – | – | – |
| 100 | – | 200 | 300 | 445 | – | – | – | – |
| 150 | 170 | 200 | 300 | 445 | – | – | – | – |
| 220 | 170 | 200 | 300 | – | – | – | – | – |
| 330 | 170 | 200 | – | – | – | – | – | – |
| 390 | – | – | 300 | – | – | – | – | – |
| 470 | 170 | 200 | – | – | – | – | – | – |
| 680 | 170 | 200 | – | – | – | – | – | – |
| 1000 | 170 | – | – | – | – | – | – | – |


 k_0 values

| | | | | | | |
|------------------|----------------------|--------|--------|---------|----------|----------|
| Lead spacing | 10 mm | | | | | |
| Type | B32671L | | | | | |
| V_{RMS} (V AC) | 200 | 250 | | 500 | 600 | 700 |
| V_R (V DC) | 400 | 630 | 1000 | 1000 | 1600 | 2000 |
| C_R (nF) | k_0 in $V^2/\mu s$ | | | | | |
| 1.0 | – | – | – | – | – | 25000000 |
| 1.2 | – | – | – | – | 14400000 | 23000000 |
| 1.5 | – | – | – | – | 14000000 | 22500000 |
| 2.2 | – | – | – | – | 13800000 | 22000000 |
| 2.7 | – | – | – | – | 13600000 | 21500000 |
| 3.3 | – | – | – | 9400000 | 13300000 | 21000000 |
| 3.9 | – | – | – | 8600000 | 13100000 | 20900000 |
| 4.7 | – | – | 400000 | 8200000 | 12000000 | 20800000 |
| 5.6 | – | – | – | 7600000 | – | – |
| 6.2 | – | – | – | 6800000 | – | – |
| 6.8 | – | – | 400000 | 6200000 | – | – |
| 8.2 | – | – | – | 5400000 | – | – |
| 10 | – | – | 400000 | 5000000 | – | – |
| 12 | – | – | – | 4600000 | – | – |
| 15 | – | 200000 | 400000 | – | – | – |
| 22 | 150000 | 200000 | 400000 | – | – | – |
| 33 | 150000 | 200000 | – | – | – | – |
| 47 | 150000 | 200000 | – | – | – | – |
| 56 | – | 200000 | – | – | – | – |
| 68 | 150000 | – | – | – | – | – |
| 100 | 150000 | – | – | – | – | – |



B32671L ... B32672L
High V AC, high temperature (wound)
 k_0 values


| | | | | | | | | | |
|------------------|----------------------|--------|--------|---------|---------|----------|----------|----------|--|
| Lead spacing | 15 mm | | | | | | | | |
| Type | B32672L | | | | | | | | |
| V_{RMS} (V AC) | 160 | 200 | 250 | | 500 | 600 | 700 | 900 | |
| V_R (V DC) | 250 | 450 | 630 | 1000 | 1300 | 1600 | 2000 | 2000 | |
| C_R (nF) | k_0 in $V^2/\mu s$ | | | | | | | | |
| 1.0 | – | – | – | – | – | – | 20300000 | 30000000 | |
| 1.2 | – | – | – | – | – | – | 19600000 | 29400000 | |
| 1.5 | – | – | – | – | – | – | 19200000 | 28000000 | |
| 2.2 | – | – | – | – | – | – | 18600000 | 27500000 | |
| 2.7 | – | – | – | – | – | – | 18200000 | 27300000 | |
| 3.3 | – | – | – | – | – | – | 18000000 | 27000000 | |
| 3.9 | – | – | – | – | – | – | 16800000 | 25200000 | |
| 4.7 | – | – | – | – | – | – | 15800000 | 23500000 | |
| 5.6 | – | – | – | – | – | – | 13100000 | 19500000 | |
| 6.2 | – | – | – | – | – | 11520000 | 12700000 | 19000000 | |
| 6.8 | – | – | – | – | 3000000 | 11200000 | 12300000 | 18400000 | |
| 8.2 | – | – | – | – | – | 9920000 | 11800000 | – | |
| 10 | – | – | – | 1000000 | 3000000 | 8960000 | 11100000 | – | |
| 12 | – | – | – | – | – | 8320000 | 10600000 | – | |
| 15 | – | – | – | 1000000 | – | 7360000 | 10400000 | – | |
| 22 | – | – | – | 1000000 | 3000000 | 6400000 | 9300000 | – | |
| 33 | – | – | 500000 | 1000000 | 3000000 | 5440000 | 9000000 | – | |
| 47 | – | – | 500000 | 1000000 | 3000000 | 4480000 | – | – | |
| 56 | – | – | – | – | – | – | – | – | |
| 68 | – | 120000 | 500000 | 1000000 | 3000000 | – | – | – | |
| 100 | – | 120000 | 500000 | 1000000 | – | – | – | – | |
| 150 | 100000 | 120000 | 500000 | 1000000 | – | – | – | – | |
| 220 | 100000 | 120000 | 500000 | – | – | – | – | – | |
| 330 | 100000 | 120000 | – | – | – | – | – | – | |
| 390 | – | – | 500000 | – | – | – | – | – | |
| 470 | 100000 | 120000 | – | – | – | – | – | – | |
| 680 | 100000 | – | – | – | – | – | – | – | |
| 1000 | 100000 | – | – | – | – | – | – | – | |



B32671L ... B32672L
High V AC, high temperature (wound)

Impedance Z versus frequency f (typical values)





B32671L


High V AC, high temperature (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms $T_A \leq 100\text{ }^\circ\text{C}$)


For $T_A > 100\text{ }^\circ\text{C}$, please use derating factor F_T .

Lead spacing 10 mm


400 V DC/200 V AC




630 V DC/250 V AC



1000 V DC/250 V AC




1000 V DC/500 V AC



B32671L


High V AC, high temperature (wound)




Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms $T_A \leq 100\text{ }^\circ\text{C}$)
 For $T_A > 100\text{ }^\circ\text{C}$, please use derating factor F_T .


Lead spacing 10 mm

1600 V DC/600 V AC



2000 V DC/700 V AC





B32672L


High V AC, high temperature (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms $T_A \leq 100\text{ }^\circ\text{C}$)


For $T_A > 100\text{ }^\circ\text{C}$, please use derating factor F_T .

Lead spacing 15 mm


250 V DC/160 V AC




450 V DC/200 V AC



630 V DC/250 V AC




1000 V DC/250 V AC



B32672L

High V AC, high temperature (wound)




Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms $T_A \leq 100^\circ C$)


For $T_A > 100^\circ C$, please use derating factor F_T .

Lead spacing 15 mm


1300 V DC/500 V AC




1600 V DC/600 V AC




2000 V DC/700 V AC



2000 V DC/900 V AC





B32671L


High V AC, high temperature (wound)

Permissible current I_{RMS} versus frequency f (for sinusoidal waveforms $T_A \leq 100\text{ }^\circ\text{C}$)


For $T_A > 100\text{ }^\circ\text{C}$, please use derating factor F_T .

Lead spacing 10 mm


400 V DC/200 V AC




630 V DC/250 V AC



1000 V DC/250 V AC




1000 V DC/500 V AC



B32671L

High V AC, high temperature (wound)




Permissible current I_{RMS} versus frequency f (for sinusoidal waveforms $T_A \leq 100\text{ }^\circ\text{C}$)


For $T_A > 100\text{ }^\circ\text{C}$, please use derating factor F_T .

Lead spacing 10 mm

1600 V DC/600 V AC



2000 V DC/700 V AC





B32672L


High V AC, high temperature (wound)

Permissible current I_{RMS} versus frequency f (for sinusoidal waveforms $T_A \leq 100\text{ }^\circ\text{C}$)


For $T_A > 100\text{ }^\circ\text{C}$, please use derating factor F_T .

Lead spacing 15 mm


250 V DC/160 V AC




450 V DC/200 V AC



630 V DC/250 V AC




1000 V DC/250 V AC



B32672L

High V AC, high temperature (wound)




Permissible current I_{RMS} versus frequency f (for sinusoidal waveforms $T_A \leq 100\text{ }^\circ\text{C}$)


For $T_A > 100\text{ }^\circ\text{C}$, please use derating factor F_T .

Lead spacing 15 mm


1300 V DC/500 V AC




1600 V DC/600 V AC



2000 V DC/700 V AC



2000 V DC/900 V AC





B32671L ... B32672L

High V AC, high temperature (wound)

Maximum AC voltage (V_{RMS}), current (I_{RMS}) vs. frequency and temperature for $T_A > 100\text{ }^\circ\text{C}$


The graphs described in the previous section for the permissible AC voltage (V_{RMS}) or current (I_{RMS}) vs. frequency are given for a maximum ambient temperature $T_A \leq 100\text{ }^\circ\text{C}$. In case of higher ambient temperatures (T_A), the self-heating (ΔT) of the component must be reduced to avoid that temperature of the component ($T_{op} = T_A + \Delta T$) reaches values above maximum operating temperature. The factor F_T shall be applied in the following way:

$$I_{RMS}(T_A) = I_{RMS, T_A \leq 100\text{ }^\circ\text{C}} \cdot F_T(T_A)$$

$$V_{RMS}(T_A) = V_{RMS, T_A \leq 100\text{ }^\circ\text{C}} \cdot F_T(T_A)$$


And F_T is given by the following curve:





Operation at overvoltages during heating and ignition of lamps ($T_A \leq 40^\circ\text{C}$)

In lighting applications, the capacitors can be subjected to overvoltages during the heating and ignition periods. An overvoltage occurs when the operation voltage exceeds the permissible AC voltage at the resonant frequency f_r .



KMK1019-1-E

For a repetitive application of on/off switching pulses (as for example in the life tests applied by electronic ballast manufacturers), limits have to be imposed on the time periods under overvoltage and on the duty cycle, in order to keep the capacitance value within the required margins:

- The overvoltage time t_{ov} should be less than 1 sec.
- The K_0 calculated in the overvoltage period (see general technical information) shall be lower than the maximum K_0 provided.
- The maximum duty cycle of the overvoltage is given by

$$\frac{t_{ov}}{t_{on} + t_{off}} \leq \left(\frac{V_{RMS}}{V_{RMS,OV}} \right)^2 \cdot 0.5$$


where $V_{RMS,OV}$ is the RMS voltage during period t_{ov}

$$V_{rms,OV} = \sqrt{\frac{V_1^2 + V_1 \cdot V_2 + V_2^2}{6}}$$

and V_{RMS} is the permissible AC voltage for continuous operation at the resonant frequency f_r (given by the "permissible AC voltage versus frequency f " graphics in the previous pages).

- The drift of capacitance depends on the V_{pp} attained, and the total time under overvoltage, which is calculated in hours as follows:
 $(N_i \cdot t_{ov}) / 3600$
 where N_i is the number of overvoltage impulses and t_{ov} is expressed in seconds.

The maximum drift of capacitance as a function of both parameters is provided graphically in the following pages.




B32671L

High V AC, high temperature (wound)


Estimation of the maximum drift of capacitance value in function of the number of total hours overvoltage

Lead spacing 10 mm

500 V AC/1000 V DC




600 V AC/1600 V DC



B32672L


High V AC, high temperature (wound)




Estimation of the maximum drift of capacitance value in function of the number of total hours overvoltage

Lead spacing 15 mm

600 V AC/1600 V DC



700 V AC/2000 V DC





B32671L ... B32672L

High V AC, high temperature (wound)

Testing and Standards

| Test | Reference | Conditions of test | Performance requirements |
|--|------------------------------------|---|--|
| Electrical Parameters | IEC 60384-16 | Voltage proof, $1.6 V_R$, 1 minute Insulation resistance, R_{INS} Capacitance, C Dissipation factor, $\tan \delta$ | Within specified limits |
| Robustness of terminations | IEC 60068-2-21 | Tensile strength (test Ua1) | Capacitance and $\tan \delta$ within specified limits |
| | | Wire diameter | |
| | | $0.5 < d1 \leq 0.8$ mm | 10 N |
| Resistance to soldering heat | IEC 60068-2-20, test Tb, method 1A | Solder bath temperature at 260 ± 5 °C, immersion for 10 seconds | $\Delta C/C_0 \leq 2\%$ $ \Delta \tan \delta \leq 0.002$ |
| Rapid change of temperature | IEC 60384-16 | T_A = lower category temperature T_B = upper category temperature Five cycles, duration $t = 30$ min. | |
| Vibration | IEC 60384-16 | Test Fc: vibration sinusoidal Displacement: 0.75 mm Acceleration: 98 m/s^2 Frequency: 10 Hz ... 500 Hz Test duration: 3 orthogonal axes, 2 hours each axe | No visible damage |
| Bump | IEC 60384-16 | Test Eb: Total 4000 bumps with 390 m/s^2 mounted on PCB 6 ms duration | No visible damage $ \Delta C/C_0 \leq 2\%$ $ \Delta \tan \delta \leq 0.002$ $R_{INS} \geq 50\%$ of initial limit |
| Climatic sequence | IEC 60384-16 | Dry heat Tb / 16 h. Damp heat cyclic, 1st cycle $+55$ °C / 24h / 95% ... 100% RH Cold Ta / 2h Damp heat cyclic, 5 cycles $+55$ °C / 24h / 95% ... 100% RH | No visible damage $ \Delta C/C_0 \leq 3\%$ $ \Delta \tan \delta \leq 0.001$ $R_{INS} \geq 50\%$ of initial limit |
| Damp Heat Steady State | IEC 60384-16 | Test Ca 40 °C / 93% RH / 56 days | No visible damage $ \Delta C/C_0 \leq 3\%$ $ \Delta \tan \delta \leq 0.001$ $R_{INS} \geq 50\%$ of initial limit |
| High temperature high humidity with load | | 60 °C / 95% RH / 1000 hours with $V_{R,DC}$ | No visible damage $ \Delta C/C_0 \leq 10\%$ $ \Delta \tan \delta \leq 0.002$ $R_{INS} \geq 50\%$ of initial limit |



| Test | Reference | Conditions of test | Performance requirements |
|-----------|-------------|--|---|
| Endurance | IEC60384-16 | 85 °C/ 1.25 V _R / 2000 hours | No visible damage ΔC/C ₀ ≤ 5% Δ tan δ ≤ 0.002 R _{INS} ≥ 50% of initial limit |
| Endurance | IEC60384-16 | 110 °C/ 1.25 V _C / 2000 hours | No visible damage ΔC/C ₀ ≤ 10% Δ tan δ ≤ 0.002 R _{INS} ≥ 50% of initial limit |

Mounting guidelines

1 Soldering

1.1 Solderability of leads

The solderability of terminal leads is tested to IEC 60068-2-20, test Ta, method 1.

Before a solderability test is carried out, terminals are subjected to accelerated ageing (to IEC 60068-2-2, test Ba: 4 h exposure to dry heat at 155 °C). Since the ageing temperature is far higher than the upper category temperature of the capacitors, the terminal wires should be cut off from the capacitor before the ageing procedure to prevent the solderability being impaired by the products of any capacitor decomposition that might occur.

| | |
|-------------------------|---|
| Solder bath temperature | 235 ±5 °C |
| Soldering time | 2.0 ±0.5 s |
| Immersion depth | 2.0 +0/−0.5 mm from capacitor body or seating plane |
| Evaluation criteria: | |
| Visual inspection | Wetting of wire surface by new solder ≥90%, free-flowing solder |



B32671L ... B32672L


High V AC, high temperature (wound)

1.2 Resistance to soldering heat


Resistance to soldering heat is tested to IEC 60068-2-20, test Tb, method 1A.

Conditions:

| Series | Solder bath temperature | Soldering time |
|--|-------------------------|--|
| MKT boxed (except 2.5 × 6.5 × 7.2 mm) coated uncoated (lead spacing > 10 mm) | 260 ±5 °C | 10 ±1 s |
| MFP MKP (lead spacing > 7.5 mm) | | |
| MKT boxed (case 2.5 × 6.5 × 7.2 mm) | 260 ±5 °C | 5 ±1 s |
| MKP (lead spacing ≤ 7.5 mm) | | < 4 s recommended soldering profile for MKT uncoated (lead spacing ≤ 10 mm) and insulated (B32559) |
| MKT uncoated (lead spacing ≤ 10 mm) insulated (B32559) | | |



| | |
|----------------------|---|
| Immersion depth | 2.0 +0/-0.5 mm from capacitor body or seating plane |
| Shield | Heat-absorbing board, (1.5 ±0.5) mm thick, between capacitor body and liquid solder |
| Evaluation criteria: | |
| Visual inspection | No visible damage |
| $\Delta C/C_0$ | 2% for MKT/MKP/MFP 5% for EMI suppression capacitors |
| $\tan \delta$ | As specified in sectional specification |



1.3 General notes on soldering


Permissible heat exposure loads on film capacitors are primarily characterized by the upper category temperature T_{max} . Long exposure to temperatures above this type-related temperature limit can lead to changes in the plastic dielectric and thus change irreversibly a capacitor's electrical characteristics. For short exposures (as in practical soldering processes) the heat load (and thus the possible effects on a capacitor) will also depend on other factors like:

- Pre-heating temperature and time
- Forced cooling immediately after soldering
- Terminal characteristics:
diameter, length, thermal resistance, special configurations (e.g. crimping)
- Height of capacitor above solder bath
- Shadowing by neighboring components
- Additional heating due to heat dissipation by neighboring components
- Use of solder-resist coatings

The overheating associated with some of these factors can usually be reduced by suitable countermeasures. For example, if a pre-heating step cannot be avoided, an additional or reinforced cooling process may possibly have to be included.

EPCOS recommendations

As a reference, the recommended wave soldering profile for our film capacitors is as follows:




T_s : Capacitor body maximum temperature at wave soldering
 T_p : Capacitor body maximum temperature at pre-heating

KMK1745-A-E



B32671L ... B32672L

High V AC, high temperature (wound)



Body temperature should follow the description below:

- MKP capacitor
 - During pre-heating: $T_p \leq 110 \text{ }^\circ\text{C}$
 - During soldering: $T_s \leq 120 \text{ }^\circ\text{C}$, $t_s \leq 45 \text{ s}$
- MKT capacitor
 - During pre-heating: $T_p \leq 125 \text{ }^\circ\text{C}$
 - During soldering: $T_s \leq 160 \text{ }^\circ\text{C}$, $t_s \leq 45 \text{ s}$

When SMD components are used together with leaded ones, the film capacitors should not pass into the SMD adhesive curing oven. The leaded components should be assembled after the SMD curing step.

Leaded film capacitors are not suitable for reflow soldering.


In order to ensure proper conditions for manual or selective soldering, the body temperature of the capacitor (T_s) must be $\leq 120 \text{ }^\circ\text{C}$.

One recommended condition for manual soldering is that the tip of the soldering iron should be $< 360 \text{ }^\circ\text{C}$ and the soldering contact time should be no longer than 3 seconds.

For uncoated MKT capacitors with lead spacings $\leq 10 \text{ mm}$ (B32560/B32561) the following measures are recommended:

- pre-heating to not more than $110 \text{ }^\circ\text{C}$ in the preheater phase
- rapid cooling after soldering

Please refer to EPCOS Film Capacitor Data Book in case more details are needed.



Cautions and warnings

- Do not exceed the upper category temperature (UCT).
- Do not apply any mechanical stress to the capacitor terminals.
- Avoid any compressive, tensile or flexural stress.
- Do not move the capacitor after it has been soldered to the PC board.
- Do not pick up the PC board by the soldered capacitor.
- Do not place the capacitor on a PC board whose PTH hole spacing differs from the specified lead spacing.
- Do not exceed the specified time or temperature limits during soldering.
- Avoid external energy inputs, such as fire or electricity.
- Avoid overload of the capacitors.

The table below summarizes the safety instructions that must always be observed. A detailed description can be found in the relevant sections of the chapters "General technical information" and "Mounting guidelines".

| Topic | Safety information | Reference chapter "General technical information" |
|-------------------------|--|---|
| Storage conditions | Make sure that capacitors are stored within the specified range of time, temperature and humidity conditions. | 4.5 "Storage conditions" |
| Flammability | Avoid external energy, such as fire or electricity (passive flammability), avoid overload of the capacitors (active flammability) and consider the flammability of materials. | 5.3 "Flammability" |
| Resistance to vibration | Do not exceed the tested ability to withstand vibration. The capacitors are tested to IEC 60068-2-6. EPCOS offers film capacitors specially designed for operation under more severe vibration regimes such as those found in automotive applications. Consult our catalog "Film Capacitors for Automotive Electronics". | 5.2 "Resistance to vibration" |

| Topic | Safety information | Reference chapter "Mounting guidelines" |
|--|---|--|
| Soldering | Do not exceed the specified time or temperature limits during soldering. | 1 "Soldering" |
| Cleaning | Use only suitable solvents for cleaning capacitors. | 2 "Cleaning" |
| Embedding of capacitors in finished assemblies | When embedding finished circuit assemblies in plastic resins, chemical and thermal influences must be taken into account. Caution: Consult us first, if you also wish to embed other uncoated component types! | 3 "Embedding of capacitors in finished assemblies" |



B32671L ... B32672L

High V AC, high temperature (wound)

Display of ordering codes for EPCOS products

The ordering code for one and the same product can be represented differently in data sheets, data books, other publications and the website of EPCOS, or in order-related documents such as shipping notes, order confirmations and product labels. **The varying representations of the ordering codes are due to different processes employed and do not affect the specifications of the respective products.**

Detailed information can be found on the Internet under www.epcos.com/orderingcodes.



Symbols and terms

| Symbol | English | German |
|----------------------|---|---|
| α | Heat transfer coefficient | Wärmeübergangszahl |
| α_C | Temperature coefficient of capacitance | Temperaturkoeffizient der Kapazität |
| A | Capacitor surface area | Kondensatoroberfläche |
| β_C | Humidity coefficient of capacitance | Feuchtekoeffizient der Kapazität |
| C | Capacitance | Kapazität |
| C_R | Rated capacitance | Nennkapazität |
| ΔC | Absolute capacitance change | Absolute Kapazitätsänderung |
| $\Delta C/C$ | Relative capacitance change (relative deviation of actual value) | Relative Kapazitätsänderung (relative Abweichung vom Ist-Wert) |
| $\Delta C/C_R$ | Capacitance tolerance (relative deviation from rated capacitance) | Kapazitätstoleranz (relative Abweichung vom Nennwert) |
| dt | Time differential | Differentielle Zeit |
| Δt | Time interval | Zeitintervall |
| ΔT | Absolute temperature change (self-heating) | Absolute Temperaturänderung (Selbsterwärmung) |
| $\Delta \tan \delta$ | Absolute change of dissipation factor | Absolute Änderung des Verlustfaktors |
| ΔV | Absolute voltage change | Absolute Spannungsänderung |
| dV/dt | Time differential of voltage function (rate of voltage rise) | Differentielle Spannungsänderung (Spannungsflankensteilheit) |
| $\Delta V/\Delta t$ | Voltage change per time interval | Spannungsänderung pro Zeitintervall |
| E | Activation energy for diffusion | Aktivierungsenergie zur Diffusion |
| ESL | Self-inductance | Eigeninduktivität |
| ESR | Equivalent series resistance | Ersatz-Serienwiderstand |
| f | Frequency | Frequenz |
| f_1 | Frequency limit for reducing permissible AC voltage due to thermal limits | Grenzfrequenz für thermisch bedingte Reduzierung der zulässigen Wechselspannung |
| f_2 | Frequency limit for reducing permissible AC voltage due to current limit | Grenzfrequenz für strombedingte Reduzierung der zulässigen Wechselspannung |
| f_r | Resonant frequency | Resonanzfrequenz |
| F_D | Thermal acceleration factor for diffusion | Therm. Beschleunigungsfaktor zur Diffusion |
| F_T | Derating factor | Deratingfaktor |
| i | Current (peak) | Stromspitze |
| I_C | Category current (max. continuous current) | Kategoriestrom (max. Dauerstrom) |



B32671L ... B32672L

High V AC, high temperature (wound)

| Symbol | English | German |
|------------------|--|---|
| I_{RMS} | (Sinusoidal) alternating current, root-mean-square value | (Sinusförmiger) Wechselstrom |
| i_z | Capacitance drift | Inkonstanz der Kapazität |
| k_0 | Pulse characteristic | Impuls Kennwert |
| L_S | Series inductance | Serieninduktivität |
| λ | Failure rate | Ausfallrate |
| λ_0 | Constant failure rate during useful service life | Konstante Ausfallrate in der Nutzungsphase |
| λ_{test} | Failure rate, determined by tests | Experimentell ermittelte Ausfallrate |
| P_{diss} | Dissipated power | Abgegebene Verlustleistung |
| P_{gen} | Generated power | Erzeugte Verlustleistung |
| Q | Heat energy | Wärmeenergie |
| ρ | Density of water vapor in air | Dichte von Wasserdampf in Luft |
| R | Universal molar constant for gases | Allg. Molarkonstante für Gas |
| R | Ohmic resistance of discharge circuit | Ohmscher Widerstand des Entladekreises |
| R_i | Internal resistance | Innenwiderstand |
| R_{ins} | Insulation resistance | Isolationswiderstand |
| R_P | Parallel resistance | Parallelwiderstand |
| R_S | Series resistance | Serienwiderstand |
| S | severity (humidity test) | Schärfegrad (Feuchtetest) |
| t | Time | Zeit |
| T | Temperature | Temperatur |
| τ | Time constant | Zeitkonstante |
| $\tan \delta$ | Dissipation factor | Verlustfaktor |
| $\tan \delta_D$ | Dielectric component of dissipation factor | Dielektrischer Anteil des Verlustfaktors |
| $\tan \delta_P$ | Parallel component of dissipation factor | Parallelanteil des Verlustfaktors |
| $\tan \delta_S$ | Series component of dissipation factor | Serienanteil des Verlustfaktors |
| T_A | Temperature of the air surrounding the component | Temperatur der Luft, die das Bauteil umgibt |
| T_{max} | Upper category temperature | Obere Kategorietemperatur |
| T_{min} | Lower category temperature | Untere Kategorietemperatur |
| t_{OL} | Operating life at operating temperature and voltage | Betriebszeit bei Betriebstemperatur und -spannung |
| T_{op} | Operating temperature, $T_A + \Delta T$ | Betriebstemperatur, $T_A + \Delta T$ |
| T_R | Rated temperature | Nenntemperatur |
| T_{ref} | Reference temperature | Referenztemperatur |
| t_{SL} | Reference service life | Referenz-Lebensdauer |



| Symbol | English | German |
|-------------|---|---|
| V_{AC} | AC voltage | Wechselspannung |
| V_C | Category voltage | Kategorie spannung |
| $V_{C,RMS}$ | Category AC voltage | (Sinusförmige) Kategorie-Wechselspannung |
| V_{CD} | Corona-discharge onset voltage | Teilentlade-Einsatzspannung |
| V_{ch} | Charging voltage | Ladespannung |
| V_{DC} | DC voltage | Gleichspannung |
| V_{FB} | Fly-back capacitor voltage | Spannung (Flyback) |
| V_i | Input voltage | Eingangsspannung |
| V_o | Output voltage | Ausgangsspannung |
| V_{op} | Operating voltage | Betriebsspannung |
| V_p | Peak pulse voltage | Impuls-Spitzen spannung |
| V_{pp} | Peak-to-peak voltage Impedance | Spannungshub |
| V_R | Rated voltage | Nennspannung |
| \hat{V}_R | Amplitude of rated AC voltage | Amplitude der Nenn-Wechselspannung |
| V_{RMS} | (Sinusoidal) alternating voltage, root-mean-square value | (Sinusförmige) Wechselspannung |
| V_{SC} | S-correction voltage | Spannung bei Anwendung "S-correction" |
| V_{sn} | Snubber capacitor voltage | Spannung bei Anwendung "Beschaltung" |
| Z | Impedance | Scheinwiderstand |
| e | Lead spacing | Rastermaß |

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or lifesaving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.

Important notes

7. The trade names EPCOS, CeraDiode, CeraLink, CeraPad, CeraPlas, CSMP, CTVS, DeltaCap, DigiSiMic, ExoCore, FilterCap, FormFit, LeaXield, MiniBlue, MiniCell, MKD, MKK, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, PowerHap, PQSine, PQvar, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.