




SOLDER POTS



SOLDER POT SELECTOR GUIDE

When ordering pot components, please order by pot catalog numbers.

Catalog No.	Pot Model No.	Wattage	Inside Dimen.	Inside Depth	Max. Temp. μ F	Solder Cap. lbs.	Shipping Wt. lbs.
P1200	12	200	1 9/16" diam.	1 1/2"	750	3/4	4
P12003	12C	200	1 9/16" diam.	1 1/2"	900	3/4	4 1/4
P120020	12T	250	1 9/16" diam.	1 1/2"	650	3/4	6 1/4
P2000	20	250	2" diam.	1 1/2"	1200	1 1/4	7
PD24	PD24	250	2" diam.	1 1/2"	1100	1 1/4	5 1/2
PD33	PD33	350	3" x 3"	1 1/2"	850	4 1/4	8
P3600	36	250	2 1/2" diam.	1 3/4"	750	2 1/4	4
P36003	36C	250	2 1/2" diam.	1 3/4"	900	2 1/4	4 1/4
P360020	36T	250	2 1/2" diam.	1 3/4"	625	2 1/4	6 1/4
P3700	37	650	3 1/2" diam.	1 3/4"	800	5	7
P37003	37C	650	3 1/2" diam.	1 3/4"	1000	5	7 1/2
P370020	37T	650	3 1/2" diam.	1 3/4"	650	5	9 1/8
P7000	70	650	4 3/4" diam.	1 3/4"	750	9	6 3/4
P700020	70T	650	4 3/4" diam.	1 3/4"	650	9	8
P710020	71T	1000	3 1/8" diam.	4 1/4"	900	9 1/2	14
PD74	PD74	1000	3 1/8" diam.	4 1/4"	900	9 1/2	13 1/2
P7500	75	650	4 3/4" x 4 3/4"	1 3/4"	750	11 3/4	8
P750020	75T	650	4 3/4" x 4 3/4"	1 3/4"	650	11 3/4	9 1/8
P800020	80T	1200	6" x 12"	1 7/8"	650	33	28

Models with suffix "C": Features a thermocape, a device which adds approximately 150 μ F to the temperature of standard models without the necessity of increasing the wattage of the heating element.

Models with suffix "T": Features an adjustable thermostat for selecting the optimum operating temperature.

ESICO·TRITON

INTERNATIONAL

P. O. Box 247 2 Esico Lane Deep River, Connecticut 06417-0247

Phone: 800.526.8661 Fax: 860.526.9524 E-mail: sales@esicotriton.com