

QTLP610C-2 HER


QTLP610C-3 Yellow

QTLP610C-4 Green

QTLP610C-7 AlGaAs Red


QTLP610C-B Blue

PACKAGE DIMENSIONS



NOTE:

1. Dimensions for all drawings are in inches (mm).
2. Cathode for -2, -3, -4 and B. Anode for -7.



APPLICATIONS

- LCD edge-lighting
- Edge card edge-lighting

DESCRIPTION

These right angle surface mount chip LEDs emit light in the lateral direction. Small size and wide viewing angle make these LEDs ideal choices for status indication in consumer electronics, industrial control and other applications.

FEATURES

- Small footprint - 3.0(L) X 2.0(W) X 1.0(H) mm
- Wide viewing angle of 120°
- Water clear optics
- Moisture-proof packaging
- Available in 0.315" (8mm) width tape on 7" (178mm) diameter reel; 2,000 units per reel

SURFACE MOUNT LED LAMP

STANDARD BRIGHT RIGHT ANGLE

QTLP610C-2 HER

QTLP610C-3 Yellow

QTLP610C-4 Green

QTLP610C-7 AlGaAs Red

QTLP610C-B Blue

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ Unless otherwise specified)

| Parameter | Symbol | QTLP610C | | | | | Units |
|---|-----------|---------------|-----|-----|-----|-----|------------------|
| | | -2 | -3 | -4 | -7 | -B | |
| Continuous Forward Current | I_F | 30 | 30 | 30 | 30 | 30 | mA |
| Peak Forward Current ($f = 1.0 \text{ KHz}$, Duty Factor = 1/10) | I_{FM} | 160 | 160 | 160 | 180 | 100 | mA |
| Reverse Voltage ($I_R = 10 \mu\text{A}$) | V_R | 5 | 5 | 5 | 5 | 5 | V |
| Power Dissipation | P_D | 84 | 84 | 84 | 72 | 135 | mW |
| Operating Temperature | T_{OPR} | -40 to +85 | | | | | $^\circ\text{C}$ |
| Storage Temperature | T_{STG} | -40 to +90 | | | | | $^\circ\text{C}$ |
| Lead Soldering Time | T_{SOL} | 260 for 5 sec | | | | | $^\circ\text{C}$ |

ELECTRICAL / OPTICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)

| Part Number | Symbol | QTLP610C | | | | | Condition |
|-------------------------------|-----------------|----------|-----|-----|-----|-----|---------------------|
| | | -2 | -3 | -4 | -7 | -B | |
| Luminous Intensity (mcd) | I_V | 3 | 3 | 5 | 10 | 15 | $I_F = 20\text{mA}$ |
| Minimum | | | | | | | |
| Typical | | 7 | 7 | 10 | 20 | 25 | |
| Forward Voltage (V) | V_F | 2.8 | 2.8 | 2.8 | 2.4 | 4.5 | $I_F = 20\text{mA}$ |
| Maximum | | | | | | | |
| Typical | | 2.0 | 2.0 | 2.1 | 1.9 | 3.8 | |
| Wavelength (nm) | λ_P | 635 | 585 | 565 | 660 | 430 | $I_F = 20\text{mA}$ |
| Peak | | | | | | | |
| Dominant | λ_D | 630 | 590 | 570 | 645 | 465 | |
| Spectral Line Half Width (nm) | $\Delta\lambda$ | 45 | 35 | 30 | 20 | 65 | $I_F = 20\text{mA}$ |
| Viewing Angle ($^\circ$) | $2\theta_{1/2}$ | 120 | 120 | 120 | 120 | 120 | $I_F = 20\text{mA}$ |

QTLP610C-2 HER

QTLP610C-3 Yellow

QTLP610C-4 Green

QTLP610C-7 AlGaAs Red

QTLP610C-B Blue

TYPICAL PERFORMANCE CURVES

Fig. 1 Forward Current vs. Forward Voltage




Fig. 2 Relative Luminous Intensity vs. DC Forward Current




Fig. 3 Relative Intensity vs. Peak Wavelength




Fig. 4 Radiation Diagram





Fig. 5 Maximum Forward Current vs. Ambient Temperature



QTLP610C-2 HER


QTLP610C-3 Yellow

QTLP610C-4 Green


QTLP610C-7 AlGaAs Red

QTLP610C-B Blue

RECOMMENDED PRINTED CIRCUIT BOARD PATTERN



RECOMMENDED IR REFLOW SOLDERING PROFILE



SURFACE MOUNT LED LAMP STANDARD BRIGHT RIGHT ANGLE

QTLP610C-2 HER



QTLP610C-3 Yellow

QTLP610C-4 Green

QTLP610C-7 AlGaAs Red

QTLP610C-B Blue

TAPE AND REEL DIMENSIONS



for -2, -3, -4, -B and -7

Polarity

Dimensional tolerance is ± 0.1 mm unless otherwise specified

Angle: ± 0.5

Unit: mm

QTLP610C-2 HER

QTLP610C-3 Yellow

QTLP610C-4 Green

QTLP610C-7 AlGaAs Red

QTLP610C-B Blue

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.