

| | | | |
|------------------------------------------------------|-------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|
| NUMBER GS-12-625 | TYPE Product Specification |  | |
| TITLE Terminal block- Plug and Socket, Fixed Plug | | PAGE 1 of 8 | REVISION D |
| | | AUTHORIZED BY Jason Hsu | DATE Nov. 11 th , 2009 |
| | | CLASSIFICATION Unrestricted | |

1.0 SCOPE

This specification covers performance, test, and quality requirement for terminal block pluggable plug, socket and fixed plug. Centerline spacing are 3.50, 3.81, 5.00, 5.08, and 7.62mm.

2.0 APPLICABLE DOCUMENTS

2.1 Drawing

| Pitch | Type | FCI series name | Drawing number | FCI part number | Poles |
|--------|--------|-----------------|----------------|--------------------|--------|
| 3.50mm | Plug | 01-350 | 20020004 | 20020004-CxxxxxxLF | 02~24p |
| | | 01-350 | 20020000 | 20020000-CxxxxxxLF | 02~24p |
| | | 02-350 | 20020009 | 20020009-CxxxxxxLF | 02~24p |
| | | 02-350 | 20020008 | 20020008-CxxxxxxLF | 02~24p |
| | Socket | 06-350 | 20020107 | 20020107-CxxxxxxLF | 02~24p |
| | | 06-350 | 20020108 | 20020108-CxxxxxxLF | 02~24p |
| | | 06-350 | 20020111 | 20020111-CxxxxxxLF | 02~24p |
| 3.81mm | Plug | 01-381 | 20020004 | 20020004-DxxxxxxLF | 02~24p |
| | | 01-381 | 20020000 | 20020000-DxxxxxxLF | 02~24p |
| | | 02-381 | 20020009 | 20020009-DxxxxxxLF | 02~24p |
| | | 02-381 | 20020008 | 20020008-DxxxxxxLF | 02~24p |
| | Socket | 06-381 | 20020107 | 20020107-DxxxxxxLF | 02~24p |
| | | 06-381 | 20020108 | 20020108-DxxxxxxLF | 02~24p |
| | | 06-381 | 20020111 | 20020111-DxxxxxxLF | 02~24p |
| 5.00mm | Plug | 01-500 | 20020006 | 20020006-GxxxxxxLF | 02~24p |
| | | 01-500 | 20020003 | 20020003-GxxxxxxLF | 02~24p |
| | | 02-500 | 20020009 | 20020009-GxxxxxxLF | 02~24p |
| | | 02-500 | 20020008 | 20020008-GxxxxxxLF | 02~24p |
| | Socket | 06-500 | 20020107 | 20020107-GxxxxxxLF | 02~24p |
| | | 06-500 | 20020108 | 20020108-GxxxxxxLF | 02~24p |
| | | 06-500 | 20020111 | 20020111-GxxxxxxLF | 02~24p |
| 5.08mm | Plug | 01-508 | 20020003 | 20020003-HxxxxxxLF | 02~24p |
| | | 01-508 | 20020006 | 20020006-HxxxxxxLF | 02~24p |
| | | 02-508 | 20020009 | 20020009-HxxxxxxLF | 02~24p |
| | | 06-508 | 20020108 | 20020108-HxxxxxxLF | 02~24p |
| | | 06-508 | 20020111 | 20020111-HxxxxxxLF | 02~24p |

PDS: Rev :E

STATUS: Released

Printed: Mar 05, 2012

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on the document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

| | | | |
|------------------------------------------------------|-------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|
| NUMBER GS-12-625 | TYPE Product Specification |  | |
| TITLE Terminal block- Plug and Socket, Fixed Plug | | PAGE 3 of 8 | REVISION D |
| | | AUTHORIZED BY Jason Hsu | DATE Nov. 11 th , 2009 |
| | | CLASSIFICATION Unrestricted | |

3.0 REQUIREMENTS

3.1 Design and Construction

Connectors shall be of the design, construction and physical dimensions specified on the applicable product drawings and shall consider the requirements mentioned on IEC 998-2-1 paragraph 10, relevant to clamping units.

3.2 Materials, Dimensions, Plating and Markings

All of these items are described on the individual drawings.

3.3 Ratings

Voltage rating, current rating, operation temperature and rated screw torque are described on the individual drawings.

3.4 Performance and Test Description

Product is designed to meet the electrical, mechanical and environment performance requirement list in section 3.5.

Unless otherwise specified, all tests shall be performed at ambient environmental conditions per IEC 160.

3.5 Test Requirements and Procedures Summary

| 3.5.1 ELECTRICAL REQUIREMENTS | | |
|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|
| DESCRIPTION | TEST CONDITION | REQUIREMENT |
| 3.5.1.1 Product Examination | Visual, dimensional and functional | Meet requirements of product drawing. |
| 3.5.1.2 Low Level Contact Resistance | Mated connectors, apply a maximum voltage of 0.2 V between wire pole and terminated terminal. | 20 milliohms maximum. |
| 3.5.1.3 Insulation resistance | IEC 60998-1, paragraph 13e 13.3. Initial 1000Volts DC, or 500Volts DC after environment test applied between two adjacent contact with measurements made 1 minute after the application of the voltage. | 1) 5000 MΩ Min. initial. 2) 5 MΩ minimum after environment test. |
| 3.5.1.4 Dielectric Withstanding Voltage | IEC 60998-1, paragraph 13e 13.4. Apply 1.6K VAC, Test between adjacent contacts of connector assemblies. | No breakdown; Current leakage < 5 mA |

PDS: Rev E

STATUS: Released

Printed: Mar 05, 2012

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on the document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

| | | | |
|------------------------------------------------------|-------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|
| NUMBER GS-12-625 | TYPE Product Specification |  | |
| TITLE Terminal block- Plug and Socket, Fixed Plug | | PAGE 5 of 8 | REVISION D |
| | | AUTHORIZED BY Jason Hsu | DATE Nov. 11 th , 2009 |
| | | CLASSIFICATION Unrestricted | |

| | | |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| | Samples were measured after salt is removed by running water. | |
| 3.5.3.5 Fire Test (Glow wire test) | Specimens with no visible flame and no sustained glowing; or flames and glowing on the specimen extinguished 30 seconds after the removal of the glow wire. | IEC 60695-2-10,-2-11,-2-12 Apply the glow-wire once for no longer than 5 seconds. |

4.0 **QUALITY ASSUREANCE PROVISIONS**

4.1 **Equipment Calibration**

All test equipment and inspection facilities used in the performance of any test shall be maintained in a calibration system in accordance with QS9000.

4.2 **Inspection Conditions**

Unless otherwise specified, all inspections shall be performed under the following conditions:

- a) Temperature: 25+/- 5°C
- b) Relative Humidity: 30% to 60%
- c) Barometric Pressure: Local ambient

4.3 **Acceptance**

- 4.3.1 Electrical and Mechanical requirements shall be as indicated in Paragraphs 3.5 using test data and appropriate statistical techniques.
- 4.3.2 Failures attributed to equipment, test setup or operator error shall not disqualify the product.

4.4 **Qualification Testing**

Qualification testing shall be performed on sample units predicted with equipment and procedures normally used in production. Test sequence are shown in Table 1(Pluggable plug), Table 2(pluggable socket), and Table3(Fixed plug).

| | | | |
|------------------------------------------------------|-------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|
| NUMBER GS-12-625 | TYPE Product Specification |  | |
| TITLE Terminal block- Plug and Socket, Fixed Plug | | PAGE 6 of 8 | REVISION D |
| | | AUTHORIZED BY Jason Hsu | DATE Nov. 11 th , 2009 |
| | | CLASSIFICATION Unrestricted | |

TABLE 1: QUALIFICATION TESTING SEQUENCE for Pluggable Plug

| TEST | PARA | Test Group | | | | | | | |
|-----------------------------------|--------------------|---------------|---|---|---|---|---|---|---|
| | | A | B | C | D | E | F | G | H |
| | | Test Sequence | | | | | | | |
| Product examination | 3.5.1.1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| LLCR | 3.5.1.2 | 2 | | | | | | 3 | |
| Insulation Resistance | 3.5.1.3 | 3 | | | 3 | 3 | 3 | 4 | |
| Dielectric withstanding voltage | 3.5.1.4 | 4 | | 4 | 4 | 4 | 4 | | |
| Mating/Un-mating force | 3.5.2.1 3.5.2.2 | | 2 | | | | | | |
| Torque | 3.5.2.5 | | 3 | | | | | | |
| Wire Pull Strength | 3.5.2.4 | | | 2 | | | | | |
| Temperature rise | 3.5.1.5 | | | 3 | | | | | |
| humidity test | 3.5.3.3 | | | | 2 | | | | |
| Heat resistance | 3.5.3.1 | | | | | 2 | | | |
| Cold resistance | 3.5.3.2 | | | | | | 2 | | |
| Salt Spray | 3.5.3.4 | | | | | | | 2 | |
| Fire Test (Glow wire test) | 3.5.3.5 | | | | | | | | 2 |
| Qualification connector per group | | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |

TABLE 2: QUALIFICATION TESTING SEQUENCE-Pluggable Socket

| TEST | PARA | Test Group | | | | | | | |
|---------------------------------|---------|---------------|---|---|---|---|---|---|---|
| | | A | B | C | D | E | F | G | H |
| | | Test Sequence | | | | | | | |
| Product examination | 3.5.1.1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Insulation Resistance | 3.5.1.3 | 2 | | 3 | 3 | 3 | | | |
| Dielectric withstanding voltage | 3.5.1.4 | 3 | | 4 | 4 | 4 | | | |
| Pin Retention (Pull force) | 3.5.2.6 | | 2 | | | | | | |
| Humidity | 3.5.3.3 | | | 2 | | | | | |
| Heat resistance | 3.5.3.1 | | | | 2 | | | | |
| Cold resistance | 3.5.3.2 | | | | | 2 | | | |
| Salt Spray | 3.5.3.4 | | | | | | 2 | | |
| Fire Test (Glow wire test) | 3.5.3.5 | | | | | | | 2 | |
| Solder ability | 3.5.2.7 | | | | | | | | 2 |

PDS: Rev E **STATUS: Released** **Printed: Mar 05, 2012**

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on the document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

| | | | |
|------------------------------------------------------|-------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|
| NUMBER GS-12-625 | TYPE Product Specification |  | |
| TITLE Terminal block- Plug and Socket, Fixed Plug | | PAGE 7 of 8 | REVISION D |
| | | AUTHORIZED BY Jason Hsu | DATE Nov. 11 th , 2009 |
| | | CLASSIFICATION Unrestricted | |

| | | | | | | | | | |
|-----------------------------------|---|---|---|---|---|---|---|---|---|
| Qualification connector per group | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
|-----------------------------------|---|---|---|---|---|---|---|---|---|

TABLE 3: QUALIFICATION TESTING SEQUENCE-Fixed Plug

| TEST | PARA | Test Group | | | | | | | | | |
|-----------------------------------|---------|---------------|---|---|---|---|---|---|---|---|--|
| | | A | B | C | D | E | F | G | H | J | |
| | | Test Sequence | | | | | | | | | |
| Product examination | 3.5.1.1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | |
| LLCR | 3.5.1.2 | 2 | | | | | | 3 | | | |
| Insulation Resistance | 3.5.1.3 | 3 | | | 3 | 3 | 3 | 4 | | | |
| Dielectric withstanding voltage | 3.5.1.4 | 4 | | 4 | 4 | 4 | 4 | | | | |
| Torque | 3.5.2.5 | | 2 | | | | | | | | |
| Wire Pull Strength | 3.5.2.4 | | | 2 | | | | | | | |
| Temperature rise | 3.5.1.5 | | | 3 | | | | | | | |
| humidity test | 3.5.3.3 | | | | 2 | | | | | | |
| Heat resistance | 3.5.3.1 | | | | | 2 | | | | | |
| Cold resistance | 3.5.3.2 | | | | | | 2 | | | | |
| Salt Spray | 3.5.3.4 | | | | | | | 2 | | | |
| Solder ability | 3.5.2.7 | | | | | | | | 2 | | |
| Fire Test (Glow wire test) | 3.5.3.5 | | | | | | | | | 2 | |
| Qualification connector per group | | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | |

| | | | |
|----------------------------------------------------------|-------------------------------|-------------------------------------------------------------------------------------|--------------------------------------|
| NUMBER GS-12-625 | TYPE Product Specification |  | |
| TITLE Terminal block- Plug and Socket, Fixed Plug | | PAGE 8 of 8 | REVISION D |
| | | AUTHORIZED BY Jason Hsu | DATE Nov. 11 th , 2009 |
| | | CLASSIFICATION Unrestricted | |

REVISION RECORD

| REV | PAGE | DESCRIPTION | ECR# | DATE |
|-----|------|-------------------------------------------------------------------------------------|-----------|-----------------------------|
| A | All | Initial Release | DG09-0204 | Nov 11 th , 2009 |
| B | 3 | 3.5.2.7 solderability test, Temperature change form 260 +/- 5 °C to 250 +/- 10°C | T09-1162 | Dec 17 th , 2009 |
| C | All | Add phase-2 product series | T10-0079 | Jun 15 th , 2010 |
| D | 2 | Add p/n 20020336 | | Jan 31 th , 2010 |

PDS: Rev :E

STATUS: Released

Printed: Mar 05, 2012

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on the document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.