

MIL-C-5015



660-004 Plug Cover



660-005 Receptacle Cover

TABLE X: SHELL SIZE DIMENSIONS

| Shell Size | E Thread        | F Max        | G Max       | H Max        | J Max       |
|------------|-----------------|--------------|-------------|--------------|-------------|
| 08         | 1/2 - 28 UNEF   | .562 (14.3)  | .656 (16.7) | .688 (17.5)  | .465 (11.8) |
| 10         | 5/8 - 24 UNEF   | .687 (17.4)  | .656 (16.7) | .815 (20.7)  | .465 (11.8) |
| 12         | 3/4 - 20 UNEF   | .812 (20.6)  | .844 (21.4) | 1.000 (25.4) | .465 (11.8) |
| 14         | 7/8 - 20 UNEF   | .937 (23.8)  | .844 (21.4) | 1.125 (28.6) | .465 (11.8) |
| 16         | 1 - 20 UNEF     | 1.062 (27.0) | .844 (21.4) | 1.188 (30.2) | .465 (11.8) |
| 18         | 1 1/8 - 18 UNEF | 1.187 (30.1) | .844 (21.4) | 1.344 (34.1) | .465 (11.8) |
| 20         | 1 1/4 - 18 UNEF | 1.312 (33.3) | .844 (21.4) | 1.469 (37.3) | .465 (11.8) |
| 22         | 1 3/8 - 18 UNEF | 1.437 (36.5) | .844 (21.4) | 1.594 (40.5) | .465 (11.8) |
| 24         | 1 1/2 - 18 UNEF | 1.562 (39.7) | .844 (21.4) | 1.719 (43.7) | .465 (11.8) |
| 28         | 1 3/4 - 18 UNS  | 1.812 (46.0) | .844 (21.4) | 1.969 (50.0) | .531 (13.5) |
| 32         | 2 - 18 UNS      | 2.062 (52.4) | .844 (21.4) | 2.219 (56.4) | .531 (13.5) |
| 36         | 2 1/4 - 16 UN   | 2.312 (58.7) | .844 (21.4) | 2.469 (62.7) | .531 (13.5) |
| 40         | 2 1/2 - 16 UN   | 2.562 (65.1) | .844 (21.4) | 2.719 (69.1) | .531 (13.5) |
| 44         | 2 3/4 - 16 UN   | 2.812 (71.4) | .844 (21.4) | 2.969 (75.4) | .531 (13.5) |
| 48         | 3 - 16 UN       | 3.062 (77.8) | .844 (21.4) | 3.188 (81.0) | .531 (13.5) |

See inside back cover fold-out or page 14 for Table II.

Metric dimensions (mm) are indicated in parentheses.

