



| Shell Size | Max. Recommended Torque (Inch Pounds) | A Dia. Max. | B Dia. Max. | C Dim. Max. |
|------------|---------------------------------------|--------------|--------------|-------------|
| 08 | 60 | .474 (12.0) | .357 (9.1) | .88 (22.4) |
| 10 | 80 | .591 (15.0) | .485 (12.3) | .88 (22.4) |
| 12 | 110 | .751 (19.1) | .602 (15.3) | .88 (22.4) |
| 14 | 120 | .876 (22.3) | .727 (18.5) | .88 (22.4) |
| 16 | 120 | 1.001 (25.4) | .852 (21.6) | .88 (22.4) |
| 18 | 120 | 1.126 (28.6) | .957 (24.3) | .88 (22.4) |
| 20 | 140 | 1.251 (31.8) | 1.082 (27.5) | .88 (22.4) |
| 22 | 140 | 1.376 (35.0) | 1.207 (30.7) | .88 (22.4) |
| 24 | 140 | 1.501 (38.1) | 1.332 (33.8) | .88 (22.4) |

APPLICATION NOTES

- Metric dimensions (mm) are indicated in parentheses.
- Material: Case hardened carbon steel with electroless nickel finish.
- Receptacle and plug holder drives: 1/4" - Shell sizes 08, 10, 12; 3/8" - Shell sizes 14 and up.