


CONNECTOR DESIGNATORS
A-B*-C-D-E-F
G-H-J-K-L-S

* Conn. Desig. B See Note 5
DIRECT COUPLING

TYPE A OVERALL SHIELD TERMINATION



STYLE 2
 (STRAIGHT
 See Note 1)



390-002
Submersible EMI/RFI Cable Sealing Backshell
with Strain Relief
Type A - Direct Coupling - Low Profile



See inside back cover fold-out or pages 13 and 14 for Tables I and II.

TABLE III: FRONT ADAPTER			
Shell Size	J Max - Conn. Designator		
	A-E-F		
	J-H-L-S	D-B-G-K	C
08/09	1.180(30.0)	1.440(36.6)	
10/11	1.180(30.0)	1.440(36.6)	
12/13	1.180(30.0)	1.440(36.6)	1.735(44.1)
14/15	1.180(30.0)	1.440(36.6)	1.915(48.6)
16/17	1.380(35.0)	1.560(39.6)	1.915(48.6)
18/19	1.380(35.0)	1.560(39.6)	1.915(48.6)
20/21	1.380(35.0)	1.560(39.6)	1.915(48.6)
22/23	1.380(35.0)	1.560(39.6)	1.915(48.6)
24/25	1.380(35.0)	1.560(39.6)	1.915(48.6)
28/29	1.610(40.9)	1.560(39.6)	1.915(48.6)
32/33	1.610(40.9)	1.750(44.5)	1.915(48.6)
36	1.610(40.9)	1.750(44.5)	1.915(48.6)
40	1.610(40.9)	2.190(55.6)	1.915(48.6)

TABLE IV: ELBOW DIMENSIONS						
Dash No.	E Max	F Max	G Max	H Max		
04	.630 (16.0)	2.117 (53.8)	.636 (16.2)	2.067 (52.5)		
06	.630 (16.0)	2.117 (53.8)	.710 (18.0)	2.187 (55.5)		
08	.692 (17.6)	2.179 (55.3)	.731 (18.6)	2.207 (56.1)		
10	.755 (19.2)	2.862 (72.7)	.825 (21.0)	2.867 (72.8)		
12	.848 (21.5)	2.972 (75.5)	.988 (25.1)	2.957 (75.1)		
16	1.036 (26.3)	3.159 (80.2)	1.087 (27.6)	3.132 (79.6)		
20	1.130 (28.7)	3.368 (85.5)	1.325 (33.7)	3.303 (83.9)		
24	1.255 (31.9)	3.408 (86.6)	1.337 (34.0)	3.453 (87.7)		
28	1.317 (33.5)	3.553 (90.2)	1.827 (46.4)	3.703 (94.1)		
32	1.348 (34.2)	3.646 (92.6)	2.027 (51.5)	3.753 (95.3)		

TABLE X: CABLE ENTRY								
Dash No.	T Max	V Max	Cable Range					
			Min				Max	
04	.780 (19.8)	.957 (24.3)	.125 (3.2)	.312 (7.9)				
06	.780 (19.8)	1.145 (29.1)	.250 (6.4)	.437 (11.1)				
08	.780 (19.8)	1.332 (33.8)	.387 (9.8)	.562 (14.3)				
10	.780 (19.8)	1.332 (33.8)	.350 (8.9)	.625 (15.9)				
12	.811 (20.6)	1.551 (39.4)	.500 (12.7)	.750 (19.1)				
16	.905 (23.0)	1.770 (45.0)	.625 (15.9)	.937 (23.8)				
20	1.092 (27.7)	2.113 (53.7)	.875 (22.2)	1.250 (31.8)				
24	1.124 (28.5)	2.363 (60.0)	1.000 (25.4)	1.375 (34.9)				
28	1.399 (35.5)	2.770 (70.4)	1.250 (31.8)	1.625 (41.3)				
32	1.399 (35.5)	3.020 (76.7)	1.437 (36.5)	1.875 (47.6)				

1. When maximum cable entry (page 22) is exceeded, Style 2 will be supplied. (Function S only).
2. Metric dimensions (mm) are indicated in parentheses.
3. Cable range is defined as the accommodations range for the wire bundle or cable. Dimensions shown are not intended for inspection criteria.
4. Consult factory for shorter lengths on straight backshells.
5. When using Connector Designator B refer to pages 18 and 19 for part number development.

TABLE XI: CABLE ENTRY									
Dash No.	W Max	X Max	Y Max	Z Max	Cable Range				
					Min			Max	
03*	.437 (11.1)	.760 (19.3)	.843 (21.4)	.630 (16.0)	.156 (4.0)	.250 (6.4)			
04*	.437 (11.1)	.760 (19.3)	.906 (23.0)	.755 (19.2)	.188 (4.8)	.312 (7.9)			
06*	.500 (12.7)	.760 (19.3)	1.093 (27.8)	.942 (23.9)	.281 (7.1)	.438 (11.1)			
08	.563 (14.3)	.760 (19.3)	1.187 (30.1)	1.067 (27.1)	.387 (9.8)	.562 (14.3)			
10	.563 (14.3)	.760 (19.3)	1.281 (32.5)	1.192 (30.3)	.375 (9.5)	.625 (15.9)			
12	.563 (14.3)	.760 (19.3)	1.500 (38.1)	1.380 (35.1)	.438 (11.1)	.750 (19.1)			
16	.656 (16.7)	1.073 (27.3)	1.719 (43.7)	1.535 (39.0)	.625 (15.9)	.938 (23.8)			
20	.656 (16.7)	1.323 (33.6)	2.062 (52.4)	1.848 (46.9)	.875 (22.2)	1.250 (31.8)			
24	.656 (16.7)	1.323 (33.6)	2.312 (58.7)	2.255 (57.3)	1.000 (25.4)	1.375 (34.9)			
28	1.188 (30.2)	1.572 (39.9)	2.719 (69.1)	2.505 (63.6)	1.250 (31.8)	1.625 (41.3)			
32*	1.187 (30.1)	1.572 (39.9)	2.969 (75.4)	2.755 (70.0)	1.437 (36.5)	1.875 (47.6)			
40*	1.125 (28.6)	1.572 (39.9)	3.531 (89.7)	3.255 (82.7)	1.875 (47.6)	2.375 (60.3)			

* Not available in Style M clamp.