340-001
O-Ring Sealed Shorting Cap Backshell
Rotatable Coupling

CONNECTOR DESIGNATORS

A-F-G

H-J-L-S

ROTATABLE COUPLING

340 F S 001 M 16-5 H 6 A

- Product Series
- Connector Designator
- Angle and Profile S = Straight
- Basic Part No.
- Finish (Table II)
- Shell Size (Table I)
- Length (1/2 inch increments: e.g. 5 = 2.5 inches, 1.0 inch Minimum Order Length
- Attachment Symbol (Table III)
- Attachment Length (1/2 inch increments: e.g. 6 = 3 inches)
- End Fitting Symbol (Table IV)



-445 Now Available with the "NESTOR"

Add "-445" to Specify Glenair's Non-Detent, Spring-Loaded, Self-Locking Coupling. See Page 41 for Details.

TABLE IV: END FITTING

Symbol	E Dia.	
A	.140	(3.6)
B	.167	(4.2)
C	.182	(4.6)
D	.191	(4.9)
E	.125	(3.2)
F	.218	(5.5)

TABLE III: ATTACHMENT OPTIONS

Symbol	Attachment
C	No attachment, body strap only
D	Bead chain, cres, passivate, with terminal
E	Link chain, cres, passivate, with reverse link
F	Wire rope, nylon jacket, with terminal
G	Nylon rope, with terminal
H	Wire rope, fluoropolymer jacket, with terminal
N	Attachment omitted
R	Wire rope, PVC jacket, with terminal
S	#8 Sash chain, cres, passivate
U	Wire rope, polyurethane jacket, with terminal

TABLE II: STANDARD FINISHES

GLENAIR SYMBOL	FINISH
B	Cadmium Plate, Olive Drab
C	Anodize, Black
G	Hard Coat, Anodic
M	Electroless Nickel
NF	Cadmium Plate, Olive Drab Over Electroless Nickel

See Back Cover for Complete Finish Information and Additional Finish Options

1. Metric dimensions (mm) are indicated in parentheses.
2. O-Ring not supplied with Connector Designators A and G.
3. Custom engraving available, consult factory.

See inside back cover fold-out or pages 13 and 14 for unabridged Tables I and II.

© 2005 Glenair, Inc. CAGE Code 06324 Printed in U.S.A.