

**CONNECTOR  
 DESIGNATORS  
 A-F-H-L-S  
 ROTATABLE  
 COUPLING**

**TYPE A OVERALL  
 SHIELD TERMINATION**



**STYLE 2  
 (STRAIGHT)**  
 See Note 1)



**STYLE 2  
 (45° & 90°)**  
 See Note 1)



**-445** Now Available with the "NESTOR"  
 Glenair's Non-Detent, Spring-Loaded, Self-Locking Coupling.  
 Add "-445" to Specify This AS85049 Style "N" Coupling Interface.


**STYLE H  
 Heavy Duty**  
 (Table X)




**STYLE A  
 Medium Duty**  
 (Table XI)



**STYLE M  
 Medium Duty**  
 (Table XI)



**STYLE D  
 Medium Duty**  
 (Table XI)



390-001

Submersible EMI/RFI Cable Sealing Backshell with Strain Relief Type A - Rotatable Coupling - Low Profile



39

TABLE III: ELBOW DIMENSIONS

Table with columns: Shell Size Conn. Desig. A-F-L-S H, E Max, F Max, G Max, H Max. Rows include dimensions for shell sizes 08 through 36.

- 1. When maximum cable entry (page 21) is exceeded, Style 2 will be supplied. Dimensions E, F, G and H will not apply. Please consult factory.
2. Metric dimensions (mm) are indicated in parentheses.
3. Cable range is defined as the accommodations range for the wire bundle or cable. Dimensions shown are not intended for inspection criteria.
4. Consult factory for shorter lengths on straight backshells.
5. Interface O-Ring not supplied with connector designator A.

TABLE X: CABLE ENTRY

Table with columns: Dash No., T Max, V Max, Cable Range (Min, Max). Rows include cable entry dimensions for dash numbers 04 through 32.

See inside back cover fold-out or pages 13 and 14 for Tables I and II.

TABLE XI: CABLE ENTRY

Table with columns: Dash No., W Max, X Max, Y Max, Z Max, Cable Range (Min, Max). Rows include cable entry dimensions for dash numbers 03\* through 40\*.

\* Not available in Style M clamp.