**MICRO SWITCH**
A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR COMPANY
FREEPORT, ILLINOIS
FED. MFR. CODE 91929

# SWITCH - BASIC

CATALOG LISTING
**1HS103**




NOTE-
1 - THIS SWITCH IS FOR LEFT HAND MOUNTING ONLY
2 - THIS SWITCH IS RECOMMENDED FOR USE IN AMBIENT TEMPERATURES FROM 250° F TO MINUS 65°F
3 - .006 MAX ROLLER SLANT ACROSS LENGTH OF ROLLER MEASURED FROM CENTER LINE OF MOUNTING HOLES
4 - THE MASS OF THE MOVING CONTACT IS .22 GRAM

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

## CHARACTERISTICS

OPERATING FORCE - - - - - - 10 - 22 OZ
RELEASE FORCE - - - - - - - - 4 OZ MIN
DIFFERENTIAL TRAVEL - - - - - .013 MAX
OVERTRAVEL - - - - - - - - - -.035-.047

## ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

| LINE VOLTAGE | INDUCTIVE LOAD | RESISTIVE LOAD |
|---|---|---|
| 28 V.D.C. | 5 AMP. | 15 AMP. |

SCALE FULL
DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:

| | | |
|---|---|---|
| ONE PLACE | (.0) | ±.030 |
| TWO PLACE | (.00) | ±.015 |
| THREE PLACE | (.000) | ±.005 |
| ANGLES | | ± |

WEIGHT 1.9 OZ MAX

DRAWN O M W 17 APR 61 CHECK
DAW 31 AUG 62 CHECK
F T H 18 APR 61 CHECK

REVISIONS

| | | |
|---|---|---|
| A | MADE MPS D W V 20 NOV 61 | |
| B | SR10463 L S D 23 AUG 62 | |
| C | C019072 RER 13 MAY 64 | |
| D | C056087 KJS 9 NOV 84 | |
| E | C057626 G J W 20 JUN 85 | |
| F | CO 55162 M A M 10 DEC 85 | |
| G | CO 61043 BGS 16 SEP 88 | |
| H | C065768 TSK 12 JUN 89 | |
| J | CO 76375 WES 2 SEPT 93 | |

ISSUE X X X
DRAWING NUMBER M 10
RELEASE NO. SR 10463
REPLACES 1HS103

FO-50378