


- NOTES**
- 1 - HOUSING MATERIAL: GLASS FILLED POLYESTER
 - 2 - BASIC SWITCHES ARE V3-115. SWITCHES DO NOT OPERATE SIMULTANEOUSLY
 - 3 - ENCLOSURE DESIGN, SYMBOL 3 (WATER TIGHT) EXCEPT THE ASSEMBLY MUST WITHSTAND 546mm Hg (TORRS) PRESSURE WHEN SUBMERGED IN CLEAR WATER
 - 4 - COLOR WHITE, CONFORMING TO SPEC TT-E-489 EXCEPT PLUNGER, CONNECTOR, AND SCREWS
- 5 CATALOG LISTING, DATE CODE, FEDERAL MANUFACTURING CODE, AND CIRCUIT DIAGRAM MARKED ON SWITCH

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

THIRD ANGLE PROJECTION



SCALE	NONE
DO NOT SCALE PRINT	
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
ONE PLACE	(.0) ± .030
TWO PLACE	(.00) ± .015
THREE PLACE	(.000) ± .005
ANGLES	±
WEIGHT	

CHARACTERISTICS	ELECTRICAL DATA
OPERATING FORCE ----- 4.5 LBS MAX	CONTACT ARRANGEMENT
RELEASE FORCE ----- .25 LBS MIN	2X S P D T
DIFFERENTIAL TRAVEL -- .031 MAX	11 AMPS AND 1/3 HP, 125, 250, OR 277 VAC
OVERTRAVEL ----- .250 MIN	1/2 AMP, 125 VDC; 1/4 AMP, 250 VDC
FULL OVERTRAVEL FORCE ----- 14 LBS MAX	4 AMPS, 125 VAC "L" (LAMP LOAD)

CATALOG LISTING
2PF1
PAGE 1 OF 1
ISSUE 2
REPLACES PR-24204
RELEASE NO.
CHECK
REVISIONS
A 0001616
JAH 13OCT03
CHECK
13 AUG 99
J A F
CHECK
13 AUG 99
J J A
DRAWN