

SiC Schottky Diodes thinQ!™

Second Generation now available in TO-220 FullPAK

High efficiency and thermal performance combine in a full isolated solution

The new FullPAK solution combines the high electrical performance standards of Infineon second generation SiC Schottky diodes and the advantages of a full isolated package, without significant impact on thermal behavior compared to standard TO-220 solutions.

The patented diffusion soldering technique enables to consistently reduce the "Chip-to-leadframe" thermal resistance and positions Infineon FullPAK products as best-in-class performance. Additionally, Infineon offers the industry's broadest portfolio in this package with current ratings up to 6A.

Comparison of the thermal resistance between standard IFX TO-220 and TO-220 FullPAK, and available competition FullPAK products:



The graph shows the same junction-case thermal resistance for IFX products at 2A and 3A, and slightly higher values for the other current ratings. This small difference is in general compensated on the final design assembly due to the need of an isolation foil for the standard TO-220 package. A clear advance on competition (only products up to 3A available) is possible thanks to IFX patented diffusion soldering.

Applications

- SMPS e.g. CCM PFC
- LCD, PDP
- Lighting
- UPS, Solar applications
- Motor drives

Features and benefits

- Thermal behavior comparable to non-isolated package thanks to Infineon diffusion soldering
- Best thermal performance for full-pack solutions
- Comparable price to non isolated package
- Mounting without isolating bushing and foil



SiC Schottky Diodes thinQ!™

Second Generation now available in TO-220 FullPAK

SiC thinQ!™ TO-220 FullPAK Product Portfolio

Voltage (V)	IF (A)	RTH JC (°K/W)	Product	Status
600	2	8,5	IDVo2S6oC	in production
600	3	5,9	IDVo3S6oC	in production
600	4	5,6	IDVo4S6oC	in production
600	5	5	IDVo5S6oC	in production
600	6	4,5	IDVo6S6oC	in production

Infineon delivers innovative high-performance solutions with best-in-class technologies help saving energy and reduce pollution. Our products are the basis for intelligent and optimal use of energy resources and are suited to meet the always rising expectations of customers and institutions in terms of energy efficiency.

Infineon SiC Schottky diode portfolio can concretely help meeting such demands and make your products fulfill the more and more required certification standards such as ENERGY STAR.







How to reach us: http://www.infineon.com

Published by Infineon Technologies AG 81726 Munich, Germany

© 2009 Infineon Technologies AG All Rights Reserved. **Legal Disclaimer** The information given in this Product Brief shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Wamings Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Order Number: B152-H9468-X-X-7600

DB2010-0002