



| JKL PART NUMBER | LENGTH A +/- 2mm | COLOR (REF.) | STARTING CIRCUIT VOLTAGE VS (Vrms) | OPERATING LAMP VOLTAGE VL (Vrms) | OPERATING LAMP CURRENT IL (mAmps) | BRIGHTNESS (CANDELA/m2) | *RATED LIFE (HRS) |
|-----------------|------------------|------------------------------------|------------------------------------|----------------------------------|-----------------------------------|-------------------------|-------------------|
| BF5118-20B | 118mm | RGB HIGH OUTPUT WHITE 5400° KELVIN | 600 | 305 | 5 ± 1 | 7000 ± 700 | 20,000 |
| BF5165-20B | 165mm | | 800 | 400 | 5 ± 1 | 7000 ± 700 | 20,000 |
| BF5200-20B | 200mm | | 850 | 445 | 5 ± 1 | 7000 ± 700 | 20,000 |
| BF5300-20B | 300mm | | 1000 | 600 | 5 ± 1 | 7000 ± 700 | 20,000 |

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

| | | | | | | | |
|---|--|---|--|--|--|---------------------------------------|--|
| | | METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0 | | JKL COMPONENTS CORPORATION | | | |
| | | | | TITLE SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP | | | |
| DRAWN BY L. WENGSTROM | | APPV'D BY JK | | DATE 02/29/00 | | SIZE A | |
| RELEASED - CANCEL BF-5mm DIA DRAWING | | DATE 2/25/00 | | FSCM NO. 55335 | | DRAWING NO. BF 5-20B | |
| REV. NO. | | DESCRIPTION/ECO NUMBER | | SCALE NONE | | RELEASED DATE 2/25/00 | |
| | | APPV'D DATE | | REVISION DATE 2/29/00 | | REV. NO. A | |
| - CAD DRAWING - MANUAL REVISIONS NOT PERMITTED | | | | | | SHEET 1 of 1 | |