


anti-surge power type leaded resistor



features

- Excellent anti-surge characteristics
- Stable characteristics of moisture resistance up to high resistance range
- RCR50 +(1M Ω - 12M Ω), RCR50EN (1M Ω - 12M Ω) and RCR60 (1M Ω - 12M Ω) are discharge resistors recognized by UL1676 and c-UL(CSA-C22.2 No.1-M94)
- RCR25EN (100k Ω ~33M Ω), RCR50EN (100k Ω - 33M Ω) and RCR60 (100k Ω - 56M Ω) is approved by EN60065 14.1 safety
- Marking: Blue-gray body color with color-coded bands
- Products with lead-free terminations meet EU RoHS requirements. EU RoHS regulation is not intended for Pb-glass contained in electrode, resistor element and glass.
- Surface mount style "N" forming is suitable for automatic mounting

dimensions and construction



* Lead length changes depending on taping and forming.

Type	Dimensions inches (mm)					
	L	C (max.)	t (max.)	D	d (nom.)	I*
RCR16	.126 \pm .008 (3.2 \pm 0.2)	.134 (3.4)	—	.067 ^{+0.08} _{-.004} (1.7 ^{+0.2} _{-.01})	.018 (0.45)	.787 Min. (20.0 Min.)
RCR25 RCR25EN	.248 \pm .02 (6.3 \pm 0.5)	.28 (7.1)	—	.098 \pm .02 (2.5 \pm 0.5)	.024 (0.6)	
RCR50(+) RCR50EN	.374 \pm .039 (9.5 \pm 1.0)	—	.118 (3.0)	.138 \pm .016 (3.5 \pm 0.4)	.028 (0.7)	
RCR60	.374 ^{+0.039} _{-.004} (9.5 ^{+1.0} _{-.02})	—	.118 (3.0)	.157 \pm .02 (4.0 \pm 0.5)	.031 (0.8)	
RCR75	.472 \pm .039 (12 \pm 1.0)	—	.118 (3.0)	.157 \pm .02 (4.0 \pm 0.5)	.031 (0.8)	
RCR100	.610 \pm .039 (15.5 \pm 1.0)	—	.118 (3.0)	.236 ^{+0.039} _{-.016} (6.0 ^{+1.0} _{-.04})	.031 (0.8)	

ordering information

New Part #	RCR	50	EN	C	T52	A	105	J
Type	RCR	Power Rating	Safety Appr. Marking	Termination Material	Taping and Forming	Packaging	Nominal Resistance	Tolerance
		16: 0.25W 25: 0.25W 50: 0.5W 60: 1W 75: 2W 100: 3W	RCR50+: + RCR25EN, RCR50EN: EN Blank: Others	C: SnCu	RCR16: T26, T52 RCR25, RCR25EN: T26, T52 RCR50(+, EN): T52 RCR60: T52 RCR75: T52 RCR100: T521, T631 L, M, N Forming	A: Ammo R: Reel TEB: Plastic embossed: N forming	2 significant figures + 1 multiplier for \pm 5% 3 significant figures + 1 multiplier for \pm 1%	F: \pm 1% J: \pm 5%

applications and ratings

Part Designation	Power Rating @ 70°C	Minimum Dielectric Withstanding Voltage	Resistance Range E-24, E-96 (F \pm 1%)	Resistance Range E-24 (J \pm 5%)	Absolute Maximum Working Voltage	Absolute Maximum Overload Voltage	Operating Temperature Range
RCR16	0.25W	300V	100k Ω - 5.1M Ω	100k Ω - 5.1M Ω	500V	1000V	-55°C to +155°C
RCR25 RCR25EN							
RCR50	0.5W	700V	3.3 Ω - 910k Ω	3.3 Ω - 910k Ω	2000V	2500V	
RCR50+				13M Ω - 33M Ω			
RCR50EN				1M Ω - 9.1M Ω			
RCR60	1.0W	1000V	100k Ω - 9.1M Ω	100k Ω - 56M Ω	4000V	5000V	
RCR75	2.0W						
RCR100	3.0W	1000V	100k Ω - 9.1M Ω	100k Ω - 51M Ω	5000V	5000V	


For further information on packaging, please refer to Appendix C.

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

11/29/16

environmental applications

Derating Curve




For resistors operated at an ambient temperature of 70°C or above, a power rating shall be derated in accordance with the above derating curve.

Notice of Surge Load

Surge withstanding load voltage for the resistors cannot be guaranteed when the undermentioned 4 items get to a remarkable overload in comparison with the conditions shown by surge withstanding voltage in Anti-surge characteristics. Please contact KOA in advance if such a case is anticipated.

1. Peak voltage to be applied
2. Pulse width
3. Conditions of protecting insulation around the resistor
4. Situation of proximity conductivity object

For example: In the figure, a metal wire is placed less than 5mm away from the resistor body, there is such a case that causes an electric discharge by a surge load 10kV and then destroys the outer coating.



Performance Characteristics

Parameter	Requirement $\Delta R \pm(\% + 0.05\Omega)$ Limit	Typical	Test Method																										
Resistance	Within regulated tolerance	—	Measuring points are 10mm \pm 1mm from the end cap																										
T.C.R.	<table border="1"> <thead> <tr> <th>Type</th> <th>T.C.R.</th> <th>Resistance Range</th> </tr> </thead> <tbody> <tr> <td>RCR16</td> <td>$\pm 200\text{ppm}/^\circ\text{C}$</td> <td>100k$\Omega$ - 5.1MΩ</td> </tr> <tr> <td>RCR25 (EN)</td> <td>$\pm 350\text{ppm}/^\circ\text{C}$</td> <td>100k$\Omega$ - 33MΩ</td> </tr> <tr> <td rowspan="2">RCR50 (+)</td> <td>$\pm 500\text{ppm}/^\circ\text{C}$</td> <td>3.3$\Omega$ - 91kΩ</td> </tr> <tr> <td>$\pm 350\text{ppm}/^\circ\text{C}$</td> <td>100k$\Omega$ - 33MΩ</td> </tr> <tr> <td>RCR50EN</td> <td>$\pm 350\text{ppm}/^\circ\text{C}$</td> <td>100k$\Omega$ - 33MΩ</td> </tr> <tr> <td>RCR60</td> <td>$\pm 350\text{ppm}/^\circ\text{C}$</td> <td>100k$\Omega$ - 56MΩ</td> </tr> <tr> <td>RCR75</td> <td>$\pm 350\text{ppm}/^\circ\text{C}$</td> <td>100k$\Omega$ - 100MΩ</td> </tr> <tr> <td>RCR100</td> <td>$\pm 200\text{ppm}/^\circ\text{C}$</td> <td>100k$\Omega$ - 51MΩ</td> </tr> </tbody> </table>	Type	T.C.R.	Resistance Range	RCR16	$\pm 200\text{ppm}/^\circ\text{C}$	100k Ω - 5.1M Ω	RCR25 (EN)	$\pm 350\text{ppm}/^\circ\text{C}$	100k Ω - 33M Ω	RCR50 (+)	$\pm 500\text{ppm}/^\circ\text{C}$	3.3 Ω - 91k Ω	$\pm 350\text{ppm}/^\circ\text{C}$	100k Ω - 33M Ω	RCR50EN	$\pm 350\text{ppm}/^\circ\text{C}$	100k Ω - 33M Ω	RCR60	$\pm 350\text{ppm}/^\circ\text{C}$	100k Ω - 56M Ω	RCR75	$\pm 350\text{ppm}/^\circ\text{C}$	100k Ω - 100M Ω	RCR100	$\pm 200\text{ppm}/^\circ\text{C}$	100k Ω - 51M Ω	—	+25°C/+125°C
Type	T.C.R.	Resistance Range																											
RCR16	$\pm 200\text{ppm}/^\circ\text{C}$	100k Ω - 5.1M Ω																											
RCR25 (EN)	$\pm 350\text{ppm}/^\circ\text{C}$	100k Ω - 33M Ω																											
RCR50 (+)	$\pm 500\text{ppm}/^\circ\text{C}$	3.3 Ω - 91k Ω																											
	$\pm 350\text{ppm}/^\circ\text{C}$	100k Ω - 33M Ω																											
RCR50EN	$\pm 350\text{ppm}/^\circ\text{C}$	100k Ω - 33M Ω																											
RCR60	$\pm 350\text{ppm}/^\circ\text{C}$	100k Ω - 56M Ω																											
RCR75	$\pm 350\text{ppm}/^\circ\text{C}$	100k Ω - 100M Ω																											
RCR100	$\pm 200\text{ppm}/^\circ\text{C}$	100k Ω - 51M Ω																											
Overload	1%	0.5%	Rated voltage x 2.5 or maximum overload voltage for 5 seconds, whichever is less																										
Resistance to Solder Heat	1%	0.5%	260°C \pm 5°C, 10 seconds \pm 1 second or 350°C \pm 10°C, 3.5 seconds \pm 0.5 seconds																										
Terminal Strength	No mechanical damage	—	Twist 360°, 5 times																										
Rapid Change of Temperature	1%	0.5%	-55°C (30 minutes)/+155°C (30 minutes), 5 cycles																										
Moisture Resistance	5%	2.5%	40°C \pm 2°C, 90-95% RH, 1000 hours, 1.5 hr ON, 0.5 hr OFF cycle RCR16, 25, 50 (+), 60: W; RCR75, 100: Wx0.1																										
Endurance @ 70°C	5%	2.5%	70°C \pm 2°C, 1000 hours, 1.5 hr ON, 0.5 hr OFF cycle																										
Resistance to Solvent	No visible damage to protective coating and marking	—	Isopropyl alcohol with ultrasonic washing, 2 minutes Power: 0.3W/cm ² , f: 28kHz, Temperature: 35°C \pm 5°C																										
Surge Withstanding	10%	2.5%	Discharge test: 2kV - 10kV, 0.01 μ F capacitor discharge pulse, 10 times (1 pulse/5 seconds maximum) <table border="1"> <thead> <tr> <th>Type</th> <th>RCR16</th> <th>RCR25 RCR25EN</th> <th>RCR50, RCR50+</th> <th>RCR50EN, RCR60, RCR75, RCR100</th> </tr> </thead> <tbody> <tr> <td rowspan="4">Applied Voltage</td> <td rowspan="4">2kV</td> <td rowspan="4">3kV</td> <td>3.3Ω - 6.2Ω: 10kV</td> <td rowspan="4">10kV</td> </tr> <tr> <td>6.8Ω - 10Ω: 7kV</td> </tr> <tr> <td>11Ω - 9.1kΩ: 5kV</td> </tr> <tr> <td>10kΩ - 91kΩ: 7kV</td> </tr> <tr> <td></td> <td></td> <td></td> <td>100kΩ - 33MΩ: 10kV</td> <td></td> </tr> </tbody> </table>	Type	RCR16	RCR25 RCR25EN	RCR50, RCR50+	RCR50EN, RCR60, RCR75, RCR100	Applied Voltage	2kV	3kV	3.3 Ω - 6.2 Ω : 10kV	10kV	6.8 Ω - 10 Ω : 7kV	11 Ω - 9.1k Ω : 5kV	10k Ω - 91k Ω : 7kV				100k Ω - 33M Ω : 10kV									
Type	RCR16	RCR25 RCR25EN	RCR50, RCR50+	RCR50EN, RCR60, RCR75, RCR100																									
Applied Voltage	2kV	3kV	3.3 Ω - 6.2 Ω : 10kV	10kV																									
			6.8 Ω - 10 Ω : 7kV																										
			11 Ω - 9.1k Ω : 5kV																										
			10k Ω - 91k Ω : 7kV																										
			100k Ω - 33M Ω : 10kV																										
EN60065 Test (RCR50EN, RCR60 only)	20%	—	Discharge test: 10kV, 1000pF capacitor discharge pulse, 50 times (1 pulse/5 seconds maximum)																										