



DATE	DESCRIPTION	REV.
8.11.99	CHANGE AS PER ECN 99-056	A
6.8.05	CHANGE AS PER ECN 05-032	B
9.22.08	CHANGE AS PER ECN 08-162	C
12.15.09	CHANGE AS PER ECN 09-186	D
1.13.12	CHANGE AS PER ECN 12-006	E

Notes:

- Shell: Mat'l: Phosphor Bronze,
Finish: Tin Plate over Nickel Plate.
- Insulator: Glass Filled LCP
- Contacts: Mat'l: Phosphor Bronze
Finish: Contact Area -Gold Plate over Nickel Plate
Solder Tail - Tin Plate over Nickel Plate

Electrical Specifications

- Contact Resistance: 30 milliohms Max.
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance : 1000 Mohms Min.
- Operating Temperature: -25°C to 85°C
- Durability min. : 1500 cycles.

KEYSTONE ELECTRONICS CORP.

www.keystone.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900

PART NAME

USB A-TYPE HORIZONTAL SOCKET

MATERIAL

AS NOTED

FINISH

AS NOTED

TOLERANCES	INCH	[MM]	CODE	DWG NO.
DECIMAL	± .010	[± 0.25]	C/M	
ANGULAR	± 1°			

THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED, DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.

DRN BY: BOONE DATE: 6.18.98

App'd: LN SCALE: 2.5X

921