CPI0806J1R2R-10

UNCONTROLLED DOCUMENT

PHYSICAL DIMENSIONS:

A	2.00 [.079]	± 0.15[.006]
B	1.60 [.063]	± 0.15[.006]
C	0.90 [.035]	± 0.10[.004]
D	0.50 [.020]	± 0.20[.008]



Pb

ELECTRICAL CHARACTERISTICS:

	L (μH) @ 1MHz ± 20%	DCR (Ω) ± 30%	I (Max)
Nom	1.20	0.160	
Min	0.96	0.112	
Max	1.44	0.208	1400mA

NOTES: UNLESS OTHERWISE SPECIFIED
1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 3000 PCS/REEL, EMBOSSED PLASTIC TAPE.
2. TERMINATION FINISH IS 100% MATTE Sn OVER Ni.
3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
4. I (MAX.) IS BASED ON THE MAXIMUM SUSTAINED CURRENT APPLIED WHILE MAINTAINING A MAXIMUM TEMPERATURE RISE OF 40°C OVER AMBIENT.
5. OPERATION TEMPERATURE TEMP: −55°C~+125°C (INCLUDING SELF−HEATING)

Ls vs Frequency



Ls vs DC BIAS Current



LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering. add 0.763 [0.030] to this dimension)

RECOMMENDED SOLDERING CONDITIONS



RoHS 2002/95/EC

DIMENSIONS ARE IN mm [INCHES].

REV	DESCRIPTION	DATE	INT
B	UPDATE LAIRD LOGO AND NOTES 5	08/05/13	QU
A	ORIGINAL DRAFT	03/01/11	QU

This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.

Laird

PROJECT/PART NUMBER:	REV	PART TYPE:	DRAWN BY:
CPI0806J1R2R−10	B	CO−FIRE	QU

DATE:	SCALE:	SHEET:
03/01/11	NTS	2 of 2

CAD # CPI0806J1R2R−10−B TOOL # −