



The Bluetooth® Intelligent Serial Module is specifically designed for applications where robust short range connectivity is required. This particular module provides a reliable Bluetooth connection that exceeds all requirements in terms of performance. The excellent range of up to 300 meters with very low power consumption of less than 36 mA makes this module a true class leader.

#### Key Features

- Best-in-class range provides open field connectivity in excess of 300 meters
- Integrated high-performance ceramic antenna
- Adaptive frequency hopping to cope with interference from other wireless products
- Optimised receive sensitivity to provide long range initial connections that largely eliminate connection hysteresis
- A full industrial operating temperature range of -40°C to +85°C
- Data transfer rate up to 300 kbps
- Fully approved product
- Class 1 version 2.0 Bluetooth
- Receive sensitivity better than -84 dBm
- Support for 128 bit encryption
- Non-discoverable modes
- 40 way Hirose connector
- 2 X 8 bit ADCs
- 9 X GPIO
- Low power modes
- Lead free
- 2 year warranty
- Supports Wi-Fi co-existence
- Embedded Bluetooth stack
- Integrated antenna with up to 300m range
- External antenna version available

#### global solutions: local support..

USA: +1.800.492.2320  
Europe: +44.1628.858.940  
Asia: +852.2268.6567

wirelessinfo@lairdtech.com  
www.lairdtech.com/wireless

As well as incorporating a fully approved embedded Bluetooth protocol stack, the module includes a comprehensive AT style interface that dramatically reduces the development time of applications from months to days.

FEATURE	IMPLEMENTATION
Bluetooth®	Class 1
Frequency	2.402 – 2.480 GHz
Max Transmit Power	+6 dBm (internal antenna - TRBLU23-00200) +4 dBm (at u.fl connector - TRBLU-23-00300)
Min Transmit Power	-27 dBm
Low Power Sniff	2.5 mA typical
Receive Sensitivity	Better than -84dB
Range	300m (free space)
Serial Interface	3.3 V UART
GPIO	9 x digital GPIO
Serial Parameters	Default: 9600,n,8,1 From 1200 bps to 921.6 kbps DTR, DRS, RTS, CTS, DCD, RI DCE or DTE mode
Current Consumption	Idle mode = 13mA Connected as master = 20mA
Physical Size	25.0 x 35.0 x 7.6 mm, 8 g
Antenna	Internal – Multilayer Ceramic External – Connection via U.FL connector
Bluetooth Qualified	Bluetooth 2.0
Lead Free	RoHS Compliant
Temperature Range	-40°C to +85°C
Interface Levels	3.3 V
Audio	Supported
Multipoint	Supported
Field Upgrades	Over UART
ADC	2 x 8bit
Protocols	UART, AT command set, Multipoint
Data Transfer Rate	Up to 300 kbps

## Ordering Information

TRBLU23-00200	Bluetooth Serial Module with integrated antenna
TRBLU23-00300	Bluetooth Serial Module with U.FL connector for external antenna

The details contained within the document are subject to change. Download the product specification from [www.lairdtech.com/wireless](http://www.lairdtech.com/wireless) for the most current specification.

LWS-DS-TRBLU23\_0713

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non-infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2012 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.