



- NOTES:
1. NUT IS TO ACCEPT A TORQUE OF 18 LB.-IN. WITHOUT CRACKING OR STRIPPING
  2. THE STARTING POINT OF THE LEAD THREAD CANNOT EXCEED .030 FROM SURFACE [A].
  3. "FLASH EXTENDING ABOVE SURFACE [A] CANNOT EXCEED .006 HIGH AND .004 THICK.

PACKAGING NOTES:  
 PLACE IN TOTE -580599 LINED WITH POLY BAG -890-750  
 LABEL TOTE WITH -914-796 PRINTED PER GENERAL LABEL  
 SPEC. LS-000003.

|    |              |               |             |       |      |
|----|--------------|---------------|-------------|-------|------|
| 1  | 057295       | RYNITE 415 HP | DESCRIPTION | LB    | 2.25 |
| NO | COMPONENT NO |               |             | QTY/M | U/M  |

| BILL OF MATERIAL |           |        |                                      |
|------------------|-----------|--------|--------------------------------------|
| CDPIES TO        | MATL SPEC | FINISH |                                      |
| 1                | 9 18      | DRW    | SCALE 4:1                            |
| 2                | 10 19     | KAM    | DATE 1/23/97                         |
| 3                | 12 20     | CHK    | SUPER DRW                            |
| 4                | 13 21     | APPD   | RAW STK WT                           |
| 5                | 14 23     |        | LBS/M                                |
| 6                | 15 33     |        | TOLERANCE UNLESS OTHERWISE SPECIFIED |
| 7                | 16 43     |        | TWO PLACE DEC ±.01                   |
| 8                | 17 53     |        | THREE PLACE DEC ±.005                |
|                  |           |        | ANGULAR ±1°                          |

|                              |           |                 |  |
|------------------------------|-----------|-----------------|--|
| TITLE                        |           | HEX NUT, MOLDED |  |
| REVISION                     | DRWS. NO. | 903-097         |  |
| M                            |           |                 |  |
| DES PLAINES, ILL INOIS 60016 |           | Litetfuse®      |  |

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.  
 DENOTES CRITICAL CHARACTERISTICS.  
 DENOTES CPK DIMENSIONS - MINIMUM CPK VALUE  
 DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF THE TESTING TO BE USED IN THE INSPECTION PROCEDURE FOR MEASUREMENT OF THIS CHARACTERISTIC. THE TESTING TO BE USED IS INDICATED IN THE INSTRUCTIONS.  
 DENOTES CP DIMENSIONS - MINIMUM CP VALUE  
 DENOTES THE DIMENSIONAL LIMITATIONS WHICH APPLY TO THIS DIMENSION. THE DIMENSIONAL LIMITATIONS ARE LISTED FOR MAXIMUM TOOL LIFE.

| LTR | REVISION   | CHK | APD |
|-----|--|-----|-----|
| K   | 39068C-REVISE & REDRAWN IN NEW STRUCTURE 4/16/98 KAM |     |     |
| L   | 39682C-CHG. 0.845 TO .7896 03/22/99 PJM              |     |     |
| M   | 80635C-CHG. .7896 TO 2.25 08/22/00 PJM               |     |     |

UNCONTROLLED DOCUMENT