

# Fuseholders

For Micro™ Fuse or Pico® II Fuses

## “Push-On” Retaining Nut Chassis Mount Type


QPL

Fuseholder will accept Littelfuse MICRO™ fuses and PICO® II fuses (rated to 5 amperes) with .025" diameter leads.


**SPECIFICATIONS:**

- Electrical:** Rated at 5 amperes for any voltage up to 125 volts.
- Mounting:** Maximum panel thickness is .09".
- Molded Parts:** Black Thermoset.
- Terminals:** Beryllium Copper, Silver-plated.
- Ambient Temperature:** -40°C to +125°C.
- Hardware:** “Push-On” retaining nut.

\* Please refer to Fuseology section for information on proper fuseholder de-rating.



**MOUNTING HOLE**



### FOR MICRO™ FUSE OR PICO® II FUSES

## Vertical/Horizontal P.C. Board Mount Type



Fuseholder will accept Littelfuse MICRO™ fuses and PICO® II fuses (rated to 5 amperes) with .025" diameter leads.

**SPECIFICATIONS:**


- Electrical:** Rated at 5 amperes for any voltage up to 125 volts.
- Molded Parts:** White Thermoplastic.
- Terminals:** Copper Alloy.
- Ambient Temperature:** -40°C to +100°C.

**ORDERING INFORMATION:**



Catalog Number	Terminal Plating	Mounting
281 005	Silver <sup>1</sup>	Vertical
281 008	Tin	Vertical
281 007	Silver <sup>1</sup>	Horizontal
281 010	Tin	Horizontal

<sup>1</sup>UL Recognized.


\* Please refer to Fuseology section for information on proper fuseholder de-rating.



**Circuit Board Mounting Detail**



**Circuit Board Mounting Detail (Component Side)**



## For LT-5™ and TR5® Fuses P.C. Board Mount Type

See 560 Series holder for new designs and replacement.

**SPECIFICATIONS:**

- Electrical:** Rated at 5 amperes for any voltage up to 250 volts.
- Molded Parts:** Black Thermoplastic (UL94 V-O).
- Terminals:** Tin-plated brass/gold inside.

**ORDERING INFORMATION:**  
Catalog Number: 021-000

\* Please refer to Fuseology section for information on proper fuseholder de-rating.

# OBSOLETE

