

ELECTRO-OPTICAL CHARACTERISTICS  $T_A=25^{\circ}\text{C}$   $I_f=20\text{mA}$

| PARAMETER   | YELLOW | GREEN | UNITS    | TEST COND            |
|---|--------|-------|----------|----------------------|
| PEAK WAVELENGTH                                   | 585    | 565   | nm       |                      |
| FORWARD VOLTAGE (TYP.)                            | 2.1    | 2.2   | $V_f$    |                      |
| FORWARD VOLTAGE (MAX.)                            | 2.5    | 2.6   | $V_f$    |                      |
| REVERSE VOLTAGE (TYP.)                            | 5.0    | 5.0   | $V_r$    | $I_r=100\mu\text{A}$ |
| AXIAL INTENSITY (TYP.)                            | 30     | 30    | mcd      | $I_f=20\text{mA}$    |
| AXIAL INTENSITY (MIN.)                            | 1.0    | 1.0   | mcd      | $I_f=2\text{mA}$     |
| VIEWING ANGLE                                     | 60     | 60    | 2x theta |                      |
| LED POSITION:                                     | 1      | 2     |          |                      |
| EPOXY LENS FINISH: DIFFUSED SAME AS EMITTED COLOR |        |       |          |                      |

LIMITS OF SAFE OPERATION AT  $25^{\circ}\text{C}$

| PARAMETER                        | COLORS | MAX        | UNITS                  |
|----------------------------------|--------|------------|------------------------|
| PEAK FORWARD CURRENT*            |        | 150        | mA                     |
| STEADY CURRENT                   | (Y/G)  | 30/25      | mA                     |
| POWER DISSIPATION                |        | 105        | mW                     |
| DERATE FROM $25^{\circ}\text{C}$ |        | -1.6       | mW/ $^{\circ}\text{C}$ |
| OPERATING, STORAGE TEMP.         |        | -40 TO +85 | $^{\circ}\text{C}$     |
| SOLDERING TEMP.                  |        | +260       | $^{\circ}\text{C}$     |
| 2.0mm FROM BODY                  |        |            | 3 SEC. MAX             |


\*  $t < 10\mu\text{s}$

NOTES:

1. SSL-LX3054LYD, LOW CURRENT YELLOW LED.
2. SSL-LX3054LGD, LOW CURRENT GREEN LED.
3. SSH-LXH2103 HOLDER.



\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.=+DECIMAL PRECISION MAX.=+0.00 -DECIMAL PRECISION

|   |                                  |  |   |
|---|----------------------------------|--|---|
| REV.  | PART NUMBER<br>SSF-LXH2103LYGD/4 | CONFIDENTIAL INFORMATION<br>THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. | 290 E. HELEN ROAD<br>PALATINE, IL 60067-6976<br>PHONE: +1.847.359.2790<br>US WEB: www.lumex.com<br>TW WEB: www.lumex.com.tw |
| T-3mm (T-1) LED, PIGGY-BACK HOLDER,<br>POS.1: 585nm YELLOW, POS.2: 565nm GREEN,<br>LOW CURRENT SELECTION. |                                  | RELIABILITY NOTE<br>OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.   |                                        |
|   |                                  | DRAWN BY: CT   | CHECKED BY: APPROVED BY: DATE: 5.5.03<br>PAGE: 1 OF 1<br>SCALE: N/A   |