

# BC337, BC337-25, BC337-40

## Amplifier Transistors

### NPN Silicon

#### Features

- These are Pb-Free Devices

#### MAXIMUM RATINGS

| Rating   | Symbol         | Value       | Unit                       |
|--|----------------|-------------|----------------------------|
| Collector – Emitter Voltage  | $V_{CEO}$      | 45          | Vdc                        |
| Collector – Base Voltage   | $V_{CBO}$      | 50          | Vdc                        |
| Emitter – Base Voltage   | $V_{EBO}$      | 5.0         | Vdc                        |
| Collector Current – Continuous   | $I_C$          | 800         | mAdc                       |
| Total Device Dissipation @ $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 625<br>5.0  | mW<br>mW/ $^\circ\text{C}$ |
| Total Device Dissipation @ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 1.5<br>12   | W<br>mW/ $^\circ\text{C}$  |
| Operating and Storage Junction<br>Temperature Range                                    | $T_J, T_{stg}$ | -55 to +150 | $^\circ\text{C}$           |

#### THERMAL CHARACTERISTICS


| Characteristic                          | Symbol          | Max  | Unit                      |
|---|-----------------|------|---------------------------|
| Thermal Resistance, Junction-to-Ambient | $R_{\theta JA}$ | 200  | $^\circ\text{C}/\text{W}$ |
| Thermal Resistance, Junction-to-Case    | $R_{\theta JC}$ | 83.3 | $^\circ\text{C}/\text{W}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.




ON Semiconductor®


<http://onsemi.com>



TO-92  
CASE 29  
STYLE 17



#### MARKING DIAGRAM



BC337-xx = Device Code  
(Refer to page 4)

A = Assembly Location

Y = Year

WW = Work Week

▪ = Pb-Free Package

(Note: Microdot may be in either location)

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 4 of this data sheet.

# BC337, BC337-25, BC337-40

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C unless otherwise noted)

| Characteristic   | Symbol               | Min | Typ | Max | Unit |
|--|----------------------|-----|-----|-----|------|
| <b>OFF CHARACTERISTICS</b>   |                      |     |     |     |      |
| Collector - Emitter Breakdown Voltage<br>(I <sub>C</sub> = 10 mA, I <sub>B</sub> = 0)  | V <sub>(BR)CEO</sub> | 45  | -   | -   | Vdc  |
| Collector - Emitter Breakdown Voltage<br>(I <sub>C</sub> = 100 μA, I <sub>E</sub> = 0) | V <sub>(BR)CES</sub> | 50  | -   | -   | Vdc  |
| Emitter - Base Breakdown Voltage<br>(I <sub>E</sub> = 10 μA, I <sub>C</sub> = 0)       | V <sub>(BR)EBO</sub> | 5.0 | -   | -   | Vdc  |
| Collector Cutoff Current<br>(V <sub>CB</sub> = 30 V, I <sub>E</sub> = 0)               | I <sub>CBO</sub>     | -   | -   | 100 | nAdc |
| Collector Cutoff Current<br>(V <sub>CE</sub> = 45 V, V <sub>BE</sub> = 0)              | I <sub>CES</sub>     | -   | -   | 100 | nAdc |
| Emitter Cutoff Current<br>(V <sub>EB</sub> = 4.0 V, I <sub>C</sub> = 0)                | I <sub>EBO</sub>     | -   | -   | 100 | nAdc |

## ON CHARACTERISTICS

|   |                               |                 |     |     |     |   |
|---|-------------------------------|-----------------|-----|-----|-----|---|
| DC Current Gain<br>(I <sub>C</sub> = 100 mA, V <sub>CE</sub> = 1.0 V)<br><br>(I <sub>C</sub> = 300 mA, V <sub>CE</sub> = 1.0 V) | BC337<br>BC337-25<br>BC337-40 | h <sub>FE</sub> | 100 | -   | 630 | - |
|   |                               |                 | 160 | -   | 400 | - |
|   |                               |                 | 250 | -   | 630 | - |
|   |                               |                 | 60  | -   | -   | - |
| Base-Emitter On Voltage<br>(I <sub>C</sub> = 300 mA, V <sub>CE</sub> = 1.0 V)   | V <sub>BE(on)</sub>           | -               | -   | 1.2 | Vdc |   |
| Collector - Emitter Saturation Voltage<br>(I <sub>C</sub> = 500 mA, I <sub>B</sub> = 50 mA)                                     | V <sub>CE(sat)</sub>          | -               | -   | 0.7 | Vdc |   |

## SMALL-SIGNAL CHARACTERISTICS

|  |                 |   |     |   |     |
|--|-----------------|---|-----|---|-----|
| Output Capacitance<br>(V <sub>CB</sub> = 10 V, I <sub>E</sub> = 0, f = 1.0 MHz)                      | C <sub>ob</sub> | - | 15  | - | pF  |
| Current - Gain - Bandwidth Product<br>(I <sub>C</sub> = 10 mA, V <sub>CE</sub> = 5.0 V, f = 100 MHz) | f <sub>T</sub>  | - | 210 | - | MHz |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.




Figure 1. Thermal Response

BC337, BC337-25, BC337-40




Figure 2. Active Region - Safe Operating Area




Figure 3. DC Current Gain




Figure 4. Saturation Region




Figure 5. "On" Voltages




Figure 6. Temperature Coefficients




Figure 7. Capacitances

## BC337, BC337-25, BC337-40

### ORDERING INFORMATION


| Device        | Marking | Package            | Shipping†          |
|---------------|---------|--------------------|--------------------|
| BC337G        | 7       | TO-92<br>(Pb-Free) | 5000 Units / Bulk  |
| BC337RL1G     | 7       |                    | 2000 / Tape & Reel |
| BC337-025G    | 7-25    |                    | 5000 Units / Bulk  |
| BC337-25RL1G  | 7-25    |                    | 2000 / Tape & Reel |
| BC337-25RLRAG | 7-25    |                    | 2000 / Tape & Reel |
| BC337-25ZL1G  | 7-25    |                    | 2000 / Ammo Box    |
| BC337-040G    | 7-40    |                    | 5000 Units / Bulk  |
| BC337-40RL1G  | 7-40    |                    | 2000 / Tape & Reel |
| BC337-40ZL1G  | 7-40    |                    | 2000 / Ammo Box    |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.


# BC337, BC337-25, BC337-40

## PACKAGE DIMENSIONS

TO-92 (TO-226)  
CASE 29-11  
ISSUE AM




STRAIGHT LEAD  
BULK PACK




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

| DIM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 0.175  | 0.205 | 4.45        | 5.20  |
| B   | 0.170  | 0.210 | 4.32        | 5.33  |
| C   | 0.125  | 0.165 | 3.18        | 4.19  |
| D   | 0.016  | 0.021 | 0.407       | 0.533 |
| G   | 0.045  | 0.055 | 1.15        | 1.39  |
| H   | 0.095  | 0.105 | 2.42        | 2.66  |
| J   | 0.015  | 0.020 | 0.39        | 0.50  |
| K   | 0.500  | ---   | 12.70       | ---   |
| L   | 0.250  | ---   | 6.35        | ---   |
| N   | 0.080  | 0.105 | 2.04        | 2.66  |
| P   | ---    | 0.100 | ---         | 2.54  |
| R   | 0.115  | ---   | 2.93        | ---   |
| V   | 0.135  | ---   | 3.43        | ---   |



BENT LEAD  
TAPE & REEL  
AMMO PACK



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

| DIM | MILLIMETERS |      |
|-----|-------------|------|
|     | MIN         | MAX  |
| A   | 4.45        | 5.20 |
| B   | 4.32        | 5.33 |
| C   | 3.18        | 4.19 |
| D   | 0.40        | 0.54 |
| G   | 2.40        | 2.80 |
| J   | 0.39        | 0.50 |
| K   | 12.70       | ---  |
| N   | 2.04        | 2.66 |
| P   | 1.50        | 4.00 |
| R   | 2.93        | ---  |
| V   | 3.43        | ---  |

STYLE 17:

1. COLLECTOR
2. BASE
3. EMITTER

**ON Semiconductor** and **ON** are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative