

Sign Panels – Blank Space for Custom Messages

Indoor/Outdoor Sub-Surface Printed Adhesive Polyester (Type PPS)

- High quality signs for use indoors and outdoors
- Excellent resistance to UV light, chemical atmosphere, and abrasion
- Excellent life and adhesion properties
- Printed graphics are protected by clear polyester laminate






Indoor/Outdoor Rigid Polyethylene (Type PRS)

- Rugged signs for indoors and outdoors
- Abrasion resistant
- Used where adhesives will not work

- Can be used with Panduit Thermal Transfer Desktop Printers and Easy-Mark™ Labeling Software to create your own custom signs
- Print your own legend on clear polyester tape with the TDP43MY Thermal Transfer Desktop Printer and adhere label to adhesive or non-adhesive sign panel
- Can also be used with Panduit Die Cut Letter and Numbers

Material Chart

| Material | Print Method | Temperature Range | Features |
|--------------------------|--------------|-------------------------------------|---|
| Polyester (PPS) | Pre-Printed | -40°F to 275°F (-40°C to 135°C) | Indoor/outdoor rated; laminated label material protects legend from abrasion and chemicals; resistant to UV light, chemical atmosphere, and abrasion; excellent life and adhesion properties. |
| Rigid Polyethylene (PRS) | | -105°F to 250°F (-76°C to 121°C) | Indoor/outdoor rated; high quality, rugged material resistant to abrasion; use where adhesives will not work. |

| Part Number | Symbol | Header | Width | | Height | | Std. Pkg. Qty | Std. Ctn. Qty. |
|-------------|---|---------|-------|-------|--------|-------|---------------|----------------|
| | | | In. | mm | In. | mm | | |
| PPS0710BWHT |  | BLANK | 10.00 | 254.0 | 7.00 | 177.8 | 1 | 25 |
| PPS1014BWHT | | | 14.00 | 355.6 | 10.00 | 254.0 | 1 | 25 |
| PPS1420BWHT | | | 20.00 | 508.0 | 14.00 | 355.6 | 1 | 25 |
| PRS0710BWHT | | | 10.00 | 254.0 | 7.00 | 177.8 | 1 | 10 |
| PRS1014BWHT | | | 14.00 | 355.6 | 10.00 | 254.0 | 1 | 10 |
| PRS1420BWHT | | | 20.00 | 508.0 | 14.00 | 355.6 | 1 | 10 |
| PPS0710BYEL |  | BLANK | 10.00 | 254.0 | 7.00 | 177.8 | 1 | 25 |
| PPS1014BYEL | | | 14.00 | 355.6 | 10.00 | 254.0 | 1 | 25 |
| PPS1420BYEL | | | 20.00 | 508.0 | 14.00 | 355.6 | 1 | 25 |
| PRS0710BYEL | | | 10.00 | 254.0 | 7.00 | 177.8 | 1 | 10 |
| PRS1014BYEL | | | 14.00 | 355.6 | 10.00 | 254.0 | 1 | 10 |
| PRS1420BYEL | | | 20.00 | 508.0 | 14.00 | 355.6 | 1 | 10 |
| PPS0710C442 |  | CAUTION | 10.00 | 254.0 | 7.00 | 177.8 | 1 | 25 |
| PPS1014C442 | | | 14.00 | 355.6 | 10.00 | 254.0 | 1 | 25 |
| PPS1420C442 | | | 20.00 | 508.0 | 14.00 | 355.6 | 1 | 25 |
| PRS0710C442 | | | 10.00 | 254.0 | 7.00 | 177.8 | 1 | 10 |
| PRS1014C442 | | | 14.00 | 355.6 | 10.00 | 254.0 | 1 | 10 |
| PRS1420C442 | | | 20.00 | 508.0 | 14.00 | 355.6 | 1 | 10 |
| PPS0710D440 |  | DANGER | 10.00 | 254.0 | 7.00 | 177.8 | 1 | 25 |
| PPS1014D440 | | | 14.00 | 355.6 | 10.00 | 254.0 | 1 | 25 |
| PPS1420D440 | | | 20.00 | 508.0 | 14.00 | 355.6 | 1 | 25 |
| PRS0710D440 | | | 10.00 | 254.0 | 7.00 | 177.8 | 1 | 10 |
| PRS1014D440 | | | 14.00 | 355.6 | 10.00 | 254.0 | 1 | 10 |
| PRS1420D440 | | | 20.00 | 508.0 | 14.00 | 355.6 | 1 | 10 |
| PPS0710N443 |  | NOTICE | 10.00 | 254.0 | 7.00 | 177.8 | 1 | 25 |
| PPS1014N443 | | | 14.00 | 355.6 | 10.00 | 254.0 | 1 | 25 |
| PPS1420N443 | | | 20.00 | 508.0 | 14.00 | 355.6 | 1 | 25 |
| PRS0710N443 | | | 10.00 | 254.0 | 7.00 | 177.8 | 1 | 10 |
| PRS1014N443 | | | 14.00 | 355.6 | 10.00 | 254.0 | 1 | 10 |
| PRS1420N443 | | | 20.00 | 508.0 | 14.00 | 355.6 | 1 | 10 |

Order number of Standard Packages required

A.
System
Overview

B1.
Cable Ties

B2.
Cable
Accessories

B3.
Stainless
Steel Ties

C1.
Wiring
Duct

C2.
Surface
Raceway

C3.
Abrasion
Protection

C4.
Cable
Management

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
& Write-On
Markers

E4.
Permanent
Identification

E5.
Lockout/
Tagout/
& Safety
Solutions

F.
Index