



Part Number System for Pan-Term® Metric Terminals

| PM | V | 1 | — | 3 | R | B | — | C |
|-----------------------|---|---|---|---|----------------------|-----------------------|---|---|
| Type | Insulation | Wire Range | | Stud Size | Tongue Configuration | Special Configuration | | Std. Pkg. Size |
| PM = Pan-Term® Metric | N = Nylon NF = Nylon Funnel V = Vinyl | 1 = 0.5 – 1.0mm ² (22 – 18 AWG) 2 = 1.5 – 2.5mm ² (16 – 14 AWG) 6 = 4.0 – 6.0mm ² (12 – 10 AWG) | — | 3 = M3 (#6) 4 = M4 (#8) 5 = M5 (#10) 6 = M6 (1/4) 8 = M8 (5/16) | R = Ring F = Fork | B = Butted Seam | — | X = 10 E = 20 Q = 25 L = 50 C = 100 |

Metric Ring Terminal, Nylon Insulated – Funnel Entry

Type PMNF-R

- Ring tongue design assures a secure connection in high vibration applications
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- Maximum insulation temperature 221°F (105°C)
- Rated up to 600 V



| Part Number | Wire Range (mm ²) | Color Code | Max. Ins. (mm) | Stud Size | Figure Dimensions (mm) | | | Recommended Installation Tool | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|-------------------------------|------------|----------------|-----------|------------------------|------|------|-------------------------------|----------------|----------------|
| | | | | | L | W | C | | | |
| PMNF1-3R-C | 0.5 – 1.0 | Red | 3.76 | M3 | 19.3 | 5.8 | 5.3 | CT-1550, CT-2500 | 100 | 500 |
| PMNF1-4R-C | | | 3.76 | M4 | 21.6 | 7.9 | 6.4 | | 100 | 500 |
| PMNF1-5R-C | | | 3.76 | M5 | 21.8 | 8.9 | 6.4 | | 100 | 500 |
| PMNF1-6R-C | | | 3.76 | M6 | 26.7 | 10.9 | 9.7 | | 100 | 500 |
| PMNF2-3R-C | 1.5 – 2.5 | Blue | 4.11 | M3 | 19.4 | 5.9 | 4.8 | CT-1550, CT-2500 | 100 | 500 |
| PMNF2-4R-C | | | 4.11 | M4 | 21.8 | 7.9 | 7.4 | | 100 | 500 |
| PMNF2-5R-C | | | 4.11 | M5 | 22.4 | 8.9 | 7.4 | | 100 | 500 |
| PMNF2-6R-L | | | 4.11 | M6 | 26.5 | 10.9 | 10.7 | | 50 | 500 |
| PMNF6-3R-L | 4.0 – 6.0 | Yellow | 5.94 | M3 | 26.7 | 5.8 | 9.1 | CT-1550, CT-2500 | 50 | 250 |
| PMNF6-4R-L | | | 5.94 | M4 | 27.4 | 7.9 | 9.1 | | 50 | 250 |
| PMNF6-5R-L | | | 5.94 | M5 | 27.4 | 9.7 | 9.1 | | 50 | 250 |
| PMNF6-6R-L | | | 5.94 | M6 | 30.2 | 10.9 | 10.9 | | 50 | 250 |
| PMNF6-8R-L | | | 5.94 | M8 | 31.5 | 13.2 | 10.9 | | 50 | 250 |

For crimping tool information, see pages D1.84 and D1.88.

A. System Overview

B1. Cable Ties

B2. Cable Accessories

B3. Stainless Steel Ties

C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

D1. Terminals

D2. Power Connectors

D3. Grounding Connectors

E1. Labeling Systems

E2. Labels

E3. Pre-Printed & Write-On Markers

E4. Permanent Identification

E5. Lockout/Tagout & Safety Solutions

F. Index