



| PANDUIT PART NO. * | BUNDLE DIA. | | A in (mm) | B in (mm) | C in (mm) | D in (mm) | E in (mm) | F in (mm) | MIN. LOOP TENSILE lbs. (N) | CROSS SECTION | TIP STYLE | WEIGHT lbs./100 pcs. (g) |
|--------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|----------------------------|---------------|-----------|--------------------------|
| | MIN. in (mm) | MAX. in (mm) | | | | | | | | | | |
| PLT3I | .06 (1.5) | 3.00 (76) | .052 (1.3) | .145 (3.7) | .220 (5.6) | .180 (4.6) | .260 (6.6) | 11.4 (290) | 40 (178) | INTERMEDIATE | CURVED | .32 (145) |
| PLT4I | .06 (1.5) | 4.00 (102) | .052 (1.3) | .145 (3.7) | .220 (5.6) | .180 (4.6) | .260 (6.6) | 14.5 (368) | 40 (178) | INTERMEDIATE | CURVED | .40 (181) |
| PLT1S | .06 (1.5) | 1.00 (25) | .052 (1.3) | .190 (4.8) | .262 (6.7) | .220 (5.6) | .316 (8.0) | 4.8 (122) | 50 (222) | STANDARD | CURVED | .13 (58) |
| PLT1.5S | .06 (1.5) | 1.50 (38) | .052 (1.3) | .190 (4.8) | .262 (6.7) | .220 (5.6) | .316 (8.0) | 6.2 (157) | 50 (222) | STANDARD | CURVED | .26 (118) |
| PLT2S | .06 (1.5) | 1.88 (47.8) | .052 (1.3) | .190 (4.8) | .262 (6.7) | .220 (5.6) | .316 (8.0) | 7.4 (188) | 50 (222) | STANDARD | CURVED | .29 (132) |
| PLT2.5S | .06 (1.5) | 2.50 (63.5) | .052 (1.3) | .190 (4.8) | .265 (6.7) | .220 (5.6) | .337 (8.6) | 9.8 (249) | 50 (222) | STANDARD | CURVED | .38 (173) |
| PLT3S | .06 (1.5) | 3.00 (76) | .052 (1.3) | .190 (4.8) | .265 (6.7) | .220 (5.6) | .337 (8.6) | 11.5 (292) | 50 (222) | STANDARD | CURVED | .45 (204) |

NOTES:

*SEE www.panduit.com FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE, PART MATERIAL, PART COLOR AND ANY THIRD PARTY RECOGNITION OR COMPLIANCE.

DIMENSIONS IN PARENTHESES ARE IN METRIC UNITS

| REV | DATE | BY | CHK | APR | DESCRIPTION | ECN | TITLE | DRAWN BY | DATE | CHK | SCALE | SHT | SIZE |
|-----|------|----|-----|-----|-------------|-----|---|----------|----------|-----|-------|------------|------|
| | | | | | | | PAN-TY CABLE TIES - PLT SERIES | CEW | 12-27-84 | HVP | NONE | SHT 1 OF 1 | A |
| | | | | | | | CUSTOMER DRAWING | | | | | | |
| | | | | | | | ITEM REVISION NAME | | | | | | |
| | | | | | | | W10001CB/32 | | | | | | |
| | | | | | | | DATASET FILE NAME | | | | | | |
| | | | | | | | W10001CB/32 SS-5540 SH2_REV32 | | | | | | |
| | | | | | | | UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN (mm) | | | | | | |
| | | | | | | | .x ± --- .xxx ± .020 (.51) | | | | | | |
| | | | | | | | .xx ± .02 (.5) ANGLES ± --- | | | | | | |
| | | | | | | | THIRD ANGLE PROJECTION | | | | | | |
| | | | | | | | MATERIAL: | | | | | | |
| | | | | | | | NYLON 6.6 | | | | | | |
| | | | | | | | DRAWING NUMBER: | | | | | | |
| | | | | | | | SS-5540 SHEET 2 | | | | | | |

D101000DA/16