


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT PART NUMBER	MIN. CABLE LENGTH
NK5EPC3**Y	3 FT.
NK5EPC5**Y	5 FT.
NK5EPC7**Y	7 FT.
NK5EPC10**Y	10 FT.
NK5EPC14**Y	14 FT.
NK5EPC20**Y	20 FT.
NK5EPC1M**Y	1 METER
NK5EPC2M**Y	2 METERS
NK5EPC3M**Y	3 METERS
NK5EPC5M**Y	5 METERS

- NOTES:  
IDENTIFICATION:
- \*\*1. SEE CURRENT NETKEY CATALOG FOR PACKAGE QUANTITIES AND AVAILABLE COLORS.
  - 2. SEE CATALOG FOR A COMPLETE LIST OF PARTS APPLICABLE FOR USE WITH THIS PART.
  - △ B. TERMINATED WITH (8-POSITION) MODULAR PLUGS ON BOTH ENDS PER T568A.
  - 4. CONSTRUCTED WITH 4-PAIR/24 AWG STRANDED UTP CAT 5e NON-PLENUM PATCH CABLE.
  - 5. MATERIAL:  
PLUG: POLYCARBONATE

△ C MODULAR PLUG

△ A PLUG POSITION ONE

△ D T568A WIRING SCHEME

PLUG POSITION	CABLE WIRE
1	WHITE GREEN
2	GREEN
3	WHITE ORANGE
4	BLUE
5	WHITE BLUE
6	ORANGE
7	WHITE BROWN
8	BROWN

MODEL FILENAME	D35123CT_CAT5100_07	SIZE	A
DRAWING FILENAME	M02479LL_DC299_00B.PRT		
TITLE	NETKEY CATEGORY 5e PATCH CORD CUSTOMER DRAWING		
	PANDUIT <sup>TM</sup> CORP. TINLEY PARK, ILL 60477	I.I. NUMBER	
	THIRD ANGLE PROJECTION	PRODUCT SPEC	
	ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED.	WORK INSTRUCTION	
	DIMENSIONAL TOLERANCES ARE: (.X) ±.03 (.XXX) ±.005 (.XX) ±.01 ANGLES ± 1°	SCALE	NONE
DRAWN BY	NER	REVIEW DRAWING NUMBERS	PART NO.
DATE	3-21-06		NK5EPC**Y
CHK'D	WJC		DRAWING NO.
			02479-299

REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP	OTH
1	5-29-07	BJN	EJH	D. ADDED T568A WIRING SCHEME C. MODULAR WAS PANDUIT B. ADDED NOTES 3-5 A. ADDED METRIC LENGTHS	02479-299		REGA		
R	3-21-06	NER	WJC	RELEASED TO PRODUCTION	02479-299		RMD		