




THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART NO.	PACKAGE QTY	MAX BUNDLE DIAMETER	LENGTH "L" +/- .3" [7]
MRS1.5H-L6	50	1.5" [38]	10.6" (269)
MRS2H-L6	50	2.0" [51]	12.2" (310)
MRS4H-L6	50	4.0" [102]	18.5" (470)
MRS6H-L6	50	6.0" [152]	24.8" (630)




SECTION A - A
SCALE 8:1

NOTES:

- APPLICATION TOOLS - MTRTH & PTRT
- MINIMUM LOOP TENSILE STRENGTH - 400 LBS. (1780 NEWTONS) WHEN TESTED ON A 1.5" MANDREL
- [] DENOTES DIMENSION IN MILLIMETERS
- TOLERANCES:

.XXX = ±.010 [.25]	.XX = ±.02 [.5]
.X = ±.03 [.8]	ANGLES = ±2°
- MATERIAL: 316 STAINLESS STEEL

04A	10/09	MIM	SKB	REVISED PART LENGTHS FOR IMPROVED APPLICATION TOOL PERFORMANCE
REV	DATE	BY	CHK	DESCRIPTION

		TM	
		TINLEY PARK, ILLINOIS	
METAL TIE - HEAVY SERIES RETAINED TENSION - 360° RADIAL SEAL 316 STAINLESS STEEL - CUSTOMER DRAWING			
DRAWN BY JAMB	CHK'D EJD	SCALE 2:1	DRAWING NO. N41228BS_DC