


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART NO.	MAX. BUNDLE DIA.	PACKAGE QTY.	LENGTH +/- .3" [ 7 ]
MLT4EH15-LP316	4" [ 102 ]	50	17.1" [ 434 ]
MLT6EH15-LP316	6" [ 152 ]	50	23.4" [ 594 ]
MLT8EH15-LP316	8" [ 203 ]	50	29.7" [ 754 ]
MLT10EH15-LP316	10" [ 254 ]	50	35.9" [ 912 ]
MLT12EH15-0316	12" [ 305 ]	25	42.2" [ 1072 ]

ⓑ



NOTES:

1. APPLICATION TOOLS - ST3MT & RT2HT
2. MINIMUM LOOP TENSILE STRENGTH - 700 LBS. (3115 NEWTONS) WHEN TESTED ON A 3" MANDREL.
3. BRACKETS [ ] DENOTES DIMENSION IN MILLIMETERS
4. TOLERANCES:
  - .XXX = ±.010 [ .25 ]
  - .XX = ±.02 [ .5 ]
  - .X = ±.03 [ .8 ]
5. MATERIAL: 316 STAINLESS STEEL

Ⓐ

BROKEN EDGES TO ELIMINATE SHARPNESS

SECTION A - A  
SCALE: 4x

N41158BS\_DC/02A

O2A	10/08	JAMB	SKB	ORIG FILE SPEC WAS S41158_02. NOTE 1: APPLICATION TOOL RTIHT REPLACED BY RT2HT				<p>PANDUIT CORP. TINLEY PARK, ILLINOIS</p> <p>METAL LOCKING TIE EXTRA HEAVY DUTY 316 STAINLESS STEEL CUSTOMER DRAWING</p>
02	5/06	JAMB	SKB	ⓑ ADDED PARTS MLT10EH15-LP316 & MLT12EH15-0316 TO TABLE.	SS00179	---	---	
01	8/04	JAMB	DPN	Ⓐ REMOVED "AISI NO.5"	11907	CCH	JJB	
00	1/04	JAMB	DPN	RELEASED	11307	CCH	JJB	
REV	DATE	BY	CHK	DESCRIPTION	ECN #	PM	CUST	
		JAMB	DPN					DRAWING NO. N41158BS_DC SCALE 2x