

NEW! Turn-Tell™ Labels

A. System Overview

B1. Cable Ties

- Innovative label design allows labels to rotate for visibility from any angle, and for repositioning on the wire/cable to align legends and improve aesthetics

- Available in P1 Cassettes for the LS8E or LS8EQ printers and in computer printable rolls, for use with Easy-Mark™ Labeling Software and desktop thermal transfer printers

B2. Cable Accessories

- Labels can be easily installed on existing terminated wires and assemblies without disconnecting the wires/cables

- Temperature range: -40°F to 200°F (-40°C to 93°C)

B3. Stainless Steel Ties



C1. Wiring Duct

C2. Surface Raceway

| Part Number | Part Description | Width | | Length | | Print-On Area Height | | Min. Cable O.D. | | Max. Wire O.D. | | Std. Pkg. Qty. | Std. Ctn. Qty. |
|--------------------|------------------------------------|-------|------|--------|-------|----------------------|------|-----------------|-----|----------------|------|----------------|----------------|
| | | In. | mm | In. | mm | In. | mm | In. | mm | In. | mm | | |
| R100X075V1T | White, 18 – 14 AWG wire/cable. | 1.00 | 25.4 | 0.75 | 19.1 | 0.25 | 6.4 | 0.12 | 3.1 | 0.16 | 4.1 | 2500 | 10000 |
| R100X125V1T | White, 12 – 10 AWG wire/cable. | 1.00 | 25.4 | 1.25 | 31.8 | 0.38 | 9.7 | 0.16 | 4.1 | 0.22 | 5.6 | 2500 | 10000 |
| R100X150V1T | White, Cat 5/5e/6 cable. | 1.00 | 25.4 | 1.50 | 38.1 | 0.50 | 12.7 | 0.22 | 5.6 | 0.28 | 7.11 | 2500 | 10000 |
| R100X150V2T | Blue, Cat 5/5e/6 cable. | 1.00 | 25.4 | 1.50 | 38.1 | 0.50 | 12.7 | 0.22 | 5.6 | 0.28 | 7.11 | 2500 | 10000 |
| R100X150V3T | Green, Cat 5/5e/6 cable. | 1.00 | 25.4 | 1.50 | 38.1 | 0.50 | 12.7 | 0.22 | 5.6 | 0.28 | 7.11 | 2500 | 10000 |
| R100X150V7T | Red, Cat 5/5e/6 cable. | 1.00 | 25.4 | 1.50 | 38.1 | 0.50 | 12.7 | 0.22 | 5.6 | 0.28 | 7.11 | 2500 | 10000 |
| R100X150V8T | Yellow, Cat 5/5e/6 cable. | 1.00 | 25.4 | 1.50 | 38.1 | 0.50 | 12.7 | 0.22 | 5.6 | 0.28 | 7.11 | 2500 | 10000 |
| R100X225V1T | White, 8 – 4 AWG wire/cable. | 1.00 | 25.4 | 2.25 | 57.2 | 0.75 | 19.1 | 0.28 | 7.1 | 0.39 | 9.9 | 2500 | 10000 |
| R100X225V2T | Blue, 8 – 4 AWG wire/cable. | 1.00 | 25.4 | 2.25 | 57.2 | 0.75 | 19.1 | 0.28 | 7.1 | 0.39 | 9.9 | 2500 | 10000 |
| R100X225V3T | Green, 8 – 4 AWG wire/cable. | 1.00 | 25.4 | 2.25 | 57.2 | 0.75 | 19.1 | 0.28 | 7.1 | 0.39 | 9.9 | 2500 | 10000 |
| R100X225V7T | Red, 8 – 4 AWG wire/cable. | 1.00 | 25.4 | 2.25 | 57.2 | 0.75 | 19.1 | 0.28 | 7.1 | 0.39 | 9.9 | 2500 | 10000 |
| R100X225V8T | Yellow, 8 – 4 AWG wire/cable. | 1.00 | 25.4 | 2.25 | 57.2 | 0.75 | 19.1 | 0.28 | 7.1 | 0.39 | 9.9 | 2500 | 10000 |
| R100X400V1T | White, 2 AWG – 250 MCM wire/cable. | 1.00 | 25.4 | 4.00 | 101.6 | 1.00 | 25.4 | 0.39 | 9.9 | 0.95 | 24.1 | 1000 | 4000 |
| R200X225V1T | White, 8 – 4 AWG wire/cable. | 2.00 | 50.8 | 2.25 | 57.2 | 0.75 | 19.1 | 0.28 | 7.1 | 0.39 | 9.9 | 1000 | 4000 |
| R200X400V1T | White, 2 AWG – 250 MCM wire/cable. | 2.00 | 50.8 | 4.00 | 101.6 | 1.00 | 25.4 | 0.39 | 9.9 | 0.95 | 24.1 | 1000 | 4000 |

Order number of labels required in multiples of Std. Pkg. Qty.

D3. Grounding Connectors

Thermal Transfer Marker Plates

E1. Labeling Systems



- Non-adhesive marker plates offer crisp, clear legends with superior legibility
- Attachable in a horizontal or vertical orientation
- Available in a variety of colors and sizes

- Use with Panduit RMR4BL resin thermal transfer ribbon
- Temperature range: -58°F to 221°F (-50°C to 105°C)

E2. Labels

E3. Pre-Printed & Write-On Markers

| Part Number | Part Description | Width | | Height | | Print-On Area Width | | Std. Pkg. Qty. | Std. Ctn. Qty. |
|---------------------|--|-------|------|--------|------|---------------------|------|----------------|----------------|
| | | In. | mm | In. | mm | In. | mm | | |
| M300X100Y6T* | Yellow, thermal transfer marker plate. | 3.00 | 76.2 | 1.00 | 25.4 | 1.80 | 45.7 | 1 | 4 |
| M300X100Y7T | White, thermal transfer marker plate. | 3.00 | 76.2 | 1.00 | 25.4 | 1.80 | 45.7 | 1 | 4 |
| M300X050Y6T* | Yellow, thermal transfer marker plate. | 3.00 | 76.2 | 0.50 | 12.7 | 1.80 | 45.7 | 1 | 4 |
| M300X050Y7T | White, thermal transfer marker plate. | 3.00 | 76.2 | 0.50 | 12.7 | 1.80 | 45.7 | 1 | 4 |
| M200X100Y6T* | Yellow, thermal transfer marker plate. | 2.00 | 50.8 | 1.00 | 25.4 | 0.80 | 20.3 | 1 | 4 |
| M200X100Y7T | White, thermal transfer marker plate. | 2.00 | 50.8 | 1.00 | 25.4 | 0.80 | 20.3 | 1 | 4 |
| M200X050Y6T* | Yellow, thermal transfer marker plate. | 2.00 | 50.8 | 0.50 | 12.7 | 1.07 | 27.3 | 1 | 4 |
| M200X050Y7T | White, thermal transfer marker plate. | 2.00 | 50.8 | 0.50 | 12.7 | 1.07 | 27.3 | 1 | 4 |

*Other colors available, replace Y6 with AC (Blue), AE (Green), AF (Gray), AG (Orange), and AI (Red).
Order number of marker plates required in multiples of Std. Pkg. Qty.

F. Index