THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	250 STR/FLEX
Wire Type	Stranded Copper: Class G, H, I, K, M, Locomotive
Wire Strip Length	1-1/16 in.
Stud Size	3/8 in.
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	YELLOW
Panduit Die Index No. on Barrel	P62
Alternate Industry Die Index No. ( ) on Barrel	(16)

CERTIFIED

LISTED
Wire Connector





						PANDUIT CORP. TINLEY PARK, ILLINOIS
						LCAX250-38H-X Copper Lug - One-Hole, Standard Flex Barrel, 45° Angle Tongue
00	6/03	CJW	SAC	RELEASED	10850	
REV	**DATE**	**BY**	**CHK**	**DESCRIPTION**	**ECN**	**SCALE** N/A **DRAWING NO / CAD FILE** LCAX250-38H-CUST