

HSTTK Kynar* Heat Shrink 4 Foot Pieces

- Applications include insulating and protecting wires and cables
- Excellent chemical and abrasion resistance
- Use in high temperature or solvent rich environment
- Voltage: 600 V
- Shrink ratio: 2:1
- Flammability: Meets UL 224 VW-1
- Mil Spec: AMS-DTL-23053/8
- Temperature range: -67°F to 347°F (-55°C to 175°C)
- For dry locations
- Material: Clear Cross-linked Polyvinylidene Fluoride (PVDF)



| Part Number | Nominal Diameter | | Min. Expanded I.D. | | Max. Recovered I.D. | | Nominal Recovered Wall Thickness | | Std. Pkg. Qty. |
|---------------|------------------|------|--------------------|------|---------------------|------|----------------------------------|-----|----------------|
| | In. | mm | In. | mm | In. | mm | In. | mm | |
| HSTTK05-48-Q | 0.046 | 1.2 | 0.046 | 1.2 | 0.023 | 0.6 | 0.010 | 0.3 | 25 |
| HSTTK06-48-Q | 0.063 | 1.6 | 0.063 | 1.6 | 0.031 | 0.8 | 0.010 | 0.3 | 25 |
| HSTTK09-48-Q | 0.093 | 2.4 | 0.093 | 2.4 | 0.046 | 1.2 | 0.010 | 0.3 | 25 |
| HSTTK12-48-Q | 0.125 | 3.2 | 0.125 | 3.2 | 0.062 | 1.6 | 0.010 | 0.3 | 25 |
| HSTTK19-48-Q | 0.187 | 4.8 | 0.187 | 4.8 | 0.093 | 2.4 | 0.010 | 0.3 | 25 |
| HSTTK25-48-Q | 0.250 | 6.4 | 0.250 | 6.4 | 0.125 | 3.2 | 0.012 | 0.3 | 25 |
| HSTTK38-48-Q | 0.375 | 9.5 | 0.375 | 9.5 | 0.187 | 4.8 | 0.012 | 0.3 | 25 |
| HSTTK50-48-5 | 0.500 | 12.7 | 0.500 | 12.7 | 0.250 | 6.4 | 0.012 | 0.3 | 5 |
| HSTTK75-48-5 | 0.750 | 19.1 | 0.750 | 19.1 | 0.375 | 9.5 | 0.017 | 0.4 | 5 |
| HSTTK100-48-5 | 1.00 | 25.4 | 1.00 | 25.4 | 0.500 | 12.7 | 0.019 | 0.5 | 5 |

*KYNAR is a registered trademark of Atofina Chemicals, Inc.

HSTTVA Heat Shrink 4 Foot and 6 Inch Pieces

- Applications include insulating and protecting wires and cables
- Flexible tubing with an adhesive inner wall which seals and protects components from moisture and corrosion
- Voltage rating: 600 V
- Shrink ratio: 2:1
- Flammability: Outer wall flame retardant
- Mil Spec: AMS-DTL-23053/4 Class 2
- Temperature range: -67°F to 230°F (-55°C to 110°C)
- For damp locations
- Material: Adhesive lined black cross-linked Polyolefin



| Part Number | Nominal Diameter | | Min. Expanded I.D. | | Max. Recovered I.D. | | Nominal Recovered Wall Thickness | | Std. Pkg. Qty. |
|--------------------------|------------------|------|--------------------|------|---------------------|------|----------------------------------|-----|----------------|
| | In. | mm | In. | mm | In. | mm | In. | mm | |
| 4' (1.22m) Pieces | | | | | | | | | |
| HSTTVA12-48-Q | 0.125 | 3.2 | 0.125 | 3.2 | 0.062 | 1.6 | 0.021 | 0.5 | 25 |
| HSTTVA19-48-Q | 0.187 | 4.8 | 0.187 | 4.8 | 0.093 | 2.4 | 0.023 | 0.6 | 25 |
| HSTTVA25-48-Q | 0.250 | 6.4 | 0.250 | 6.4 | 0.125 | 3.2 | 0.029 | 0.7 | 25 |
| HSTTVA38-48-Q | 0.375 | 9.5 | 0.375 | 9.5 | 0.187 | 4.8 | 0.029 | 0.7 | 25 |
| HSTTVA50-48-5 | 0.500 | 12.7 | 0.500 | 12.7 | 0.250 | 6.4 | 0.030 | 0.8 | 5 |
| HSTTVA75-48-5 | 0.750 | 19.1 | 0.750 | 19.1 | 0.375 | 9.5 | 0.035 | 0.9 | 5 |
| HSTTVA100-48-5 | 1.00 | 25.4 | 1.00 | 25.4 | 0.500 | 12.7 | 0.042 | 1.1 | 5 |
| HSTTVA150-48-5 | 1.50 | 38.1 | 1.50 | 38.1 | 0.750 | 19.1 | 0.047 | 1.2 | 5 |

Table continues on page C3.36

A. System Overview

B1. Cable Ties

B2. Cable Accessories

B3. Stainless Steel Ties

C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

D1. Terminals

D2. Power Connectors

D3. Grounding Connectors

E1. Labeling Systems

E2. Labels

E3. Pre-Printed & Write-On Markers

E4. Permanent Identification

E5. Lockout/Tagout & Safety Solutions

F. Index